Canvas extensions

Define the contract, state, and allowed actions

Today's outcome

Build one delivery-readiness canvas in the Copilot app.

Record:

- the contract;
- one direct update;
- one agent-requested update;
- one rejected update and its recovery.

You need the Copilot app and the built-in `/create-canvas` skill. If project scope is unavailable, use user scope.

Choose the right customization

Need	Use
Repository convention	Instructions
Repeatable procedure	Skill
Specialist behavior	Custom agent
External tool or data	MCP server
Shared interactive artifact	Canvas
Packaged customizations	Plugin

Use a canvas when people and an agent need to inspect or change the same visible state.

Canvas anatomy

```
shared state
  ├─ human actions in the interface
  ├─ agent-callable capabilities
  └─ validation before every change
```

The contract names all four parts before implementation starts.

Worked contract

Part	Delivery-readiness rule
State	item, status, review flag, evidence
Status	`planned`, `in-progress`, `review`, `ready`
Human actions	set status, flag review, add evidence
Agent capabilities	read board, update one named item, list flagged items
Validation	known item, accepted status, evidence before `ready`

Keep authority narrow

Allowed:

- read the current board;
- update one named item;
- list items flagged for review.

Out of scope:

- deployment;
- external writes;
- credentials;
- hidden data imports;
- broad actions such as "manage the project."

Prepared demo inputs

ID	Item	Start state	Evidence
DOC-101	Draft operator guide	`planned`	none
API-204	Add retry metric	`in-progress`	test log
WEB-318	Check empty state	`review`	preview

Demo sequence

1. Run the local contract tests.
2. Create the canvas from the worked prompt.
3. Move `WEB-318` to `ready` with a visible control.
4. Ask the agent to move `API-204` to `review`.
5. Ask for `DOC-101` to move to `ready`.
6. Show the rejection, add evidence, and retry.

Creation prompt

```
/create-canvas

Create a delivery-readiness canvas from @prepared-items.json.
Use the contract in @canvas-contract.md.
People can add evidence and update one item.
Copilot can read the board, update one named item, and list review flags.
Reject unknown items or statuses. Require evidence before ready.
Do not connect external systems.
```

Use project scope when `.github/extensions` is allowed. Otherwise use user scope.

Two paths, one state

Path	Result
Human control	The item visibly changes in the canvas
Agent capability	The named item changes and the response matches the canvas

If the response and visible state disagree, stop and inspect the artifact.

Rejection is part of the design

Request:

```
Move DOC-101 to ready.
```

Expected:

```
Rejected: evidence is required before ready.
```

The state stays unchanged and the message names the rule.

Recovery keeps the rule

1. Add synthetic evidence to `DOC-101`.
2. Retry the same transition.
3. Check that `ready` is now accepted.
4. Record the state before, the rejection, the correction, and the state after.

Review the generated extension

Check:

- state fields and defaults;
- visible actions;
- agent-callable capabilities;
- dependencies and persisted data.

Remove anything the contract did not request.

Source of truth

The canvas is a working artifact, not a system of record.

If another system owns the data, label the canvas as a projection and keep external writes out of scope.

Lab handoff

Use one contract and one prepared data set for the full two hours.