

Orchestrate Agents and Workstreams

Product and Delivery Teams | Intermediate

Session 23 | 3 hours

Agenda

Segment	Time
Parent objective and workstreams	8 min
Child-session contracts	10 min
Monitor and intervene	10 min
Live orchestration demonstration	12 min
Review and consolidate	12 min
Lab handoff	8 min

Required access

- `/orchestrate` or an approved equivalent is required.
- The tool must create and coordinate live child sessions.
- Confirm that you can open, steer, and stop each child.
- `/spawn` alone does not meet the lesson goal.

Stop and resolve access if orchestration is unavailable.

No role-play, prepared-result, offline, or static completion route is available.

Product state: September 23, 2026

- `/orchestrate` is a documented GitHub Copilot app skill.
- `/spawn` creates a focused child session.
- `/usage` opens plan usage and rate-limit details.
- Commands vary by context.
- **My work** may appear under a renamed session or work surface.

Confirm the current command picker before the session.

One parent objective

Decide whether the Service Request Portal release is ready for review.
Produce a short evidence record. Do not change production or publish claims.

The parent owns scope, routing, review, and the final decision.

Independent workstreams

ID	Question	Packet
WS-01	Which user - visible changes are supported?	Release notes
WS-02	What does support need before launch?	Readiness checklist
WS-03	What could block release?	Risk register
WS-04	Which approved answers can we prepare?	Stakeholder FAQ

Parallel work needs clean boundaries. Sequence hidden dependencies.

Child-session contract

Goal: One bounded question

Inputs: Approved, sanitized sources

Return: Findings, evidence, gaps, recommendation

Do not: Change systems or invent facts

Stop when: Access, scope, usage, or evidence becomes unsafe

Reviewer: Named human owner

The result packet is the deliverable.

Start live orchestration

```
/orchestrate Prepare release-review evidence for the Service Request Portal.  
Use the four workstreams in the approved plan. Keep them independent.  
Require one result packet per workstream. Obey every stop condition.
```

Confirm that GitHub Copilot created the expected child sessions.

Monitor the work

Use **My work**, sessions, agents, or the current equivalent.

Check:

- status and elapsed time;
- evidence gathered;
- usage against the guard;
- scope drift or blocked access;
- whether the packet is ready.

Intervene deliberately

Signal	Action
Safe and on scope	Wait
Safe work needs correction	Redirect
Restricted data, excess usage, or broken boundary	Stop
Contract met	Accept
Unsupported or unsafe result	Reject
Human authority required	Escalate

Stopping weak work is a valid management decision.

Live demonstration

1. Start four child sessions through GitHub Copilot orchestration.
2. Open the live session list.
3. Redirect an unsupported claim.
4. Stop a restricted-data request.
5. Accept evidence-backed work.
6. Record the human decision.

Do not substitute prepared packets when a live run fails.

Evidence before fluency

Review each packet for:

- scope;
- source references;
- boundary compliance;
- open questions;
- a usable recommendation.

A polished answer with no evidence is still a rejection.

One shared record

Child sessions return packets to the parent.

```
Parent objective
|-- WS-01 packet
|-- WS-02 packet
|-- WS-03 packet
`-- WS-04 packet
    |
    Human review
    |
    Release-readiness record
```

One owner edits the final record.

Human approval remains the gate

Record:

- accepted evidence;
- rejected claims and reasons;
- unresolved owners and dates;
- **Go**, **Conditional go**, or **No-go**.

Copilot coordinates work. It does not receive release authority.

Session 16 is different

Session 16	Session 23
Optional Squad framework	Built-in app orchestration
Persistent roles and routing	Temporary workstreams
Team setup and shared memory	Result packets and review
Advanced implementation	Manager-led delivery practice

No custom-agent construction or Squad implementation in this session.

Lab deliverable

- Orchestration plan with live child-session identifiers
- Management action for each child session
- Live result packets
- Acceptance or rejection for every result
- Release-readiness record with human approval

Azure Boards may use MCP or the browser. GitHub Copilot must perform the orchestration.