# Orchestrate agents and workstreams

Product and delivery teams, or developers after Session m2-05

Session m7-05 | 3 hours

# Agenda

| Segment | Time |
| --- | --- |
| Parent objective and boundaries | 10 min |
| Minimal workstream plan | 10 min |
| Monitor and intervene | 12 min |
| Live demonstration | 13 min |
| Review and lab handoff | 15 min |

# Required access

- `/orchestrate` must create and coordinate live child sessions.
- Product route: GitHub MCP must read the selected issues.
- Developer route: local project read access and Python 3.10 or later.
- You must be able to open, redirect, and stop child sessions.

**Stop if orchestration or the selected route's inputs are unavailable.**

# Choose one lab route

| Route | Inputs | Result |
| --- | --- | --- |
| Product and delivery | Four live GitHub issues | Parent result used by Session m7-06 |
| Developer | Local evaluator, tests, synthetic PR snapshot | Separate implementation, coverage, and PR conclusions |

Each route takes 120 minutes. Developers need Session m2-05, not Sessions m7-01 to m7-04.

# One parent objective

Review the four approved status-visibility issues and return one reviewed result for each.

The parent owns scope and review.

# Keep the plan small

Each workstream needs:

- a question with a clear scope;
- approved inputs;
- a stop condition;
- a reviewer.

The orchestration surface already holds session links, status, timing, and usage.

# Four independent workstreams

| Workstream | Question |
| --- | --- |
| Public mapping | Is the mapping ready for approval? |
| Requester status | Is the issue ready for implementation review? |
| Empty and stale states | Are fallback states testable? |
| Access boundary | Is the approved evidence ready? |

Move shared questions back to the parent.

# Developer workstreams

| Question | Input |
| --- | --- |
| Does implementation meet the behavior contract? | Brief and evaluator |
| What do tests prove or miss? | Brief, tests, and evaluator |
| Is the supplied PR ready? | Brief and PR snapshot |

Children read the same fixed inputs. They do not wait for one another or edit.

# Practise steering

Redirect the test reviewer after its first answer:

```
Check criterion 5. Does the test prove sorted reason codes, the exact complete
reason list, or both? Do not edit files.
```

Inspect the revised answer. A follow-up question does not prove the first answer was wrong.

# Reconcile the readiness claim

The synthetic author says: "Local tests pass, so the PR is READY."

Check the actual snapshot:

- required `integration-tests` failed;
- blocking thread `R1` is unresolved.

Check the parent's decision against the snapshot. Do not manufacture conflicting child answers. Local success does not override PR blockers.

# Start live orchestration

```
/orchestrate Use the four workstreams in my approved plan. Keep them independent.
Each result must answer its question, cite approved inputs, state unresolved
gaps, and give a recommendation. Obey each stop condition.
```

# Monitor on the platform

| Signal | Action |
| --- | --- |
| Safe and on scope | Wait |
| Safe work needs correction | Redirect |
| A boundary is crossed | Stop |
| The result meets the plan | Accept |
| The result lacks support | Reject |
| Human authority is required | Escalate |

Do not maintain a second status log.

# Review each result

- Does it answer the assigned question?
- Does it use only approved issue evidence?
- Did it obey the stop condition?
- Are gaps listed?
- Is the recommendation supported?

Reject answers that lack supporting sources.

# The parent result is the handoff

The reviewed result:

- links findings to live GitHub issues;
- shows rejected claims;
- names gaps and owners;
- recommends the next follow-up.

Session m7-06 reads this result and the live issues.

# The human keeps authority

Copilot coordinates work. A person reviews results and approves any issue update, publication, or release statement.

# Session m5-01 is different

| Session m5-01 | Session m7-05 |
| --- | --- |
| Persistent roles and routing | Temporary workstreams |
| Optional framework setup | Built-in orchestration |
| Shared memory | Live issue evidence |

# Lab deliverable

1. Approved orchestration plan
2. Live child-session results
3. Reviewed parent result linked to live issues

Keep progress on the orchestration surface. Do not copy it into a delivery-status form or copy session identifiers.

For developers, use the developer plan and reviewed parent result instead of live issues. Include the actual redirection, rejected or unresolved claims, and observed usage.