Rectangling Panoramic Images via Warping

Kaiming He, Microsoft Research Asia Huiwen Chang, ITCS, Tsinghua University Jian Sun, Microsoft Research Asia

SIGGRAPH 2013

Motivation


- Limitation of digital camera
- Make the scene more descriptive

Problem Definition

- How to find the feature points of an image
- Errors when matching the feature points
- Find a better method to warp the image to a rectangle region

- Step1. Find the feature points of all input images.
- Step2. Match the feature points of two consecutive images and merge them all into a big panorama.


 Step3. Mesh-free Local warping: warp the image into a rectangle by Seam Carving Algorithm. That is a DP method to fill up all missing pixels.



 Step4. Draw meshes on image in step 3 and warp it back to the original image. Record the translation of each mesh point.







(d) mesh warped backward


 Step5. Mesh-free Global warping: Optimize the energy of each mesh points by alternating algorithm. The energy function is:

$$E(v, \{\theta_{\rm m}\}) = E_s(V) + \lambda_L E_L(V, \{\theta_{\rm m}\}) + \lambda_B E_B(V)$$


V can be optimized by fixing θ_m and solving a linear system. θ_m can be optimized by fixing V and minimize:

$$\min_{\theta_m} \sum_{j \in bin(m)} \left\| C_j(\theta_m e_{q(j)} \right\|^2$$

• Step6. Stretch the image and post-processing.









(c) after stretching reduction

Expected Results - Image 1





Expected Results - Image 2





References

Rectangling Panoramic Images via Warping, 2013 http://kaiminghe.com/publications/sig13pano.pdf

Seam segment carving: retargeting images to irregularly-shaped image domains, 2012

https://projet.liris.cnrs.fr/imagine/pub/proceedings/ECCV-2012/papers/7577/75770314.pdf

Image Alignment and Stitching: A Tutorial, 2006 https://dl.acm.org/doi/10.1561/0600000009

Image warps for artistic perspective manipulation, 2010 https://dl.acm.org/doi/abs/10.1145/1833349.1778864