

Init 容器

init 模板

```
apiVersion: v1
kind: Pod
metadata:
  name: myapp-pod
  labels:
    app: myapp
spec:
  containers:
  - name: myapp-container
    image: busybox
    command: ['sh', '-c', 'echo The app is running! && sleep 3600']
    initContainers:
    - name: init-myservice
      image: busybox
      command: ['sh', '-c', 'until nslookup myservice; do echo waiting for myservice; sleep 2; done;']
    - name: init-mydb
      image: busybox
      command: ['sh', '-c', 'until nslookup mydb; do echo waiting for mydb; sleep 2; done;']
```

```
kind: Service
apiVersion: v1
metadata:
  name: myservice
spec:
  ports:
  - protocol: TCP
    port: 80
    targetPort: 9376
---
kind: Service
apiVersion: v1
metadata:
  name: mydb
spec:
  ports:
  - protocol: TCP
    port: 80
    targetPort: 9377
```

检测探针 - 就绪检测

readinessProbe-httpget

```
apiVersion: v1
kind: Pod
metadata:
  name: readiness-httpget-pod
  namespace: default
spec:
  containers:
    - name: readiness-httpget-container
      image: wyanglinux/myapp:v1
      imagePullPolicy: IfNotPresent
      readinessProbe:
        httpGet:
          port: 80
          path: /index1.html
        initialDelaySeconds: 1
        periodSeconds: 3
```

检测探针 - 存活检测

livenessProbe-exec

```
apiVersion: v1
kind: Pod
metadata:
  name: liveness-exec-pod
  namespace: default
spec:
  containers:
    - name: liveness-exec-container
      image: hub.atguigu.com/library/busybox
      imagePullPolicy: IfNotPresent
      command: ["/bin/sh", "-c", "touch /tmp/live ; sleep 60; rm -rf /tmp/live; sleep 3600"]
      livenessProbe:
        exec:
          command: ["test", "-e", "/tmp/live"]
        initialDelaySeconds: 1
        periodSeconds: 3
```

livenessProbe-httpget

```
apiVersion: v1
kind: Pod
metadata:
  name: liveness-httpget-pod
  namespace: default
spec:
```

```

containers:
- name: liveness-httpget-container
  image: hub.atguigu.com/library/myapp:v1
  imagePullPolicy: IfNotPresent
  ports:
  - name: http
    containerPort: 80
  livenessProbe:
    httpGet:
      port: http
      path: /index.html
    initialDelaySeconds: 1
    periodSeconds: 3
    timeoutSeconds: 10

```

livenessProbe-tcp

```

apiVersion: v1
kind: Pod
metadata:
  name: probe-tcp
spec:
  containers:
  - name: nginx
    image: hub.atguigu.com/library/myapp:v1
    livenessProbe:
      initialDelaySeconds: 5
      timeoutSeconds: 1
      tcpSocket:
        port: 80

```

启动、退出动作

```

apiVersion: v1
kind: Pod
metadata:
  name: lifecycle-demo
spec:
  containers:
  - name: lifecycle-demo-container
    image: nginx
    lifecycle:
      postStart:
        exec:
          command: ["/bin/sh", "-c", "echo Hello from the postStart handler > /usr/share/message"]
      preStop:
        exec:

```

```
command: ["/bin/sh", "-c", "echo Hello from the post-stop handler >  
/usr/share/message"]
```

~~post-stop~~
prestop

这个没法演示，
pod都死了