Reem portfolio env

The portfolio needs 14 environment variables in production: 12 required and 2 optional. Put them in `.env.local` for local work and in Vercel under Project Settings, Environment Variables.

This file lists names and where each value comes from, never the secret values themselves. Keep real secrets out of chat, email and Git. A blank template is in `.env.example`.

Variables

Key	What it is	Where the value comes from	Required
`DATABASE_URL`	Neon Postgres connection	Neon console, Connect, the pooled string (host contains `-pooler`)	Yes
`AUTH_SECRET`	Signs admin login sessions	Generate: `openssl rand -base64 32`	Yes
`ADMIN_EMAIL`	The one admin login email	Your choice, currently `reemfathima66@gmail.com`	Yes
`ADMIN_PASSWORD_HASH`	Hashed admin password	Run `npm run admin:hash -- "your password"`, copy the line it prints	Yes
`AWS_ENDPOINT_URL_S3`	Neon object storage endpoint	Neon console, Object storage, Connect	Yes
`AWS_ACCESS_KEY_ID`	Storage access key	Neon console, Object storage, Connect	Yes
`AWS_SECRET_ACCESS_KEY`	Storage secret key	Neon console, Object storage, Connect	Yes
`AWS_REGION`	Storage region	Shown with the endpoint, `ap-southeast-1`	Yes
`S3_BUCKET`	Bucket name	The bucket you created, `uploads`	Yes
`NEXT_PUBLIC_TURNSTILE_SITE_KEY`	Contact form spam check, public key	Cloudflare dashboard, Turnstile, your site	Yes
`TURNSTILE_SECRET_KEY`	Contact form spam check, secret key	Same Turnstile site, secret key	Yes
`NEXT_PUBLIC_SITE_URL`	Live site address, no trailing slash	Your domain, for example `https://yourname.com`	Yes

Key	What it is	Where the value comes from	Required
`NEXT_PUBLIC_ADMIN_TZ`	Time zone for admin dates	Defaults to `Asia/Kolkata`	No
`DB_POOL_MAX`	Max database connections	Defaults to 10 on Neon, 1 locally	No

Notes

- **Rotate anything pasted into chat.** The first Neon database password was shared in a conversation, so reset it in Neon and use the new connection string.
- **Local and Vercel are separate.** Vercel does not read `.env.local`. Add every key above to Vercel, then redeploy.
- **Local database.** If `DATABASE_URL` points at `127.0.0.1`, the app uses the local test database. Switch it to the Neon string to work against real data.
- **Restart after changes.** A running server reads these values only when it starts.
- **Password hash.** The hash is base64 text, so it pastes safely into Vercel. Changing the admin password means generating a new hash and updating this one variable.
- **Storage is private.** The bucket is not public. The app reads from it and serves images at `/files/...`, so no public URL variable is needed.
- **Region.** `vercel.json` runs the site in Singapore (`sin1`), next to the Neon database.