VOLTWISE

Electric Vehicle Driving Range Optimization

Using Physics-Informed Battery Digital Twin and ML Ensembles

Advanced Machine Learning Lab - CAT II Mini Project

M.Sc. AI & ML, Coimbatore Institute of Technology, Coimbatore

Abstract

VoltWise presents a simple and explainable machine learning framework for electric vehicle (EV) driving range prediction and battery health estimation. The system utilizes 81,000+ real-world battery telemetry records covering 5,000 driving trips across varying weather, speed, and driving styles. Battery State of Health (SOH) and Remaining Useful Life (RUL) are estimated using a physics-informed degradation model based on thermal and cycle stress. In parallel, driving range is predicted using a weighted regression ensemble combining Random Forest, Gradient Boosting (GBDT), and an Optuna-tuned XGBoost model. The pipeline includes outlier cleaning, domain feature engineering, and SHAP-based feature interpretation. Compared with baseline linear regression, the tuned XGBoost model reduces prediction error by 56.3%, achieving a Mean Absolute Error (MAE) of 9.68 km and an R^2 score of 0.9589. The system is packaged with a FastAPI backend and an interactive dashboard for practical testing.

1. Problem Definition and Objectives

Standard on-board vehicle dashboards estimate driving range using static average energy consumption, which frequently causes severe prediction errors during extreme cold or hot weather, high air-conditioning usage, and aggressive driving styles [1], [2]. Simultaneously, lithium-ion battery packs lose storage capacity over time due to ambient temperature shifts and repeated charge-discharge cycles [3]. Most traditional machine learning range predictors assume the battery is in factory-new condition, completely ignoring capacity fade.

VoltWise resolves this critical gap by combining a physical battery digital twin with machine learning range prediction. The core objectives are: (1) clean and curate an EV telemetry dataset with outlier filtering and domain-specific feature engineering; (2) estimate battery State of Health (SOH) and Remaining Useful Life (RUL) using physical degradation laws; (3) train and compare machine learning regressors (Linear Regression, Random Forest, GBDT, and XGBoost) to forecast real-world driving range; (4) identify which vehicle and ambient factors most influence range using SHAP feature attributions; and (5) provide a simple FastAPI REST service and an interactive interface for real-time testing.

2. Dataset and Preprocessing

The project uses real-world telemetry data containing 81,000+ sensor readings processed into 5,000 distinct trip cycles with 14 vehicle and environmental features. Sensor anomalies, charging noise, and extreme current spikes were clipped using the standard 1.5x IQR rule. The dataset was partitioned 70% for training, 15% for validation, and 15% for final evaluation using a stratified protocol. All continuous inputs were standardized strictly on training data statistics to prevent data leakage.

Table 1. Dataset summary

Variable / Dataset	Value	Role
Telemetry observations	81,000+ sensor records	Battery voltage, current, and temperature telemetry
Driving trip instances	5,000 trips	Input observations for range regression modeling
Vehicle & weather features	14 attributes	Speed, SOC, temperature, humidity, wind, elevation, AC
Engineered features	40+ attributes	Usable energy, weather severity index, interaction terms
Train / validation / test	70% / 15% / 15%	Stratified evaluation protocol (3,500 / 750 / 750 trips)
Target variable	Real range (km)	Continuous ground-truth target for regression

Key engineered features include Usable Energy (E_{usable} = Capacity * SOH * SOC) and a Weather Severity Index combining precipitation, headwind velocity, and ambient temperature deviations from the optimal 22 deg C operating window.

3. VoltWise System Architecture

The VoltWise architecture employs a dual-branch processing pipeline combining physical degradation kinetics with data-driven regression trees:




Figure 1. VoltWise pipeline: dual-branch processing, ensemble prediction, and output generation.

The physics digital twin calculates cumulative battery capacity loss (D) and State of Health (SOH) based on calendar aging days, full equivalent cycle count, and operating temperature T (deg C) accelerated by Arrhenius kinetics:

$$D = (k_cal * days + k_cyc * cycles) * exp(k_temp * (T - 25) / 25) \quad (1)$$

$$SOH = max(0.70, 1.0 - D) \quad (2)$$

Empirical calibration parameters are set to k_{cal} = 0.00015 day^{-1}, k_{cyc} = 0.00028 cycle^{-1}, and thermal coefficient k_{temp} = 0.0693. Remaining Useful Life (RUL) represents estimated calendar days until the battery reaches the standard automotive retirement threshold (SOH = 0.70). Driving range (y_{pred}) is synthesized by combining individual model outputs:

$$y_pred = 0.35 * y_RF + 0.35 * y_GBDT + 0.20 * y_XGB + 0.10 * y_Linear \quad (3)$$

4. Machine Learning Methodology

Four machine learning regressors are evaluated: (A) Ordinary Least Squares Linear Regression as a baseline, (B) Random Forest regressor with 200 trees and bootstrap sampling, (C) Gradient Boosted Decision Trees (GBDT) with 250 sequential estimators optimizing residual errors at learning rate 0.05, and (D) an optimized XGBoost model. A weighted blending ensemble (E) combines all four model outputs.

Hyperparameter optimization is performed using Optuna across 50 trials on the validation split [5]. The search space tunes the number of trees (100-500), maximum tree depth (3-8), learning rate (0.01-0.20), and subsample ratio (0.6-1.0) to directly minimize validation Mean Absolute Error (MAE). The best-performing configuration selected depth=5, learning_rate=0.04, and L2 regularization lambda=1.5. Model accuracy is evaluated using MAE, Root Mean Squared Error (RMSE), and coefficient of determination (R^2 score). Model explainability is provided through SHAP (SHapley Additive exPlanations) values [6].

5. Results and Comparative Analysis

The experimental dataset was partitioned into three distinct subsets with no temporal or vehicle overlap:

Table 2. Dataset partition summary

Partition	Samples	Description
Training set (70%)	3,500 trips	Model parameter learning and tree split construction
Validation set (15%)	750 trips	Optuna hyperparameter optimization and blending weight tuning
Test set (15%)	750 trips	Final evaluation on unseen, held-out vehicle telemetry

Table 3. Test-set model comparison (evaluated on held-out test set)

Model Architecture	MAE (km)	RMSE (km)	R2 Score	Latency	Rank
A. Linear Regression (Baseline)	22.144	29.774	0.8112	< 1 ms	5
B. Random Forest	17.642	24.201	0.8752	12 ms	4
C. Gradient Boosting (GBDT)	11.875	17.026	0.9383	4 ms	3
D. XGBoost (Optuna Tuned)	**9.685**	**13.887**	**0.9589**	**2 ms**	**1 (Best)**
E. Weighted Blending Ensemble	12.962	18.488	0.9272	18 ms	2




Figure 2. Model comparison: MAE error reduction and R^2 score across baseline and ensemble models.

Detailed Key Findings and Performance Analysis:

1. Significant Error Reduction: The Optuna-tuned XGBoost model achieved a Mean Absolute Error of 9.685 km and an R^2 of 0.9589 on the test partition. This performance corresponds to a **56.3% reduction in error** relative to standard Linear Regression (MAE 22.144 km). Gradient Boosting (GBDT) also proved strong with an MAE of 11.875 km, demonstrating that non-linear decision boundaries are essential for modeling non-linear battery discharge behavior.

2. Real-Time Inference Latency: Single-sample inference latency for XGBoost is approximately 2 ms, compared to 12 ms for Random Forest and 18 ms for the weighted blending ensemble. This confirms that XGBoost is exceptionally well-suited for high-frequency deployment directly on edge automotive microcontrollers and in-vehicle telematics units where compute cycles and RAM are constrained.

3. Physics Digital Twin Integration: Traditional range prediction algorithms estimate range purely from instantaneous energy consumption. By injecting SOH and usable capacity from the physics digital twin into the feature matrix, the model properly penalizes range predictions on aged battery packs, avoiding catastrophic battery depletion before reaching a charging station.

4. Blending Ensemble Robustness: While single-model XGBoost attained the lowest absolute error, the 4-model weighted ensemble (MAE 12.962 km, R^2 0.9272) provides valuable regularization against sensor outliers, ensuring robust fallbacks under anomalous driving profiles.

5. Environmental Degradation Dynamics: Telemetry evaluation under extreme weather demonstrates that driving at -10 deg C increases energy draw by 28% compared to standard 22 deg C conditions. In contrast, high-speed highway cruising above 90 km/h increases aerodynamic drag losses quadratically, underscoring the necessity of dynamic environmental inputs.

Feature Importance and Model Interpretability:

To verify model trustworthiness and understand feature contributions, Tree SHAP was computed across the test instances:




Figure 3. SHAP feature importance ranking: Usable capacity, SOC, speed, and ambient temperature dominance.

SHAP Interpretability Insights: Battery Usable Capacity, State of Charge (SOC), Vehicle Speed, and Ambient Temperature account for over 78% of the total predictive power. Ambient temperature exhibits pronounced non-linear effects: cold temperatures (-10 deg C) reduce predicted range by up to 28% due to elevated internal cell resistance and cabin heating loads, while moderate temperatures (20-25 deg C) maximize efficiency.

6. Deployment and System Architecture

The complete predictive pipeline is packaged for practical hard-copy demonstration and real-world deployment:

1) **FastAPI REST Service:** Production-ready backend with Pydantic schema validation enforcing physical input bounds (temperature between -20 deg C and 50 deg C; SOC between 0% and 100%). Provides modular endpoints for real-time range estimation, SOH calculation, and safe charging advice.

2) **Containerization:** Packaged using a reproducible Dockerfile containing the lightweight Python runtime, dependencies, and serialized model weights.

3) **Interactive Dashboard:** An intuitive web interface allows operators and drivers to dynamically simulate trip variables, temperature shifts, and payload changes, observing instantaneous range predictions and battery health indicators.

7. Conclusion and Future Scope

VoltWise demonstrates that integrating a physical battery degradation digital twin with machine learning regression significantly improves EV driving range prediction accuracy. The Optuna-tuned XGBoost model achieved an MAE of 9.685 km and an R^2 score of 0.9589, representing a 56.3% error reduction over baseline linear methods with an inference latency of just 2 ms.

Future Scope: Future extensions include deploying Long Short-Term Memory (LSTM) recurrent networks for continuous cell voltage tracking, and integrating road elevation gradients from digital mapping services for dynamic elevation-aware energy optimization.

References

[1] C. Bingham, C. Walsh, and S. Carroll, 'Impact of driving characteristics on electric vehicle energy consumption,' *SAE Int. J. Alt. Power*, vol. 1, no. 1, pp. 132-141, 2012.

[2] Y. Bi, D. Chrenko, F. Gao, and D. Paire, 'Estimating vehicle electric consumption using machine learning algorithms,' in *Proc. IEEE Transportation Electrification Conf. and Expo (ITEC)*, 2020, pp. 450-455.

[3] J. Schmalstieg, S. Kabitz, M. Ecker, and D. U. Sauer, 'A holistic aging model for Li(NiMnCo)O2 based 18650 lithium-ion cells,' *Journal of Power Sources*, vol. 257, pp. 325-334, 2014.

[4] T. Chen and C. Guestrin, 'XGBoost: A scalable tree boosting system,' in *Proc. 22nd ACM SIGKDD Int. Conf. Knowl. Discov. Data Min.*, 2016, pp. 785-794.

[5] T. Akiba, S. Sano, T. Yanase, T. Ohta, and M. Koyama, 'Optuna: A next-generation hyperparameter optimization framework,' in *Proc. 25th ACM SIGKDD Int. Conf. Knowl. Discov. Data Min.*, 2019, pp. 2623-2631.

[6] S. M. Lundberg and S.-I. Lee, 'A unified approach to interpreting model predictions,' in *Proc. Advances in Neural Information Processing Systems (NeurIPS)*, 2017, pp. 4765-4774.