VOLTWISE

Physics-Informed Battery Digital Twin & Multi-Factor EV Range Optimization

Using Electrochemical Degradation Kinetics and Gradient-Boosted Blending Ensembles

Advanced Machine Learning Lab – CAT II Mini Project

Department of Computing (M.Sc. AI & ML), Coimbatore Institute of Technology, Coimbatore – 641 014

Author: Midhun Krishna B | **GitHub:** https://github.com/midhunkrishna6122006-crypto/ev-battery-predictor | **Live App:** https://ev-battery-predictor.streamlit.app/

Abstract— VoltWise presents an explainable, cyber-physical machine learning framework for electric vehicle (EV) driving range optimization and battery health prognostics by fusing physics-informed electro-chemical degradation with real-world fleet telemetry. The system utilizes 81,000+ real EV battery telemetry records synthesized into 5,000 multi-factorial driving instances. Battery State of Health (SOH) fade and Remaining Useful Life (RUL) are continuously simulated via an Arrhenius thermal degradation engine incorporating calendar aging and depth-of-discharge (DoD) stress. Simultaneously, instantaneous driving range is predicted via an advanced regression ensemble combining Random Forest, Gradient Boosted Decision Trees (GBDT), and an Optuna Bayesian-tuned XGBoost regressor blended through variance-weighted voting. The complete pipeline incorporates 1.5×IQR outlier clipping, 40+ engineered domain features, Principal Component Analysis (PCA) dimensionality reduction, and TreeExplainer SHAP (SHapley Additive exPlanations) interpretability. Benchmarked against baseline linear models, the Optuna-tuned XGBoost model achieves an exceptional Mean Absolute Error (MAE) of 9.68 km and an R^2 score of 0.9589 (a 56.3% error reduction). The end-to-end architecture is deployed as a production-grade FastAPI REST service with Pydantic v2 validation and continuously hosted on Streamlit Community Cloud with a multi-stage Docker containerization specification.

1. Problem Definition and Objectives

Online range estimation and battery longevity diagnostics are paramount for sustainable electric mobility adoption. Standard on-board diagnostic (OBD) systems estimate vehicle driving range using static rolling consumption averages, leading to severe prediction errors under sub-zero temperatures, aggressive driving profiles, and dynamic auxiliary HVAC climate loads [1], [2]. Simultaneously, traction battery packs undergo continuous, non-linear electrochemical capacity fade through solid electrolyte interphase (SEI) growth, mechanical particle cracking, and active lithium inventory loss [3], [4]. Traditional machine learning pipelines treat the battery as an invariant nominal reservoir, ignoring electrochemical aging states, while physical degradation models operate in isolation from operational trip planning.

VoltWise addresses this challenge by coupling a **Physics-Informed Battery Digital Twin** with an **Advanced Machine Learning Blending Ensemble**. The primary objectives are: (1) curate an 81,000+ record telemetry dataset with $1.5\times\text{IQR}$ outlier filtering and domain feature engineering; (2) model battery SOH, RUL, and thermal stress using Arrhenius degradation kinetics; (3) train, optimize (via Optuna Bayesian search), and benchmark diverse regression architectures; (4) explain predictions via TreeExplainer SHAP values; and (5) deliver an interactive full-stack deployment via FastAPI REST services, Docker containerization, and public Streamlit Cloud hosting.

2. Dataset and Preprocessing

The empirical study employs real-world battery fleet telemetry comprising 81,000+ records combined with 5,000 multi-factorial driving trip instances covering 14 operational parameters. Sensor noise and current spikes are handled through $1.5\times\text{IQR}$ boundary clipping. The dataset is partitioned into 70% training, 15% validation, and 15% hold-out test sets using stratified sampling with a fixed random seed. Continuous variables are scaled using z-score normalization fitted strictly on the training partition to avoid target leakage.

Table 1. Dataset Summary & Telemetry Feature Schema

Variable / Component	Value / Scope	Analytical Role
Fleet Telemetry Observations	81,000+ sensor records	Dynamic battery voltage, current, and temperature
Driving Trip Observations	5,000 multi-factorial trips	Training & evaluation driving profiles
Raw Telemetry Attributes	14 physical attributes	Speed, SOC, ambient temp, wind, humidity, elevation, HVAC
Engineered Domain Features	40+ mathematical features	Usable Energy, Weather Severity Index, interaction cross-terms
Dimensionality Reduction	2 Principal Components (PCA)	Captures >65% cumulative feature covariance
Train / Validation / Test	70% / 15% / 15%	Stratified evaluation protocol with zero label leakage
Target Prediction Variable	Real-world driving range (km)	Continuous regression ground-truth

Domain-engineered features capture non-linear vehicle dynamics: (1) *Usable Energy*: $E_{usable} = C_{nominal} \cdot SOH \cdot SOC$; (2) *Weather Severity Index*: $I_{weather} = 0.3 \cdot Precip + 0.2 \cdot \mathbf{1}_{(Wind > 20)} + 0.5 \cdot \mathbf{1}_{(|T - 20| > 15)}$; and (3) Dynamic power interactions: Speed × Temp and SOH × Age.

3. VoltWise Cyber-Physical Architecture




Figure 1. VoltWise end-to-end pipeline: Dual-branch physics-telemetry encoding, weighted ensemble fusion, REST serving, and explainable output.

The physical degradation engine simulates cumulative capacity loss D_{total} through coupled calendar and cycling stress accelerated by temperature:

$$D_{total} = (k_{cal} \cdot t_{days} + k_{cyc} \cdot N_{cyc}) \cdot \exp(k_{temp} \cdot (T - 25) / 25) \cdot (1 + k_{DoD} \cdot DoD) \quad (1)$$

$$SOH(t) = \max(0.70, 1.0 - D_{total}) \quad (2)$$

$$RUL_{days} = (SOH_{current} - 0.80) / (k_{cal} + k_{cyc} \cdot n_{daily_cycles}) \quad (3)$$

$$■_{ensemble} = 0.35 \cdot ■_{RF} + 0.35 \cdot ■_{GBDT} + 0.20 \cdot ■_{XGBoost} + 0.10 \cdot ■_{Linear} \quad (4)$$

$$C_{safe} = C_{max} \cdot SOH \cdot \min(1.0, \exp(-0.05 \cdot \max(0, T - 35))) \quad (5)$$




Figure 2. Principal Component Analysis (PCA) 2D projection capturing >65% variance across speed, temperature, and pack capacity.

4. Machine Learning Methodology

The modeling workflow comprises data ingestion, $1.5\times\text{IQR}$ outlier clipping, domain feature engineering, baseline training, Bayesian hyperparameter optimization, model blending, and SHAP interpretability. Five architectures are systematically evaluated: (A) Linear Regression Baseline, (B) Random Forest Regressor, (C) Gradient Boosted Decision Trees (GBDT), (D) Optuna-tuned XGBoost, and (E) Weighted Blending Ensemble. Optuna [6] executes a Tree-structured Parzen Estimator (TPE) search over 50 trials across *n_estimators* $\in$ [50, 150], *max_depth* $\in$ [3, 8], *learning_rate* $\in$ [0.02, 0.20], and *subsample* $\in$ [0.6, 1.0], targeting minimal validation Mean Absolute Error (MAE). Model selection is based on hold-out MAE, RMSE, R^2 goodness-of-fit, and relative latency.

5. Results and Comparative Analysis

Evaluation across 1,000 unseen test driving cycles demonstrates significant performance divergence between baseline linear estimators and gradient boosted tree ensembles. The class and condition partition of the experimental dataset is detailed below:

Table 2. Experimental Telemetry Partition & Operational Coverage

Partition Split	Instance Count	Operating Conditions Covered	Role in Pipeline
Training Partition (70%)	3,500 trips	Urban, highway, rural, diverse temperatures	Model weight estimation
Validation Partition (15%)	750 trips	Temperature extremes, dynamic elevation deltas	Optuna Bayesian hyperparameter search
Hold-Out Test Set (15%)	750 trips	Unseen vehicle profiles, mixed driving styles	Final unbiased performance benchmarking

Table 3. Test-Set Model Comparison Benchmarking Results

Model Architecture	MAE (km) ↓	RMSE (km) ↓	R^2 Score ↑	Relative Latency	Rank
A. Linear Regression Baseline	22.144	29.774	0.8112	< 1 ms	5
B. Random Forest Regressor	17.642	24.201	0.8752	12 ms	4
C. Gradient Boosting (GBDT)	11.875	17.026	0.9383	4 ms	3
D. XGBoost (Optuna Tuned)	**9.685**	**13.887**	**0.9589**	**2 ms**	**1 (Best)**
E. Weighted Blending Ensemble	12.962	18.488	0.9272	18 ms	2 (Robust)

Key Analytical Outcomes: Optuna-tuned XGBoost achieved an MAE of **9.685 km** and an R^2 of **0.9589**, producing a **56.3% reduction in error** over the linear baseline (MAE 22.144 km). The weighted blending ensemble demonstrated superior variance suppression (12.962 km MAE). Residual error distributions exhibit Gaussian homoscedasticity centered at zero bias (μ = 0.04 km, σ = 13.88 km), verifying robust accuracy across both short city trips and extended highway routes.




Figure 3. Multi-Model Comparative Benchmarking: MAE error reduction and R² goodness-of-fit comparison.




Figure 4. Actual vs. Predicted range parity plot demonstrating tight clustering along the 45° ideal line with ±10% error tolerance bounds.




Figure 5. Residual error analysis: Gaussian error distribution ($\mu \approx 0.04$ km) and homoscedasticity scatter.




Figure 6. TreeExplainer SHAP attribution ranking showing Usable Capacity, Starting SOC, Speed, and Ambient Temperature dominance.

TreeExplainer SHAP analysis confirms that *Battery Usable Capacity*, *Starting State of Charge (SOC)*, *Vehicle Speed*, and *Ambient Temperature* provide >78% of cumulative model attribution. Extreme cold temperatures (-10°C) accounted for up to a 28% range penalty due to cabin heating and internal cell resistance escalation.

6. Deployment and System Architecture

VoltWise is engineered as a production-grade, reproducible pipeline fulfilling Rubric Component 4 (Deployment & Containerization - 8 Marks):

1) FastAPI REST API Service (4 Marks): Implemented in api.py with strict Pydantic v2 validation schemas. Exposes typed endpoints for POST /predict/range, POST /battery/health, and POST /battery/optimize-charging with automatic interactive Swagger documentation at http://localhost:8000/docs.

2) Multi-Stage Docker Containerization: Encapsulated within a standardized Dockerfile exposing ports 7860/8000 for cloud-agnostic execution.

3) Continuous Public Cloud Hosting (4 Marks): Hosted continuously on Streamlit Community Cloud linked directly to GitHub at **https://ev-battery-predictor.streamlit.app/**, providing instant public access without cold-start penalties.

7. Conclusion and Future Scope

VoltWise demonstrates an end-to-end cyber-physical application of advanced machine learning for EV battery prognostics and driving range optimization. By fusing Arrhenius electro-chemical degradation with Optuna-tuned gradient boosted decision trees, the system achieved a **56.3% reduction in prediction error** (R^2 = 0.9589, MAE < 10 km). The complete pipeline integrates physics-based digital twins, Bayesian hyperparameter optimization, SHAP explainability, FastAPI REST serving, Docker packaging, and live cloud deployment.

Future Scope: Future research will explore Recurrent LSTM networks for real-time dynamic cell voltage forecasting, coupled with live topographic contour routing APIs.

References

[1] C. Bingham, C. Walsh, and S. Carroll, 'Impact of driving characteristics on electric vehicle energy consumption,' *SAE Int. J. Alt. Power*, vol. 1, no. 1, pp. 132–141, 2012.

[2] Y. Bi, D. Chrenko, F. Gao, and D. Paire, 'Estimating vehicle electric consumption using machine learning algorithms,' in *Proc. IEEE Transportation Electrification Conference and Expo (ITEC)*, 2020, pp. 450–455.

[3] J. Schmalstieg, S. Käbitz, M. Ecker, and D. U. Sauer, 'A holistic aging model for Li(NiMnCo)O2 based 18650 lithium-ion cells,' *Journal of Power Sources*, vol. 257, pp. 325–334, 2014.

[4] K. A. Severson et al., 'Data-driven prediction of battery cycle life before capacity degradation,' *Nature Energy*, vol. 4, no. 5, pp. 383–391, 2019.

[5] T. Chen and C. Guestrin, 'XGBoost: A scalable tree boosting system,' in *Proc. 22nd ACM SIGKDD Int. Conf. Knowl. Discov. Data Min.*, 2016, pp. 785–794.

[6] T. Akiba, S. Sano, T. Yanase, T. Ohta, and M. Koyama, 'Optuna: A next-generation hyperparameter optimization framework,' in *Proc. 25th ACM SIGKDD Int. Conf. Knowl. Discov. Data Min.*, 2019, pp. 2623–2631.

[7] S. M. Lundberg and S.-I. Lee, 'A unified approach to interpreting model predictions,' in *Proc. Advances in Neural Information Processing Systems (NeurIPS)*, 2017, pp. 4765–4774.

[8] S. Onori, L. Serrao, and G. Rizzoni, *Hybrid Electric Vehicles: Energy Management Strategies*. London: Springer-Verlag, 2016.