

ENGINEERING SUPPLIES

MCB 495

MICROCYCLONIC BAFFLE FILTER


January, 2020

Creating the highest quality kitchen ventilation equipment requires in-depth knowledge of a chef's needs, restaurant servicing, expertise in ventilation engineering, HVAC install and modern manufacturing. The MCB filter has been specifically engineered to meet the highest standard possible. The MCB filter is suitable for the demanding cooking situations. It is optimised for high filtration efficiency with low pressure loss. It is highly durable and suitable for machine washing due to its size and full stainless steel construction.



Details

- **High energy efficiency** is very important for kitchen ventilation because of the volumes of air involved.. The MCB filter achieves the highest levels of energy efficiency with cleverly calibrated surface area and internal geometry. The filter is made with opposing parabolic shaped corrugated compress,. This creates tangential intersections between air streams giving 7 primary vortices at a diameter up to 9mm in the centre of the filter (34,000 per square meter). High turbulence is generated with minimal energy. Oil is collected in the compress and drained down to the filter channel.
- **Ease of operation** is often overlooked but is very important for the successful hospitality business.
- **Durable** Heavy-duty stainless steel filters fit and can be **easily cleaned** in common commercial dishwashers.
- **Certified and fire tested filter.** AS1530 fire tested.
- **Air quality, 98.5% removal efficiency** using gravimetric determination to DIN 18869-5
- Best filtration to pressure loss ratio
- **Quiet** operation of a hood helps and reduces stress in the kitchen



EU MCB 495 Microcyclonic Baffle Filter

Model Number: N16i14

Dimensions	mm	Inch						
Length	495	19.48						
Width	50	1.97						
Height	254	10						
Airflow	L/s	CFM	Clean Resistance, Pa		Dirty Resistance, Pa			
Optimum	167	353	15		30			
Peak	230	487	25		50			
Maximum	330	699	36		85			
Particulate Filtration	25µ	10µ	5µ	1µ	0.5µ	0.3µ	Face Velocity	L/s
Laser spec.	100	92	79	85	88	58	1.78 m/s	167

Options Available

- Reduce weight and increase heat sensitivity change to aluminium
- Add UV catalytic coating

Weight

2Kg, 4.4lb

