TAPHOS-STICK FIELD VALIDATION CHECKLIST

Target Property: 9745 Morris Road, St. Francisville, LA (30.91° N, -91.28° W)
Operational Engine: Multi-Temporal Micro-Topographic Anomaly Tracker (M-TMAT)
Document Purpose: Pre-sweep hardware calibration & evidence safety protocol

1. Initial Gate Arrival & Environment Stabilization

- [ ] **Secure Property Access:** Verify legal clearance, warrant documentation, or explicit WFPSO escort prior to passing the property gate.
- [ ] **Record Baseline Met:** Log current ambient temperature, humidity, and cloud cover to account for dielectric shifts in topsoil.
- [ ] **Canopy Density Assessment:** Note overhead foliage thickness near the entry road to establish reference attenuation profiles for the M-TMAT sensor.

2. Hardware Boot & Telemetry Sync

- [ ] **Power-On Sequence:** Initiate the primary Taphos-Stick chassis and verify the battery charge is above 85% for stable multi-hour operation.
- [ ] **GNSS RTK Lock Check:** Confirm a minimum satellite count of 12+ and achieve a high-precision RTK 'Fix' status before moving.
- [ ] **JSON Stream Injection Test:** Run a 30-second loop using the local simulation telemetry dataset to confirm UI compass rendering, proximity indicators, and hexadecimal color-coded alert states match perfect heading alignments.

3. Micro-Topographic Calibration Loop

- [ ] **Flat Ground Zeroing:** Rest the unit on a known undisturbed, level surface near the boundary line to establish the local baseline zero index.
- [ ] **Delta-Z Sensor Verification:** Manually pass the sensor array over an explicit micro-topographic depression or small surface feature to confirm instantaneous response metrics update on the display.
- [ ] **Sky-View Factor Alignment:** Validate that the ambient occlusion shader auto-adjusts relative lighting curves as the device transitions under heavy loess bluff tree cover.

4. Targeted Ground-Truthing & Evidence Isolation

- [ ] **Target TA-01 Approach (Excavation):** Navigate directly along the 35.4° bearing. Confirm proximity flags shift to HIGH at exactly 50.2 feet from the reference house datum.
- [ ] **Target TA-02 Approach (Fill Mound):** Execute the secondary 242.1° line sweep. Monitor for positive delta-z spike indicators at 34.9 feet.

[ ] **Non-Invasive Delineation:** Pinpoint anomaly bounds using surface flags. **STRICT PROTOCOL: Do not break the soil horizon.** Maintain pristine subsurface layers for specialized forensic teams (GPR, HRD K9, or soil augering).

NOTICE AND LEGAL DISCLAIMER: This is for informational and simulation calibration purposes only. All on-site search or recovery procedures must be conducted exclusively under the jurisdiction and direct oversight of authorized law enforcement agencies. Incorrect field manipulation can permanently compromise fragile environmental and biological chain-of-custody baselines. AI responses may include mistakes.