Chapter 18

# Virtual-Circuit Networks: Frame Relay and ATM

18-1   FRAME RELAY

Frame Relay is a virtual-circuit wide-area network that was designed in response to demands for a new type of WAN in the late 1980s and early 1990s.

Topics discussed in this section:

Architecture
Frame Relay Layers
Extended Address
FRADs
VOFR
LMI

Figure 18.1 *Frame Relay network*

LAN

Router

Frame Relay network
(WAN)

To the rest of
the Internet

Router

Note

VCIs in Frame Relay are called DLCIs.

Figure 18.2 *Frame Relay layers*

Frame Relay operates only at the physical and data link layers.

# Figure 18.3 *Frame Relay frame*

C/R: Command/response
EA: Extended address
FECN: Forward explicit congestion notification

BECN: Backward explicit congestion notification
DE: Discard eligibility
DLCI: Data link connection identifier

Flag	Address	Information	FCS	Flag

DLCI	C/R	EA	DLCI	FECN	BECN	DE	EA
6 bits	1 bit	1 bit	4 bits	1 bit	1 bit	1 bit	1 bit

Frame Relay does not provide flow or error control; they must be provided by the upper-layer protocols.

Figure 18.4 *Three address formats*

DLCI		C/R	EA = 0
DLCI	FECN	BECN	DE	EA = 1

a. Two-byte address (10-bit DLCI)

DLCI		C/R	EA = 0
DLCI	FECN	BECN	DE	EA = 0
DLCI		0	EA = 1

b. Three-byte address (16-bit DLCI)

DLCI		C/R	EA = 0
DLCI	FECN	BECN	DE	EA = 0
DLCI			EA = 0
DLCI		0	EA = 1

c. Four-byte address (23-bit DLCI)

Figure 18.5 *FRAD*

18-2   ATM

Asynchronous Transfer Mode (ATM) is the cell relay protocol designed by the ATM Forum and adopted by the ITU-T.

Topics discussed in this section:

Design Goals
Problems
Architecture
Switching
ATM Layers

Figure 18.6 *Multiplexing using different frame sizes*

A cell network uses the cell as the basic unit of data exchange.
A cell is defined as a small, fixed-size block of information.

Figure 18.7 *Multiplexing using cells*

Figure 18.8 *ATM multiplexing*

Figure 18.9 *Architecture of an ATM network*

Figure 18.10 *TP, VPs, and VCs*

Figure 18.11 *Example of VPs and VCs*

Note

Note that a virtual connection is defined
by a pair of numbers:
the VPI and the VCI.

Figure 18.12 *Connection identifiers*

Figure 18.13 *Virtual connection identifiers in UNIs and NNIs*

a. VPI and VCI in a UNI

b. VPI and VCI in an NNI

# Figure 18.14 *An ATM cell*

Figure 18.15 *Routing with a switch*

Figure 18.16 *ATM layers*

# Figure 18.17 *ATM layers in endpoint devices and switches*

Figure 18.18 *ATM layer*

Figure 18.19 *ATM headers*

GFC: Generic flow control
VPI: Virtual path identifier
VCI: Virtual circuit identifier

PT: Payload type
CLP: Cell loss priority
HEC: Header error control

Figure 18.20 *AAL1*

Figure 18.21 *AAL2*

Figure 18.22 *AAL3/4*

CS header

CPI	Btag	BAsize
8 bits	8	16

CPI: Common part identifier
Btag: Beginning tag
BAsize: Buffer allocation size

CS trailer

AL	Etag	L
8 bits	8	16

AL: Alignment
Etag: Ending tag
L: Length

SAR header

ST	SN	MID
2	4	10

ST: Segment type
SN: Sequence number
MID: Multiplexing identifier

SAR trailer

| LI	CRC
6	10

LI: Length identifier
CRC: Error detector

Figure 18.23 *AAL5*

18-3   ATM LANs

ATM is mainly a wide-area network (WAN ATM); however, the technology can be adapted to local-area networks (ATM LANs). The high data rate of the technology has attracted the attention of designers who are looking for greater and greater speeds in LANs.

Topics discussed in this section:

ATM LAN Architecture
LAN Emulation (LANE)
Client/Server Model
Mixed Architecture with Client/Server

# Figure 18.24 *ATM LANs*

# Figure 18.25 *Pure ATM LAN*

Figure 18.26 *Legacy ATM LAN*

# Figure 18.27 *Mixed architecture ATM LAN*

Figure 18.28 *Client and servers in a LANE*

Figure 18.29 *Client and servers in a LANE*