

2. Models for Statistical Structured Prediction:

Probabilistic Graphical Models

2.1. Directed Graphical Models (Bayesian Networks)

- Generative models: HMM and PCFG

2.2. Undirected Graphical Models (Markov Random Fields)


- Discriminative Models: Conditional Random Fields

Probabilistic Graphical Models are an **elegant** framework that combines uncertainty (probabilities) and logical structure (independence constraints) to make simplifying assumptions about which variables affect which other variables.

These assumptions can often be represented graphically, leading to whole sets of models known collectively as **Graphical Models** (GMs)

Why do we **need** Graphical Models?

- GMs are the basis for the probabilistic approach to *Intelligent Systems*.
- GMs are a compact representation of joint probability distributions using graphs, constituting a perfect match between **Probability Theory** and **Graph Theory**.
- GMs allow us to abstract out the conditional independence relationships between the variables from the details of their parametric forms.
- GMs generalize to Neural Networks and Hidden Markov Models, among others.



[from K.P. Murphy, 2012]

Nodes represent random variables.

The **graph** represents a set of independences and factorizes a distribution.

Graphical models: taxonomy

- **Bayesian Networks** based on **Directed Graphs**.
- **Markov Random Fields** based on **Undirected Graphs**.

Key components

- **Inference**: deduce probability distributions from other given.
- **Learning**: obtain the probabilistic model from observations.

Applications

- Medical diagnosis, fault detection, ...
- **Computer Vision**: image segmentation, 3D reconstruction, scene analysis, ...
- **Natural Language Processing**: speech recognition, information extraction, machine translation, ...
- **Robotics**: planning, detection, ...

BNS: CONDITIONAL INDEPENDENCE

Representing knowledge through the notion of **conditional independence**


- Two events, a and b , are **(unconditionally) independent** and we denote it as $(a \perp b)$ if:

$$p(a, b) = p(a) \cdot p(b) \quad \text{or} \quad p(a | b) = p(a)$$

- Two events, a and b , are **conditionally independent** given an event c , and we denote it as $(a \perp b | c)$ if:

$$p(a | b, c) = p(a | c) \quad \text{or} \quad p(a, b | c) = p(a | c) \cdot p(b | c)$$


BNS: RULES OF CONDITIONAL AND UNCONDITIONAL INDEPENDENCE



Causal direction: $(a \perp b | c) \quad (a \not\perp b)$

$$P(a, b | c) = \frac{P(a)P(c | a)P(b | c)}{P(c)} = P(a | c)P(b | c)$$


but $P(a, b) \neq P(a)P(b)$



Common parent: $(a \perp b | c) \quad (a \not\perp b)$

$$P(a, b | c) = \frac{P(c)P(a | c)P(b | c)}{P(c)} = P(a | c)P(b | c)$$

but $P(a, b) \neq P(a)P(b)$



V-structure: $(a \not\perp b | c) \quad (a \perp b)$

$$P(a, b | c) \neq P(a | c)P(b | c)$$

$$\text{but } P(a, b) = \sum_c P(a)P(b)P(c | a, b) = P(a)P(b)$$

BNS: INFERENCE

The purpose is to estimate the posterior probability of some variable x from the joint distributions associated with a BN, given some evidence y (regardless of the values of the rest of the variables z).

$$P(x | y) = \frac{P(x, y)}{P(y)} \quad \text{con:} \quad P(x, y) = \sum_z P(x, y, z); \quad P(y) = \sum_{x, z} P(x, y, z);$$

The goal is to efficiently calculate $P(x, y)$ and $P(y)$.


- The usefulness of calculating the posterior probability.

Prediction.- What is the probability of observing a symptom knowing that the patient has a particular disease?

Diagnosis.- What is the probability that a particular disease is a correct diagnosis given some symptoms?

BNS: EXAMPLES (GENERATIVE MODELS)

Classifiers



Naive Bayes

- Predicting a single class y given a vector of features $\mathbf{x} = \{x_1, x_2, \dots, x_T\}$
- Assumption: once the class label is known all the features are independent


$$p(x_1, x_2, \dots, x_T, y) = p(y) \prod_{t=1}^T p(x_t | y)$$

BNS: EXAMPLES (GENERATIVE MODELS)

Sequential Prediction



Sequence Labeling



Markov model


$$p(x_1, x_2, \dots, x_T) = p(x_1) \cdot p(x_2|x_1) \cdot p(x_3|x_2) \dots = p(x_1) \prod_{t=1}^T p(x_t|x_{t-1})$$

(Bigram) Hidden Markov Model

$$P(x_1^T, y_1^T) = \prod_{t=1}^T q(y_t|y_{t-1}) \cdot e(x_t|y_t)$$

BAYESIAN NETWORKS: EXAMPLES (GENERATIVE MODELS)

Parsing



Probabilistic Context-Free Grammars

$$t_x = [S = \alpha_0 \xrightarrow{r_1} \alpha_1 \xrightarrow{r_2} \alpha_2 \dots \alpha_{m-1} \xrightarrow{r_m} \alpha_m = \mathbf{x}] \quad P(x_1^T, t_x) = \prod_{i=1 \dots m} P(r_i);$$

$$P(r_i) = P(Y_j Y_k | Y_i) \quad \text{or} \quad P(r_i) = P(X_l | Y_i)$$

MARKOV RANDOM FIELDS

Bayesian Networks cannot perfectly represent all distributions.


Markov Random Fields (MRF) are graphical models based on Undirected Graphs.

The **nodes** represent the random variables.

The **edges** represent some notion of probabilistic interaction between neighboring nodes. Edges show which variables depend on each other.

Example

[Kevin P. Murphy, 2012]



MARKOV RANDOM FIELDS


Conditional independence properties: **global Markov property** for MRFs

MRFs define conditional independence relationships via simple graph separation:

for sets of nodes A , B , and C , we say,

$$A \perp B | C \Leftrightarrow C \text{ separates } A \text{ from } B \text{ in the graph.}$$

Example:




$$\{1, 2\} \perp \{6, 7\} \mid \{3, 4, 5\}$$

MARKOV RANDOM FIELDS

Definitions: A **clique** of an undirected graph is a fully connected subgraph.
A **maximal clique** is a clique that is not a subgraph of any other clique.

Example:



Cliques: $\{1, 2\}; \dots \{1, 2, 3\}; \{2, 3, 5\}; \{2, 4, 5\}; \{3, 5, 6\}; \{4, 5, 6\} \dots \{4, 5, 6, 7\};$

No-cliques: $\{1, 2, 3, 5\}; \{2, 3, 4, 5, 6\}; \dots$

maximal cliques: $\{1, 2, 3\}; \{2, 3, 5\}; \{2, 4, 5\}; \{3, 5, 6\}; \{4, 5, 6, 7\};$

MARKOV RANDOM FIELDS: FACTORIZATION

Definition.- Let G be the undirected graph that underlies an MRF. A probability distribution P_G defines a factorization over G if it is associated with:

$$P_G(X_1, \dots, X_T) = \frac{1}{Z} \prod_{C \in Q} \psi_C(V_C)$$

Where,

$V = \{X_1, X_2, \dots, X_T\}$ is the set of random variables;

Q is the set of all the (maximal) cliques of G ;


V_C is the subset of variables from clique C ;

$\psi_C : Q \rightarrow \mathbb{R}^{>0}$ is the **potential function** for clique c , and

Z is a normalization factor (constant) defined as:

$$Z = \sum_{X_1, \dots, X_T} \prod_{C \in Q} \psi_C(V_C)$$

MARKOV RANDOM FIELDS: FACTORIZATION



Example $Q = \{ \{1, 2, 3\}; \{2, 3, 5\}; \{2, 4, 5\}; \{3, 5, 6\}; \{4, 5, 6, 7\}; \}$

$$P_G(1, 2, 3, 4, 5, 6, 7) = \frac{1}{Z} \psi_1(1, 2, 3) \cdot \psi_2(2, 3, 5) \cdot \psi_3(2, 4, 5) \cdot \psi_4(3, 5, 6) \cdot \psi_5(4, 5, 6, 7)$$

MRFs are more powerful than BNs but are more challenging to deal with computationally.

STRUCTURED PREDICTION: CRFs

Given $x = x_1, x_2, \dots, x_T \in \mathcal{X}^*$ and $y = y_1, y_2, \dots, y_T \in \mathcal{Y}^*$

➤ **Discriminative models: Conditional Random Fields (CRF)**

[Lafferty, McCallum, Pereira, 2001].

➤ Model parameters θ

➤ Compatibility function $\phi(x, y; \theta) \rightarrow \mathcal{R}$
that that gives high positive scores to compatibles pairs (x, y)

➤ Conditional distribution:

$$p(y | x; \theta) = \frac{\exp\{\phi(x, y; \theta)\}}{Z(x; \theta)}$$

Where

$$Z(x; \theta) = \sum_{y' \in \mathcal{Y}^*} \exp\{\phi(x, y'; \theta)\}$$

CRFs: COMPATIBILITY FUNCTIONS

Example [Carreras, 2011]

	1	2	3	4	5
x	Jack	London	went	to	Paris
y	PER	PER	-	-	LOC
y^1	PER	LOC	-	-	LOC
y^2	-	-	-	-	LOC

➤ (Bigram) Indicator Features

$$f_1(y_{t-1}, y_t, x_t) = \begin{cases} 1 & \text{if } x_t = \text{"London"} \text{ and } y_{t-1} = \text{PER and } y_t = \text{PER} \\ 0 & \text{otherwise} \end{cases}$$

e.g., $f_1(\text{PER}, \text{PER}, x_2) = 1$, and $f_1(\text{PER}, -, x_3) = 0$

➤ Other possible examples of indicator features:

$$\begin{aligned} f_1(\dots) &= 1 \text{ iff } x_t = \text{"London"} \text{ and } y_{t-1} = \text{PER and } y_t = \text{PER} \\ f_2(\dots) &= 1 \text{ iff } x_t = \text{"London"} \text{ and } y_{t-1} = \text{PER and } y_t = \text{LOC} \\ f_3(\dots) &= 1 \text{ iff } x_{t-1} = \sim/(\text{in}|\text{to}|\text{at})/ \text{ and } x_t = \sim/[\text{A-Z}]/ \text{ and } y_t = \text{LOC} \\ f_4(\dots) &= 1 \text{ iff } y_t = \text{LOC and } \text{WORLD_CITIES}(x_t) = 1 \\ f_5(\dots) &= 1 \text{ iff } y_t = \text{PER and } \text{FIRST_NAMES}(x_t) = 1 \end{aligned}$$

CRFs: FACTORED COMPATIBILITY FUNCTIONS

➤ Let $f(y_{i-1}, y_i, x_i)$ be a vector of features

$$(f_1(y_{i-1}, y_i, x_i), f_2(y_{i-1}, y_i, x_i), \dots, f_K(y_{i-1}, y_i, x_i))$$

➤ Given $f(\cdot)$ and let $\theta \in \mathcal{R}^K$ be a weight matrix

$$\begin{aligned} \phi(x, y; \theta) &= \sum_{t=1}^T \theta f(y_{t-1}, y_t, x_t) \\ &= \sum_{t=1}^T \sum_{k=1}^K \theta_k f_k(y_{t-1}, y_t, x_t) \end{aligned} \quad (1)$$

➤ Let $y_0 = \text{NULL}$, so the bigram $y_0 y_1$ is defined for $t = 1$.

➤ This factorization will allow efficient algorithms since if $y \neq y'$ share bigrams then they will share scores

CONDITIONAL RANDOM FIELDS

$$\begin{aligned} p(y|x; \theta) &= \frac{\exp\{\phi(x, y; \theta)\}}{Z(x; \theta)} \\ &= \frac{\exp\{\sum_{t=1}^T \sum_{k=1}^K \theta_k f_k(y_{t-1}, y_t, x_t)\}}{Z(x; \theta)} \end{aligned} \quad (2)$$

Where

$$Z(x; \theta) = \sum_{y' \in \mathcal{Y}^*} \exp \left\{ \sum_{t=1}^T \sum_{k=1}^K \theta_k f_k(y'_{t-1}, y'_t, x_t) \right\} \quad (3)$$

➤ Features $f(\cdot)$ are given (problem-dependent).

➤ $\theta \in \mathcal{R}^K$ are the parameters of the model.

➤ CRFs are log-linear models on the feature functions.

CRFs: THREE PROBLEMS

➤ **Inference:** Compute the probability of an output sequence y for x

$$p(y|x; \theta) = \frac{1}{Z(x; \theta)} \prod_{t=1}^T \exp \left\{ \sum_{k=1}^K \theta_k f_k(y_{t-1}, y_t, x_t) \right\}$$

➤ **Decoding:** predict the best output sequence for x

$$\arg \max_{y \in \mathcal{Y}^*} p(y|x; \theta) = \arg \max_y \prod_{t=1}^T \exp \left\{ \sum_{k=1}^K \theta_k f_k(y_{t-1}, y_t, x_t) \right\}$$

➤ **Parameter estimation:** learn parameters θ , given training data

$$\{(x^{(1)}, y^{(1)}), (x^{(2)}, y^{(2)}), \dots, (x^{(N)}, y^{(N)})\}$$

BIBLIOGRAPHIC REFERENCES

➤ Probabilistic Context-Free Grammars

- T.L.Booth and R.A.Thompson: [Applying Probability Measures to Abstract Languages](#). IEEE Trans. on Compututurs, 22(5):442–450. May 1973.
- C.S.Wetherell: [Probabilistic Languages: A Review and Some Open Questions](#). ACM Computing Surveys, 12(4):361–379. December 1980. doi:10.1145/356827.356829.
- [M.Collins](#): [Probabilistic Context-Free Grammars](#). Course notes,Columbia University, 2011.

➤ Graphical Models

- C.M.Bishop: [Pattern Recognition and Machine Learning](#). Chap.8: Graphical Models. Springer, 2006.
- D.Koller, N.Friedman, L.Getoor and B.Taskar: [Graphical Models in a Nutshell](#) in *An Introduction to Statistical Relational Learning*. MIT Press, 2007.

➤ Conditional Random Fields

- J.Lafferty, A.McCallum and F.C.N.Pereira: [Conditional Random Fields: Probabilistic Models for Segmenting and Labeling Sequence Data](#). ICMI:282-289. 2001.
- C.Sutton and A.McCallum: [An introduction to conditional random fields for relational learning](#) in *An Introduction to Statistical Relational Learning*. MIT Press, 2007.