
Stat 215A - Week 6

Some slides thanks to Rebecca Barter

Lab 2 check in

Any questions?

To do today

Lowess


Independent component analysis

Multidimensional scaling


Lo(w)ess - locally weighted scatterplot smoothing

Lowess


Local linear fit in this example,
but can fit higher order
polynomials



Lowess




Lowess



Lowess


Identify neighborhood to fit the polynomial.

Here span = 5



Lowess


Fit a weighted least squares line within the neighborhood



Lowess


Fit a weighted least squares line within the neighborhood

Higher weight given to points near the focal point (red)




Lowess

The first point of the regression lines is the fitted focal point (blue diamond)




Lowess

Move onto the new focal point and fit a different weighted regression line




Lowess

Fit a new local regression line




Lowess

So on and so forth...



Lowess



Loess - locally weighted scatterplot smoothing

Parameters to choose

- ❑ The **span/bandwidth**: size of the neighborhood.
- ❑ The **degree** of the local polynomial (previous slide degree = 1).
- ❑ The **weights** for the weight least squares.

Independent Component Analysis


Independent component analysis

Classic goal: separate the underlying speech signals each corresponding to an individual at a cocktail party




<http://tarynwilliford.com/wp-content/uploads/2010/12/RetroCocktailParty.jpg>

Independent component analysis: example




<https://www.quora.com/What-is-the-difference-between-PCA-and-ICA>

Independent component analysis: example



<https://www.quora.com/What-is-the-difference-between-PCA-and-ICA>

Independent component analysis: example



<https://www.quora.com/What-is-the-difference-between-PCA-and-ICA>

Independent component analysis

Goal of PCA

- ❑ **Compress the data** so that each dimension contains as much information as possible

Goal of ICA

- ❑ **Identify the independent parts** that make up the data

Independent component analysis

Goal of PCA

- ❑ Compress the data so that each dimension contains as much information as possible
- ❑ **Maximize variability** (second moment)

Goal of ICA

- ❑ Identify the independent parts that make up the data
- ❑ **Maximize kurtosis** (fourth moment)

Independent component analysis

Goal of PCA

- ❑ Compress the data so that each dimension contains as much information as possible
- ❑ Maximize variability (second moment)
- ❑ Each component is **orthogonal**

Goal of ICA

- ❑ Identify the independent parts that make up the data
- ❑ Maximize kurtosis (fourth moment)
- ❑ Each component is **statistically independent**, but not necessarily orthogonal

Independent component analysis

Goal of PCA

- ❑ Compress the data so that each dimension contains as much information as possible
- ❑ Maximize variability (second moment)
- ❑ Each component is orthogonal
- ❑ PCA **removes correlations**, but not higher order dependence

Goal of ICA

- ❑ Identify the independent parts that make up the data
- ❑ Maximize kurtosis (fourth moment)
- ❑ Each component is statistically independent, but not necessarily orthogonal
- ❑ ICA removes correlations and **higher order dependence**

Independent component analysis

Goal of PCA


- ❑ Compress the data so that each dimension contains as much information as possible
- ❑ Maximize variability (second moment)
- ❑ Each component is orthogonal
- ❑ PCA removes correlations, but not higher order dependence
- ❑ The **first few components** are most important

Goal of ICA

- ❑ Identify the independent parts that make up the data
- ❑ Maximize kurtosis (fourth moment)
- ❑ Each component is statistically independent, but not necessarily orthogonal
- ❑ ICA removes correlations and higher order dependence
- ❑ **All components** are equally important


Independent component analysis

PCA




Independent component analysis

PCA



ICA



Multidimensional scaling (MDS)

Multidimensional scaling

Suppose you knew the **distances** between all major US cities


Could you figure out the coordinate locations of each city?

Given a distance matrix, MDS tries to recover low-dimensional coordinates such that the distances are preserved

Multidimensional scaling

X	Boston	NYC	DC	Miami	Chicago	Seattle	San.Francisco	Los.Angles	Denver
Boston	0	206	429	1504	963	2976	3095	2979	1949
NYC	206	0	223	1308	802	2815	2934	2786	1771
DC	429	223	0	1075	671	2684	2799	2631	1616
Miami	1504	1308	1075	0	1329	2373	3053	2687	2037
Chicago	963	802	671	1329	0	2013	2142	2054	996
Seattle	2976	2815	2684	2373	2013	0	808	1131	1307
San Francisco	3095	2934	2799	3053	2142	808	0	379	1235
Los Angles	2979	2786	2631	2687	2054	1131	379	0	1059
Denver	1949	1771	1616	2037	996	1307	1235	1059	0

Multidimensional scaling



Multidimensional scaling

MDS moves objects around in the space defined (e.g. R^2) and checks how well the distances between the objects can be reproduced by the new configuration.

It wants to minimize goodness-of-fit measure call stress

$$stress = \sqrt{\frac{\sum (d_{ij} - \hat{d}_{ij})^2}{\sum d_{ij}^2}}$$

Multidimensional scaling: algorithm

Steps of a Classical MDS algorithm:

Classical MDS uses the fact that the coordinate matrix can be derived by **eigenvalue decomposition** from $B = XX'$. And the matrix B can be computed from proximity matrix D by using double centering.^[2]

Double centering means
subtracting the mean from
each row and column



1. Set up the squared proximity matrix $D^{(2)} = [d_{ij}^2]$
2. Apply double centering: $B = -\frac{1}{2}JD^{(2)}J$ using the **centering matrix** $J = I - \frac{1}{n}11'$, where n is the number of objects.
3. Determine the m largest **eigenvalues** $\lambda_1, \lambda_2, \dots, \lambda_m$ and corresponding **eigenvectors** e_1, e_2, \dots, e_m of B (where m is the number of dimensions desired for the output).
4. Now, $X = E_m\Lambda_m^{1/2}$, where E_m is the matrix of m eigenvectors and Λ_m is the **diagonal matrix** of m eigenvalues of B .

Classical MDS assumes **Euclidean** distances. So this is not applicable for direct dissimilarity ratings.

Exercise: implement MDS (mds.Rmd)