FAMILY OWNED & OPERATED SINCE 1961

65 years

MINI-FLEX CORPORATION

Mini-Flex Corporation

2026 METAL BELLOWS CATALOG

Complete Bellows Data List

PAGE 3 | PARTS -125, -138

MATERIAL KEY:
SS = STAINLESS STEEL 304, 304L, 316, 316L, 321, 347
I = INCONEL 600, 625, 718, X-750
N = NICKEL 200, NI-SPAN C-902
H = HASTELLOY X
M = MONEL 400, 404
BC = BERYLLIUM COPPER C17200
PB = PHOSPHOR BRONZE C52100
B = BRASS 70-30

Part Number	Conv. ID	Conv. OD	Wall	Neck 1 OD	Neck 2 OD	Neck 1 ID	Neck 2 ID	Neck 1 Length	Neck 2 Length	Conv. Free Length	Max. Deflect. Comp.	Spring Rate (lbs./ in.)	Eff. Area (sq.in.)	Squirm Rating (PSI)	Burst Rating (PSI)	# of Conv
BC-125-60-133	0.099	0.225	0.006	0.127	0.127	0	0	0.3	0.3	0.82	0.135	133	0.021	450	5100	28
BC-125-60-175	0.105	0.246	0.006	0.127	0.127	0	0	0.26	0.26	0.54	0.1	175	0.024	1000	5100	14
I600-125-60-380	0.101	0.224	0.006	0.127	0.127	0.114	0.115	0.3	0.3	0.46	0.053	380	0.02	3100	6600	16
I718-125-28-160	0.11	0.195	0.0028	0.127	0.127	0.12	0.12	0	0	0.27	0.052	160	0.0183	2300	4300	10
I718-125-28-190	0.11	0.195	0.0028	0	Cup	0	0	0	0	0	0	190*	0.0183	0	4500	8
I718-125-63-460	0.1	0.224	0.0063	0.127	0.127	0	0	0.3	0.3	0.46	0.06	460	0.02	TBD	10000	16
I718-125-63-13200	0.104	0.182	0.0063	0.127	0.126	0.113	0.113	0.125	0.125	0.05	0.005	13200	0.016	N/A	8500	2
I718-125-72-3600	0.103	0.19	0.0072	0.126	0.126	0.111	0.111	0.125	0.125	0.165	0.015	3600	0.0168	TBD	12600	7
I718-125-72-4000	0.103	0.19	0.0072	0.126	0.126	0.111	0.111	0.125	0.125	0.143	0.013	4600	0.0168	TBD	12600	6
I718-125-72-14300	0.102	0.181	0.0072	0.126	0.127	0.111	0.112	0.2	0.2	0.05	0.004	14300	0.016	N/A	12000	2
I718-125-72-21000	0.102	0.172	0.0072	0.126	0.127	0.111	0.112	0.2	0.2	0.05	0.004	21000	0.015	N/A	12000	2
AN-125-50-192	0.107	0.231	0.005	0.127	0.127	0	0	0.08	0.08	0.36	0.04	192	0.022	600	3400	14
PBA-125-50-68	0.104	0.229	0.005	0.127	0.127	0	0	0.1	0.1	0.8	0.13	68	0.022	480	3400	28
I718-138-40-160	0.124	0.205	0.004	0.14	0.14	0.132	0.132	0.04	0.04	0.84	0.105	160	0.021	TBD	6000	30
I718-138-40-850	0.124	0.205	0.004	0.14	0.14	0.132	0.132	0.06	0.06	0.125	0.02	850	0.021	TBD	6200	6

*All specs are measured in inches