FAMILY OWNED & OPERATED SINCE 1961

65 years

MINI-FLEX CORPORATION

Mini-Flex Corporation

2026 METAL BELLOWS CATALOG

Complete Bellows Data List

MATERIAL KEY:
SS = STAINLESS STEEL 304, 304L, 316, 316L, 321, 347
I = INCONEL 600, 625, 718, X-750
N = NICKEL 200, NI-SPAN C-902
H = HASTELLOY X
M = MONEL 400, 404
BC = BERYLLIUM COPPER C17200
PB = PHOSPHOR BRONZE C52100
B = BRASS 70-30

Part Number	Conv. ID	Conv. OD	Wall	Neck 1 OD	Neck 2 OD	Neck 1 ID	Neck 2 ID	Neck 1 Length	Neck 2 Length	Conv. Free Length	Max. Deflect. Comp.	Spring Rate (lbs./ in.)	Eff. Area (sq.in.)	Squirm Rating (PSI)	Burst Rating (PSI)	# of Conv
I718-159-58-760	0.139	0.258	0.0058	0.161	0.21	0.15	0.199	0.05	0.05	.270*	0.043	760**	0.031	3600	8700	7
I718-159-72-280	0.128	0.254	0.0072	0.161	0.161	0.1466	0.1466	0.35	0.35	1.23	0.175	280	0.028	1300	9800	35
I718-159-72-336	0.134	0.292	0.0072	0.161	0.163	0.147	0.149	0.25	0.25	0.58	0.098	336	0.036	2700	8800	14
I718-159-72-410	0.134	0.257	0.0072	0.161	0.161	0.1466	0.1466	0.1	0.1	0.78	0.1	360	0.03	2400	9350	22
I718-159-72-425	0.132	0.255	0.0072	0.161	0.161	0.1466	0.1466	0.1	0.1	.760*	.105**	425	0.03	3100	9300	22
I718-159-72-428	0.133	0.276	0.0072	0.161	0.163	0.147	0.15	0.25	0.25	0.535	0.088	428	0.033	3500	9300	14
I718-159-72-430	0.132	0.257	0.0072	0.161	0.21	0.146	0.196	0.07	0.07	0.76	0.105	430	0.03	3000	10750	21
I718-159-72-450	0.131	0.279	0.0072	0.161	0.163	0.147	0.149	0.13	0.13	0.55	0.05	450	0.033	TBD	10000	14
I718-159-72-1060	0.129	0.252	0.0072	0.161	0.161	0	0	0.15	0.15	0.41	0.039	1060	0.028	TBD	9600	12
I718-159-72-1235	0.131	0.248	0.0072	0.163	0.165	0.148	0.151	0.07	0.07	0.31	0.04	1235	0.028	2500	9600	9
I718-159-72-1300	0.129	0.275	0.0072	0.161	0.21	0.149	0.198	0.05	0.05	0.2	0.023	1400	0.032	4000+	9150	5
I718-159-72-2300	0.13	0.252	0.0072	0.161	0.162	0.148	0.149	0.04	0.04	0.155	0.025	2340	0.029	TBD	11000	5
I718-159-72-4900	0.133	0.247	0.0072	0.161	0.162	0.147	0.148	0.15	0.15	0.073	0.0128	4900	0.028	N/A	9300	2
I718-159-72-9800	0.147	0.245	0.0072	0.161	0.161	0.147	0.147	0.17	0.17	0.04	0.005	9800	0.03	N/A	9300	1
I718-159-82-597	0.13	0.257	0.0082	0.161	0.161	0.145	0.145	0.1	0.1	0.78	0.1	500	0.029	3300	10900	22
IX-159-50-160	0.135	0.248	0.005	0.161	0.161	0.151	0.151	0.15	0.15	1.12	0.15	160	0.029	TBD	6400	34
IX-159-50-250	0.136	0.268	0.005	0.161	0.163	0.151	0.153	0.25	0.25	0.54	0.087	250	0.032	2000	7000	14

*All specs are measured in inches