CSCI 3104 Fall 2021 Instructor: Profs. Grochow and Waggoner

Retake Token Quiz-Standard 3

	ue Date	
	ame	
St	rudent ID	49
C	Contents	
1	Instructions	1
2	Honor Code (Make Sure to Virtually Sign)	2
	Standard 3- Dijkstra's Algorithm	3
	3.1 Problem 2	3

1 Instructions

- The solutions **should be typed**, using proper mathematical notation. We cannot accept hand-written solutions. Here's a short intro to LATEX.
- You should submit your work through the **class Canvas page** only. Please submit one PDF file, compiled using this LATEX template.
- You may not need a full page for your solutions; pagebreaks are there to help Gradescope automatically find where each problem is. Even if you do not attempt every problem, please submit this document with no fewer pages than the blank template (or Gradescope has issues with it).
- You may not collaborate with other students. Copying from any source is an Honor Code violation. Furthermore, all submissions must be in your own words and reflect your understanding of the material. If there is any confusion about this policy, it is your responsibility to clarify before the due date.
- Posting to any service including, but not limited to Chegg, Discord, Reddit, StackExchange, etc., for help on an assignment is a violation of the Honor Code.
- You **must** virtually sign the Honor Code (see Section 2). Failure to do so will result in your assignment not being graded.

2 Honor Code (Make Sure to Virtually Sign)

Problem 1. • My submission is in my own words and reflects my understanding of the material.


- Any collaborations and external sources have been clearly cited in this document.
- I have not posted to external services including, but not limited to Chegg, Reddit, StackExchange, etc.
- \bullet I have neither copied nor provided others solutions they can copy.

I agree to the above, Michael Ghattas.	
--	--

3 Standard 3- Dijkstra's Algorithm

3.1 Problem 2

Problem 2. Consider the following directed, weighted graph G. Work through Dijkstra's algorithm using vertex **D** as the source. Clearly show both the **found distances** and **priority queue** at each iteration.



Answer:

- We begin on vertex **D**.
- Queue = [(D, 0)]Distances = $[(D, 0), (A, 2), (G, 5), (F, 7), (C, \infty), (B, \infty), (E, \infty)]$. We remove (D, 0) from the queue.
- Queue = [(A, 2), (G, 5), (F, 7)]Distances = $[(D, 0), (A, 2), (G, 5), (F, 7), (C, 8), (B, 5), (E, \infty)]$. We remove (A, 2) from the queue.
- Queue = [(B, 5), (G, 5), (F, 7), (C, 8)] Distances = [(D,0), (A,2), (G,5), (F,7), (C,7), (B,5), (E,6)]. We remove (B, 5) from the queue.
- Queue = [(G, 5), (E, 6), (F, 7), (C, 7)]Distances = (D, 0), (A, 2), (G, 5), (F, 7), (C, 7), (B, 5), (E, 6)]. We remove (G, 5) from the queue.
- Queue = [(E, 6), (F, 7), (C, 7)]Distances = [(D, 0), (A, 2), (G, 5), (F, 7), (C, 7), (B, 5), (E, 6)]. We remove (E, 6) from the queue.
- Queue = [(F, 7), (C, 7)]Distances = [(D, 0), (A, 2), (G, 5), (F, 7), (C, 7), (B, 5), (E, 6)]. We remove (F, 7) from the queue.
- Queue = [(C, 7)]Distances = [(D, 0), (A, 2), (G, 5), (F, 7), (C, 7), (B, 5), (E, 6)]. We remove (C, 7) from the queue.
- The algorithm is now at the **end**.

Our final found distances are:

$$[(D, 0), (A, 2), (G, 5), (F, 7), (C, 7), (B, 5), (E, 6)].$$