

Outline



2

- 1 Browsers and the Web Application Model
- 2 Window Object
- 3 Event Handling in Modern Browsers
- 4 Event Propagation in the DOM

Browser as an OS!



3

- Modern Browsers are equivalent to an OS for web applications
 - Provide core services such as access to the display (DOM, location bar), and permanent state (cookies, local storage, history)
 - Schedule event handlers for different tasks and control the global ordering of events
 - Allow network messages to be sent and received from the server

Modern Web Application



4

- Applications running on web browsers that use the browser's facilities
 - Update the browser's DOM or shared location bar
 - Schedule events in the future and register event handlers for various parts of the web application
 - Send and receive asynchronous AJAX messages from the web server
- Web applications run on top of the browser OS !

Browser Sandbox



5

- However, web applications are restricted in their behaviour for security reasons
 - Cannot write persistent state to the host file system (use cookies or browser local storage)
 - Cannot write to parts of the DOM tree that come from other domains (Same Origin Policy - SOP)
 - Cannot read cookies belonging to other domains (SOP)
 - Only allowed to communicate with their domain

Same Origin Policy (SOP)

- Restricts which parts of the web application can be read/written by JavaScript code
- Origin = (URL, domain, portNumber)
- NOTE: Origin of the script is not important. What is important is the origin on the document in which script is embedded

JavaScript Two Phase Execution Model



6

Phase 1

- All code within the `<script></script>` tag is executed when they're loaded in the order of loading (unless the script tag is `async` or `deferred`)
- Some scripts may choose to defer execution or execute asynchronously. These are executed at the end of phase 1

JavaScript Two Phase Execution Model



6

Phase 1

- All code within the `<script></script>` tag is executed when they're loaded in the order of loading (unless the script tag is `async` or `deferred`)
- Some scripts may choose to defer execution or execute asynchronously. These are executed at the end of phase 1


Phase 2

- Waits for events to be triggered and executes handlers corresponding to the events in order of event execution (single-threaded model)
- Events can be of four kinds:
 - Load event: After page has finished loading (phase 1)
 - User events: Mouse clicks, mouse moves, form entry
 - Timer events: Timeouts, Interval
 - Networking: Async messages response arrives

JS Event Loop



7



Window Object



8

- 1 Browsers and the Web Application Model
- 2 Window Object
- 3 Event Handling in Modern Browsers
- 4 Event Propagation in the DOM

Window object



9

- Global object that provides a gateway for almost all features of the web application
- Passed to standalone JS functions, and can be accessed by any function within the webpage
- Example Features
 - DOM: Through the `window.document` property
 - URL bar: Through `window.location` property
 - Navigator: Browser features, user agent etc.
 - Browser history: `window.history`
 - ...

window.alert, confirm and prompt



- Alert: Simple way to popup a dialog box on the current window with an OK button
 - Can display an arbitrary string as message
- Prompt: Asks the user to enter a string and returns it
- Confirm: Displays a message and waits for user to click OK or Cancel, and returns a boolean

Example

```
1  do {  
2      var name = prompt("What is your name?");  
3      var correct = confirm("You entered: " + name);  
4  } while (! correct);  
5  
6  alert("Hello " + name);
```

setTimeout and setInterval



11

- **setTimeout** is used to schedule a future event asynchronously **once** after a specified no of milliseconds (can be set to 0)
 - Can specify arguments to event handler
 - Can be cancelled using the **clearTimeout** method
- **setInterval** has the same functionality as **setTimeout**, except that the event fires repeatedly until **clearInterval** is invoked

Example of setTimeout

```
1 var timeoutHandler = function(message) {  
2     return function() {  
3         alert(message);  
4     };  
5 };  
6  
7 var ret = setTimeout(timeoutHandler("Hello"),100);  
8 // [...]  
9 if (flag) clearTimeout(ret);
```

setTimeout and setInterval



11

- **setTimeout** is used to schedule a future event asynchronously **once** after a specified no of milliseconds (can be set to 0)
 - Can specify arguments to event handler
 - Can be cancelled using the **clearTimeout** method
- **setInterval** has the same functionality as **setTimeout**, except that the event fires repeatedly until **clearInterval** is invoked

Example of setInterval

```
1 var intervalHandler = function(message) {  
2     var i = 0;  
3     return function() {  
4         alert(message + ' ' + i);  
5         i += 1;  
6     }  
7 };  
8 var ret = setInterval(intervalHandler("invocation"  
9     ),1000); // [...]  
9 if (flag) clearInterval(ret);
```

Class Activity



12

- Implement a function that invokes another function **func** a specified number of times **noTimes**, asynchronously, each time after **time** ms.
- The function should pass as an argument to **func** the number of times it called **func** so far.

HINT

Use `setInterval`

```
1 function invokeTime( func , noTimes , time ) {  
2     // IMPLEMENT THIS  
3 }  
4 var setup = function() {  
5     invokeTimes( function(i) { alert("hello " + i); }, 10,  
6                 1000 );  
7 }  
8 setup();
```

Solution



13

```
1  function invokeTimes(func, noTimes, time) {
2      let count = 0;
3
4      function onInterval() {
5          if (count < noTimes) {
6              count++; // starts from 1
7              func(count); // Call func with the current count
8          } else {
9              clearInterval(intervalId); // Stop the interval
10         }
11     }
12
13     var intervalId = setInterval(onInterval, time); // Set up
14         the interval
15
16     var setup = function() {
17         invokeTimes( function(i) { alert("hello " + i); }, 10,
18             1000 );
19     }
20     setup(); // Executes the setup function
```

Event Handling in Modern Browsers



14

- 1 Browsers and the Web Application Model
- 2 Window Object
- 3 Event Handling in Modern Browsers**
- 4 Event Propagation in the DOM

Event Handling



15

- JavaScript code is event-driven, which means that you need to register event callbacks
- Events are of five types in JavaScript
 - Mouse Events (e.g., **mousedown**, **mousemove**, etc)
 - Window Events (**load**, **DOMContentLoaded**, etc)
 - Form events (**submit**, **reset**, **changed** etc)
 - Key events (**keydown**, **keyup**, **keypress** etc)
 - DOM events (part of DOM3 specification)

A cautionary note on event handling



16

- There are many browser incompatibilities regarding the types of events implemented, and the way to register event handlers (e.g., IE prior to v9 is different from almost all other browsers)
- This is complicated by the fact that the DOM3 spec itself is a moving target for over 10 years
- In this class, we will follow DOM2 spec. and assume that the browser is standard compliant
 - Focus on set of events that are common (except IE)

Registering Event Handlers



17

- Two ways of registering event handlers
 - Old method (DOM 1.0): Directly add a **onclick** or **onload** property to the DOM object/window
 - Disadvantage: Allows only one event handler to be specified. New handlers must remember to chain the old handler, and can potentially 'swallow' the handler
 - New method (DOM 2.0): Allows multiple event handlers to be added to the DOM object/window

Registering Event handlers: DOM 1.0



18

- Use `on<event>` as the handler for `<event>`
 - No caps anywhere. Eg., `onload`, `onmousemove`

```
1 element = document.getElementById('myButton');
2
3 element.onclick = function(event) {
4     this.style.backgroundColor = "#ffffff";
5     return true;
6 }
```

- ① `this` is bound to the DOM element on which the `onclick` handler is defined – can access its properties thro' `this.prop`
- ② `return` value of false tells browser not to perform the default value associated with the property (true otherwise)

Chaining event handlers in DOM 1.0 method (This is deprecated now !)



19

- If you want to have multiple event handlers in the above method, you need to remember to chain the earlier handlers and call them

```
1 var old = element.onclick;  
2 element.onclick = function(event) {  
3     this.style.backgroundColor = "#ffffff";  
4     if (old) return old(event);  
5     return true;  
6 }
```

Registering Event handlers: DOM 2.0



20

- The DOM 1.0 method is clunky and can be buggy. Also, difficult to remove event handlers
- DOM 2 event handlers
 - `addEventListener` for adding a event handler
 - `removeEventListener` for removing event handlers
 - `stopPropagation` and `stopImmediatePropagation` for stopping the propagation of an event (later)

addEventListener



21

- Used to add an Event handler to an element. Does NOT overwrite previous handlers
 - Arg1: Event type for which the handler is active
 - Arg2: Function to be invoked when event occurs
 - Arg3: Whether to invoke in the 'capture' phase of event propagation (more later) - false typically

Example

```
1  var b = document.getElementById("mybutton");
2  b.addEventListener("click", function() {
3      alert("hello");
4  }, false );
```

More on *addEventListener*



- Does not overwrite previous handlers, even those set using *onclick*, *onmouseover* etc.
- Can be used to register multiple event handlers – invoked in order of registration (handlers set through DOM 1.0 model have precedence)

Example

```
1  var b = document.getElementById("mybutton");
2  b.addEventListener("click", function() {
3      alert("hello");
4  }, false);
5  b.addEventListener("click", function() {
6      alert("world");
7  }, false);
```

removeEventListener



23

- Used to remove the event handler set by `addEventListener` functions, with the same arguments
 - No error even if the function was not set as event handler

Example

```
1 var handleClick = function() {  
2     alert("clicked");  
3 };  
4 var b = document.getElementById("mybutton")  
5 b.addEventListener("click", handleClick ,  
6     false);  
7 b.removeEventListener("click", handleClick ,  
8     false);
```


Event Handler Context



24

- Invoked in the context of the element in which it is set (**this** is bound to the target)
- Single argument that takes the **event** object as a parameter – different events have different properties, with info about the event itself
- Return value is discarded – not important
- Can access variables in the scope in which it is defined, as any other JS function
 - Can support closures within Event Handlers

Class Activity



25

- Write a handler for the `click` property of the button in the example earlier that displays a message (`str1 + str2`) using the alert feature
- `str1` is determined at runtime when setting the event handler for the button `b`, and should not be stored in the global context
- `str2` is determined based on the event target at the time of its invocation e.g., `event.target`. e.g., the button's text content.

Solution



26

Example

```
1 document.addEventListener('DOMContentLoaded',
   function() {
2     var button = document.getElementById('myButton
       ');
3     // Assuming 'str1' is determined here at
       runtime.
4     var str1 = 3 + 5;
5
6     function handleClick(event) {
7         // 'str2' is determined based on the event
           target at the time of its invocation.
8         var str2 = event.target.textContent ||
           event.target.innerText;
9         alert(str1 + str2);
10    }
11
12    button.addEventListener('click', handleClick);
13 });
```

Event Propagation in the DOM



27

- 1 Browsers and the Web Application Model
- 2 Window Object
- 3 Event Handling in Modern Browsers
- 4 Event Propagation in the DOM**

Event Propagation




28

- Events triggered on an element propagate through the DOM tree in 2 consecutive phases
 - Capture phase: Event is triggered on the topmost element of the DOM and propagates down to the event target element
 - Bubble phase: Event starts from the event target element and 'bubbles up' the DOM tree to the top
- Events may therefore trigger handlers on elements different from their targets



Capture and Bubble Phases



Event Propagation Setup



- To associate an event handler with the capture phase of event propagation, set the third parameter of `addEventListener` to `true`

Example

```
1 var div1 = getElementById("one");  
2 div1.addEventListener("click", handler, true);
```

- The default way of triggering event handlers is during the bubble phase (3rd argument is false)

First phase: Capture



31

```
1 var div1 = getElementById("one");
2 div1.addEventListener("click", handler1, true);
3 var div2 = getElementById("two");
4 div2.addEventListener("click", handler2, true);
```

Capture Phase

- Assume that the **div** element **'two'** is clicked.
- **handler1** is invoked before **handler2** as both are registered during the capture phase.

Second phase: Bubble



32

```
1 var div1 = getElementById("one");
2 div1.addEventListener("click", handler1, false);
3 var div2 = getElementById("two");
4 div2.addEventListener("click", handler2, false);
```

Bubble Phase

- Assume that the **div** element **'two'** is clicked.
- **handler2** is invoked before **handler1** as they are both registered during the bubble phase.

Exercise



33

```
1 var div1 = getElementById("one");
2 div1.addEventListener("click", handler1, true);
3 div1.addEventListener("click", handler1, false);
4 var div2 = getElementById("two");
5 div2.addEventListener("click", handler2, false);
6 div2.addEventListener("click", handler3, true);
```

Question

- Which handlers and in which order will they be triggered? Why?

Solution



34

```
1 var div1 = getElementById("one");
2 div1.addEventListener("click", handler1, true);
3 div1.addEventListener("click", handler1, false);
4 var div2 = getElementById("two");
5 div2.addEventListener("click", handler2, false);
6 div2.addEventListener("click", handler3, true);
```

Answer

- Order: 1, 3, 2, 1
- Capturing: 1, 3
- Bubbling: 2, 1

Stopping Event Propagation



- In the prior example, suppose **handler1** and **handler2** are registered in the capture phase

Stopping Event Propagation

```
1  var handler1 = function( clickEvent ) {  
2      clickEvent.stopPropagation();  
3  }
```

- Then **handler2** will never be invoked as the event will not be sent to **div2** in the capture phase

stopPropagation, preventDefault and stopImmediatePropagation



36

- An event handler can stop the propagation of an event through the capture/bubble phase using the **event.stopPropagation** function
 - Other handlers registered on the element are still invoked however
- To prevent other handlers on the element from being invoked and its propagation, use **event.stopImmediatePropagation**
- To prevent the browser's default action, call the method **event.preventDefault**

Class Activity



37

- Write JavaScript code that handles click events on two nested elements (a **button** inside a **div**, with both having an **alert**). The goal is to stop the click event on the inner element from propagating to the outer element.

Stopping Event Propagation

```
1 <div id="outer">Outer Element
2   <button id="inner">Click Me (Inner Element)</
   button>
3 </div>
4
5 document.addEventListener('DOMContentLoaded',
   function() {
6   var outer = document.getElementById('outer');
7   var inner = document.getElementById('inner');
8
9   // YOUR CODE HERE!
10 });
```

Solution



38

Stopping Event Propagation

```
1 <div id="outer">Outer Element
2   <button id="inner">Click Me (Inner Element)</
   button>
3 </div>
4 document.addEventListener('DOMContentLoaded',
   function() {
5   var outer = document.getElementById('outer');
6   var inner = document.getElementById('inner');
7
8   outer.addEventListener('click', function() {
9     alert("Outer element clicked!");
10  });
11
12  inner.addEventListener('click', function(event
    ) {
13    event.stopPropagation(); // Stop the event
                                from propagating to the outer element
14    alert("Inner element clicked!");
15  });
16 });
```

Table of Contents



- 1 Browsers and the Web Application Model
- 2 Window Object
- 3 Event Handling in Modern Browsers
- 4 Event Propagation in the DOM