# BRIGHTSTONE SQ

## PRODUCT SPECIFICATIONS

| | |
|---|---|
| Style Name | Brightstone Sq |
| Construction | Tufted Multi - Level Pattern Loop |
| Yarn System | 100%  Nylon 6,0 |
| Dye Method | Solution Dyed |
| Gauge | 1/12" |
| Production Weight | 21 oz psy |
| Total Thickness | 6.0mm |
| Backing | ComfortBac v2 |
| Tile Size | 50cm x 50cm |

## PERFORMANCE SPECIFICATIONS

| | |
|---|---|
| Radiant Panel | ASTM E 648 Class 1 |
| Smoke Density | ASTM E 662 Less than 450 |
| Static Propensity | AATCC 134 Less than 3.5KV |
| Colour Fastness to Light | AATCC 16E  ≥4 |
| Colour Fastness to Rubbing/Crocking | AATCC 165  ≥4 |
| Dimensional Stability | AACHEN  ≤0.2% |
| Foot Traffic Recommendation TARR | Heavy Commercial |
| Antimicrobial | Health Guard |
| Certificates | Singapore Green Label Certification |
| | Singapore Green Building Product Certification (4 ticks) |

**RECOMMENDED INSTALLATION METHOD**



1/4 Turn  Ashlar  Brick

039-017-2094
Environmentally Preferred Carpet