

Grammar

Base Type

$\tau ::= \sigma \mid r$

$\sigma ::= \text{float} \mid \sigma \times \sigma \mid \eta \cdot \sigma$

Natural Numbers

$\eta ::= 0 \mid 1 \mid \dots$

Range

$r ::= \eta..\eta \mid \text{empty}$

Term

$t ::= \text{fl} \mid \eta \mid p \mid \text{for } i : r \text{ in } t \mid \text{let } x := t \text{ in } t \mid (t, t) \mid \text{if } t \leq \eta \text{ then } t \text{ else } t \mid t + t \mid t * t \mid t - t \mid t / t$

- i and x are identifiers.

Literal

$\text{fl} ::= 0.0 \mid -4.21 \mid 523.215 \mid \dots$

Place Expression

$p ::= x \mid p[t] \mid p.\text{fst} \mid p.\text{snd}$

Environment

Type Environment

$\Gamma ::= \bullet \mid \Gamma, (x : \tau)$

Typing Rules

$$\frac{\Gamma \vdash t_l : \text{float} \quad \Gamma \vdash t_r : \text{float} \quad \text{op} \in \{+, -, *, /\}}{\Gamma \vdash t_l \text{ op } t_r : \text{float}} \text{T-ARITH}$$

$$\frac{x : \sigma \in \Gamma}{\Gamma \vdash x : \sigma} \text{T-VAR}$$

$$\frac{\Gamma \vdash t : \sigma \quad \Gamma, (x : \sigma) \vdash t_{\text{body}} : \sigma_{\text{body}}}{\Gamma \vdash \text{let } x := t \text{ in } t_{\text{body}} : \sigma_{\text{body}}} \text{T-LET}$$

$$\begin{array}{c}
\frac{r' = \text{mkRng}(\eta_l.. \eta_r) \quad \Gamma, (i : r') \vdash t_{\text{body}} : \sigma}{\Gamma \vdash \text{for } i : \eta_l.. \eta_r \text{ in } t_{\text{body}} : \text{length}(r') \cdot \sigma} \text{T-FOR} \\
\\
\frac{\Gamma \vdash t : \eta_t \cdot \sigma \quad \Gamma \vdash t_{\text{index}} : \eta_l.. \eta_r \quad \eta_r < \eta_t}{\Gamma \vdash t[t_{\text{index}}] : \sigma} \text{T-INDEX-RANGE} \\
\\
\frac{\Gamma \vdash t_{\text{index}} : \text{empty} \quad \Gamma \vdash t : \eta_t \cdot \sigma}{\Gamma \vdash t[t_{\text{index}}] : \sigma} \text{T-INDEX-RANGE-EMPTY} \\
\\
\frac{\Gamma \vdash t : \eta_t \cdot \sigma \quad \eta < \eta_t}{\Gamma \vdash t[\eta] : \sigma} \text{T-INDEX-NAT} \\
\\
\frac{\Gamma \vdash t : \sigma_1 \times \sigma_2}{\Gamma \vdash t.\text{fst} : \sigma_1} \text{T-FST} \\
\\
\frac{\Gamma \vdash t : \sigma_1 \times \sigma_2}{\Gamma \vdash t.\text{snd} : \sigma_2} \text{T-SND} \\
\\
\frac{\begin{array}{c} \Gamma \vdash t : \eta_l.. \eta_r \quad r_{\text{then}} = \text{mkRng}(\eta_l.. \min(\eta, \eta_r)) \\ r_{\text{else}} = \text{mkRng}(\min(\eta, \eta_r) + 1.. \eta_r) \quad \Gamma, (t : r_{\text{then}}) \vdash t_{\text{then}} \sigma_{\text{then}} \\ \Gamma, (t : r_{\text{else}}) \vdash t_{\text{else}} \sigma_{\text{else}} \quad \sigma = \sigma_{\text{then}} = \sigma_{\text{else}} \end{array}}{\Gamma \vdash \text{if } t \leq \eta \text{ then } t_{\text{then}} \text{ else } t_{\text{else}} : \sigma} \text{T-IF} \\
\\
\frac{\Gamma \vdash t : \text{empty} \quad \Gamma \vdash t_{\text{then}} \sigma_{\text{then}} \quad \Gamma \vdash t_{\text{else}} \sigma_{\text{else}} \quad \sigma = \sigma_{\text{then}} = \sigma_{\text{else}}}{\Gamma \vdash \text{if } t \leq \eta \text{ then } t_{\text{then}} \text{ else } t_{\text{else}} : \sigma} \text{T-IF-EMPTY}
\end{array}$$

Auxillary definitions

$\text{mkRng}(r) = \text{match } r \text{ with}$

$\eta_l.. \eta_r \Rightarrow \text{if } 0 \leq \eta_l \leq \eta_r \text{ then } \eta_l.. \eta_r \text{ else empty}$
 $\text{empty} \Rightarrow \text{empty}$

$\text{length}(r) = \text{match } r \text{ with}$

$\text{empty} \Rightarrow 0$
 $\eta_l.. \eta_r \Rightarrow \eta_r - \eta_l + 1$