HR FEST 2026

// 30-MINUTES PLENARY TALK

Reinforcement Learning in Continuous Representation Spaces

Miguel A. Solís
Universidad Andrés Bello, Chile
miguel.solis@unab.cl
www.miguelsolis.info → Invited Talks

ORGANIZED BY

Universidad Nacional del Callao

TECHNICALLY CO-SPONSORED BY

IEEE

IEEE Region 9

IEEE Robotics & Automation Society

HR FEST 2026

Robotics

Areas

- Mobile Robotics
- Bio-inspired Robotics
- Cognitive Robotics
- Intelligent Robotics
- Human-Robot Interaction
- Tele-operated Robotics
- Swarm Robotics

...



HR FEST 2026

Perception and Action





Image extracted from “Robotic Systems” de Kris Hauser, University of Illinois at Urbana-Champaign.

Reinforcement Learning



Agent interacts with the environment through trial and error.

- **Receives an input (perception), with current state “s”.**
- **Then, decides (acts) with an action “a” as output.**
- **Receives a reward (reinforcement) “r”.**

Sequential Decision Problem

state “s” belongs to a Markovian Decision Process if and only if:

$$Pr\{s_{k+1}|s_k\} = Pr\{s_{k+1}|s_1, ..., s_k\}.$$

Reinforcement Learning Problem

S: set of states.

A: set of actions.

$T : S \times A \times S \rightarrow [0, 1]$ transition function (unknown)

R: $S \times A \times S \rightarrow \mathbb{R}$ rewards function


$\pi : S \rightarrow A$ policy

Return $V^{\pi}(s_k) = r_k + \gamma r_{k+1} + \gamma^2 r_{k+2} + ...$

$$= \sum_{i=0}^{\infty} \gamma^i r_{k+i}.$$

Example

Grid-world



States: location on the grid.

Actions: up, down, left, right.

Rewards: +1 on the goal
-1 on prohibited zone
-0.1 otherwise

Basic (and tabular) methods: Value Iteration, Policy Iteration

Value Iteration

0	0.62	0.8	1	+1
1	0.46		0.8	-1
2	0.31	0.46	0.62	0.46
	0	1	2	3

Policy Iteration

0	der.	der.	der.	meta
1	arr.		arr.	prohib
2	arr.	der.	arr.	izq.
	0	1	2	3

Q-learning

Update rule:

$$Q(s_k, a_k) \leftarrow (1-\alpha)Q(s_k, a_k) + \alpha\left(r_{k+1} + \gamma \max_a Q(s_{k+1,a})\right)$$

Then, policy should be given by:


$$\pi^*(s_k) = arg\max Q^*(s_k, a_k)$$



Image extracted from “Introduction to Q-learning with OpenAI Gym”, Gelana Tostaeva, Medium.

Example

Grid-world



States: location on the grid.


Actions: up, down, left, right.

Rewards: +1 on the goal
-1 on prohibited zone
-0.1 otherwise


Basic (and tabular) methods: Value Iteration, Policy Iteration

Q-learning

- Visited (state,action) pairs are the only ones updated.





- Including exploration:



Example

Taxi







HR FEST 2026

Deep Reinforcement Learning


Need of function approximators (such as artificial neural networks)



General scheme (pretty much the same)



Deep Reinforcement Learning



so… discrete action space

Replay buffer


s_1, a_1, r_2, s_2
s_2, a_2, r_3, s_3
s_3, a_3, r_4, s_4
…
$s_t, a_t, r_{t+1}, s_{t+1}$

$\rightarrow \quad s, a, r, s'$


HR FEST 2026

Deep Reinforcement Learning

Inverted pendulum



Random policies



REINFORCE

Policy parametrization:

$$\Pi = \{\pi_\theta, \theta \in \mathbb{R}^m\}$$

for every policy we would have:

$$J(\theta) = \mathbb{E}\left[\sum_{t\geq 0} \gamma^t r_t | \pi_\theta\right]$$

we always are looking for optimal policy:


$$\theta^* = \arg\max_\theta J(\theta)$$

but now we have transition probability given by:


$$p(\tau;\theta) = \prod_{t>0} p(s_{t+1}|s_t, a_t)\pi_\theta(a_t|s_t)$$

REINFORCE

on the hands-on side:




ACTOR-CRITIC




HR FEST 2026

CONSERVATIVE APPROACHES



APPLICATIONS






G.A. Ahumada, C.J. Nettle and M.A. Solis, 'Accelerating Q-learning through Kalman Filter Estimations applied in a RoboCup SSL Simulation', **Proceedings** of the 10th IEEE Latin American Robotics Symposium, 2013.

APPLICATIONS


- dist(K_i,pelota), dist(T_j,pelota)
- dist(K_i,K_j)
- dist(K_i,T_j)
- angle(K_i,T_i)



Ollino, F., Solis, M. A., & Allende, H. (2018). Batch reinforcement learning on a RoboCup Small Size League keepaway strategy learning problem. In 4th Congress on Robotics and Neuroscience, CRoNe 2018. CEUR-WS.

Closing remarks

- ANNs are the most popular function approximators for RL on continuous spaces, but there is room for other techniques (such as fuzzy logic).
- Specific RL algorithm to be applied would depend on the given problem.
- don't miss the workshop tomorrow **Saturday Oct 7th, 9am** at **Library Auditorium**



HR FEST 2026

// Q&A

Thank you! Questions?

Miguel A. Solís

miguel.solis@unab.cl

www.miguelsolis.info → Invited Talks

References

- Sutton, R. S., & Barto, A. G. (2018). Reinforcement learning: An introduction. MIT press.
- Kober, J., Bagnell, J. A., & Peters, J. (2013). Reinforcement learning in robotics: A survey. The International Journal of Robotics Research, 32(11), 1238-1274.
- Mnih, V., Kavukcuoglu, K., Silver, D., Rusu, A. A., Veness, J., Bellemare, M. G., ... & Hassabis, D. (2015). Human-level control through deep reinforcement learning. nature, 518(7540), 529-533.

ORGANIZED BY

Universidad Nacional del Callao

TECHNICALLY CO-SPONSORED BY

IEEE

IEEE Region 9

IEEE Robotics & Automation Society