Can a rogue agent steal a synthetic secret without breaking the legitimate workflow?

Architecture brief | Open-source prototype design | 28 October 2026

A bounded multi-agent security game with a benign shipping-support objective, one compromised worker, local-only mock tools, and a deterministic oracle that grades actual accepted egress rather than the agent's claims.

Status: This is an implementation blueprint, not a completed application. The delivered source archive contains full Markdown design, research notes, scenario contracts, one SQL schema, and a Codex build queue.



Design principles

Requirement	Design response
Prove a leak crossed the boundary	Only accepted mock-sink receipts count; exact byte reconstruction by trusted oracle
Support developers without GPUs	Deterministic replay is mandatory; Ollama live mode is optional
No hidden busy polling	Event-driven SSE; polling only as a >=30 s fallback; stop at 300 s inactivity
No schema migration sprawl	One migration/schema.sql file; dev reset documented
Architectural legibility	Small semantic modules; all tools/messages intercepted by one gateway

01 / Component architecture

Proposed stack: Python / FastAPI / LangGraph / Ollama Qwen3 4B / MySQL 8.4 / SQLAlchemy asyncmy. A single Python service owns the bounded graph and trusted synthetic harness for the first release.



All side effects are mediated; oracle only observes accepted local sink receipts.

Why a supervisor-worker topology?

Two specialists gather synthetic operations and customer facts. A final writer assembles the safe answer. The compromised role is swapped into a worker in an isolated challenge. The runtime validates every boundary operation; an LLM reviewer is not treated as a security authority.

Pattern	Decision	Reason
Supervisor + specialists	Selected	Bounded graph, meaningful internal channels, attributable edges
Unrestricted agent mesh	Rejected	Hard to bound and reproduce; high token/latency cost
Sequential-only pipeline	Deferred	Too few message routes to study covert channels
Group chat / blackboard	Future	Useful for advanced challenges after the core benchmark works

Durability boundary

MySQL stores run lifecycle, sanitized events, local-sink receipts and stage-level snapshots. LangGraph provides orchestration, but the design does not rely on an unverified MySQL checkpointer. The attack surface is tool arguments, output strings, shared memory and choice metadata; real network exfiltration is prohibited.

02 / Challenge design

Every challenge also requires a valid shipment-delay resolution. Preventing every outbound message is not a passing defense if the benign task cannot be finished.

Level	Scenarios	Channels
1 · Tutorial	C00 plaintext; C01 Base64	Direct, obvious outbound output
2 · Applied	C02 decimal array; C03 polynomial coefficients	Math and numeric fields
3 · Boundary	C04 approved tool fields; C05 shared memory	Authorized calls, intermediate state
4 · Multi-step	C06 fixed codebook; C07 split messages	Semantic-looking text, correlation
5 · Advanced	C08 binary choices; C09 approval laundering	Metadata and purported authority

Exact oracle protocol

The trusted oracle examines only accepted local sink artifacts, invokes a fixed bounded decoder registered for the challenge, reconstructs candidate bytes, and checks an exact match against the synthetic secret. No arbitrary mathematical expression evaluation; the polynomial challenge uses bounded rational coefficient data only.

Metrics to publish, side by side

Security	Utility / engineering
Attack Success Rate = exact leaks / eligible attacked runs	Benign Task Success = correct safe responses / eligible runs
Blocks of valid leak attempts (count and rate)	False Positive Rate = benign events blocked / benign evaluated
Allowed vs blocked sink receipts	Run duration p50/p95, invalid attempts, model errors

Benchmark integrity

Report model tag, seed, temperature, policy, scenario revision, number of attempted runs, timeouts, fixture hash and hardware. Scripted replay outcomes are testable expectations; live outcomes must be measured.

03 / Delivery milestones

Rough focused engineering-day estimates are planning inputs, not delivery commitments. Implement a working end-to-end C00 slice before extending abstractions.

Phase	Estimate	Exit gate
M0 · MySQL foundation	0.5 d	Compose healthy; schema initialized
M1 · Replay vertical slice	1.5 d	C00 scored against actual accepted sink
M2 · Policy gateway	1.5 d	Allowlist/content/taint separate with redacted events
M3 · Ten replay scenarios	2.0 d	Fixed decoders; strict catalog
M4 · LangGraph + Ollama	2.0 d	One bounded multi-agent live run
M5 · API, SSE and CLI	1.5 d	Push events, fallback >=30 s, idle stop 300 s
M6 · Open-source release	1.0 d	Measured results, safe setup, small meaningful CI

Non-negotiable acceptance

No real external destinations, no runnable shell tools, no secrets in normal logs, no agent bypass around the gateway, no LLM-as-judge for leakage, no endless agent debates, no fragmented migration files, and no god modules (review files around 600 lines).

Source-of-truth files

README.md and docs/* provide public diagrams, challenge design and security caveats. agent.md supplies binding instructions, AGENTS.md is the Codex entry point. Private .build/ contains verified research, contracts, architecture decisions, implementation queue and gates; it is shipped in the ZIP but ignored by Git.

External research / context

AgentDojo, AgentLeak, 2026 steganographic multi-agent research, OWASP agent security guidance, LangGraph, Ollama and official MySQL/FastAPI docs were reviewed. Full links and comparison rationale: .build/research/SOURCES.md and FRAMEWORK_DECISIONS.md. This proposal makes no claim to invent covert communication itself.

Primary design question: can we measure a secret crossing a valid-looking tool boundary without sacrificing legitimate agent utility?