

////////////////////////////////////

◇ Simple If Condition

```
echo "Enter a number: "  
read num  
  
if [ $num -gt 10 ]  
then  
    echo "Number is greater than 10"  
else  
    echo "Number is 10 or less"  
fi
```

////////////////////////////////////

◇ Using for Loop

```
echo "Enter a number: "  
read num  
  
for ((i=1; i<=5; i++))  
do  
    num=$((num + i))  
done  
echo "Sum = $num"
```

////////////////////////////////////

◇ Using Case

```
echo "Choice:  
1) Create directory  
2) Check if file exists  
3) Display file
```

4) Move/Copy file

5) Create file"

read ch

case \$ch in

1)

echo "Enter directory name:"

read d

mkdir \$d

echo "Directory created"

::

2)

echo "Enter file name:"

read f

if [-f \$f]

then

echo "File exists"

else

echo "File does not exist"

fi

::

3)

echo "Enter file name:"

read f

cat \$f

::

4)

echo "1) Copy 2) Move"

read op

echo "Enter source file:"

```

read s
echo "Enter destination:"
read d
if [ $op -eq 1 ]
then
    cp $s $d
    echo "File copied"
else
    mv $s $d
    echo "File moved"
fi
::
5)
echo "Enter file name:"
read f
touch $f
echo "File created"
::
*)
echo "Invalid choice"
::
Esac

```

◇ Sed Commands

1. Substitute (Replace Text)

☞ Replace all occurrences:

```
sed 's/old/new/g' file.txt
```

2. Replace in Specific Line

`sed '2s/old/new/' file.txt`

→ Replace only in line 2

3. Delete Lines

`sed '2d' file.txt`

→ Deletes line 2

☞ Delete range:

`sed '2,5d' file.txt`

4. Print Specific Lines

`sed -n '3p' file.txt`

→ Prints only line 3

☞ Range:

`sed -n '2,4p' file.txt`

5. Insert Line

`sed '2i Hello' file.txt`

→ Inserts "Hello" before line 2

6. Append Line

`sed '2a Hello' file.txt`

→ Adds "Hello" after line 2

7. Replace Only Matching Lines

`sed '/error/s/old/new/' file.txt`

→ Replace only lines containing "error"

8. Remove Blank Lines

`sed '/^$/d' file.txt`

9. Replace in File Directly (Important)

`sed -i 's/old/new/g' file.txt`

→ Changes file permanently

10. Show Line Numbers

`sed '=' file.txt`

◇ Quick Example

`sed 's/Linux/Unix/g' notes.txt`

→ Replaces all "Linux" with "Unix"

◇ Chmod Commands

`chmod 777 file.txt`

👉 Everyone can read, write, execute (⚠ not safe)

`chmod 644 file.txt`

👉 Owner: read/write

👉 Others: read only

`chmod 600 file.txt`

👉 Only owner can read/write (secure)

`chmod 755 file.txt`

👉 Set full permission to owner, read+execute to others

chmod 000 file.txt

👉 Remove all permissions