
Section 1. Introduction

HIGHLIGHTS

This section of the manual contains the following topics:

1.1	Introduction	1-2
1.2	Family Reference Manual Sections	1-2
1.3	Device Structure.....	1-2
1.4	Development Support	1-3
1.5	Style and Symbol Conventions	1-4
1.6	Related Documentation	1-5
1.7	Revision History	1-6

Note: This family reference manual section is meant to serve as a complement to device data sheets. Depending on the device variant, this manual section may not apply to all PIC32 devices.

Please consult the note at the beginning of the “**Device Overview**” chapter in the current device data sheet to check whether this document supports the device you are using.

Device data sheets and family reference manual sections are available for download from the Microchip Worldwide Web site at: <http://www.microchip.com>

1.1 INTRODUCTION

Microchip’s PIC32 series of 32-bit microcontrollers are designed to fulfill a customer’s requirements for enhanced features and performance for their MCU-based applications.

Common attributes among all devices in the PIC32 series are:

- Pin, peripheral and source code compatibility
- Common software and hardware development tools

1.2 FAMILY REFERENCE MANUAL SECTIONS

The collective PIC32 family reference manual sections describe the PIC32 family series of 32-bit microcontrollers. All sections that comprise the PIC32 Family Reference Manual are available from the Microchip web site: www.microchip.com. These individual sections explain the PIC32 family architecture and operation of the peripheral modules, but do not cover the specifics of each device in a particular family. Users should refer to the respective product data sheet for device-specific details, such as:

- Pinout and packaging details
- Memory map
- List of peripherals included on the device, including multiple instances of peripherals
- Device-specific electrical specifications and characteristics

1.3 DEVICE STRUCTURE

The PIC32 architecture has been broken down into the following functional blocks:

- [MCU Core](#)
- [System Memory](#)
- [System Integration](#)
- [Peripherals](#)

1.3.1 MCU Core

The PIC32 MCU core is discussed in **Section 2. “CPU”** (DS61113).

1.3.2 System Memory

The system memory provides on-chip nonvolatile Flash memory and volatile SRAM memory, featuring user and protected kernel-segment-partitioning for real-time operating systems.

Refer to the specific device data sheet for the list of applicable family reference manual sections for this topic.

1.3.3 System Integration

System integration consists of a comprehensive set of modules and features that connect the MCU core and peripheral modules into a single operational unit. System integration features also provide these advantages:

- Decreased system cost, by bringing traditionally off-chip functions into the microcontroller
- Increased design flexibility, by adding a wider range of operating modes
- Increased system reliability, by enhancing the ability to recover from unexpected events

Refer to the specific device data sheet for the list of applicable family reference manual sections for this topic.

1.3.4 Peripherals

The PIC32 devices have many peripherals that allow it to interface with the external world.

Refer to the specific device data sheet for the list of applicable family reference manual sections for this topic.

1.4 DEVELOPMENT SUPPORT

Microchip offers a wide range of development tools that allow users to efficiently develop and debug application code. Microchip's development tools can be divided into four categories:

- Code generation
- Hardware/software debug
- Device programmer
- Product evaluation boards

As new tools are developed, the latest product briefs and user guides can be obtained from the Microchip web site (www.microchip.com) or from your local Microchip Sales office.

Microchip offers other references and support to speed the development cycle. These include:

- Application notes
- Reference designs
- Local sales offices with field application support
- Corporate applications support line
- Getting started guides
- "How to" brochures
- MASTERS conferences
- Webinars
- Design centers

These can all be found on the Microchip web site (www.microchip.com). Also, the Microchip web site lists other sites that may provide useful references.

1.5 STYLE AND SYMBOL CONVENTIONS

Throughout the individual family reference manual sections, certain style, format, and font conventions are used to signal particular distinctions for the affected text. [Table 1-1](#) lists these conventions, specific symbols, and non-conventional word definitions and abbreviations.

1.5.1 Document Conventions

[Table 1-1](#) defines some of the symbols, terms and typographic conventions used in this manual.

Table 1-1: Document Conventions

Symbol or Term	Description
Set	To force a bit or register to a value of logic '1'.
Clear	To force a bit or register to a value of logic '0'.
Reset	1) To force a register/bit to its default state. 2) A condition in which the device places itself after a device Reset occurs. Some bits will be set to '0' (such as interrupt enable bits), while others will be set to '1' (such as the I/O data direction bits).
0xnn or nnh	Designates the number 'nn' in the hexadecimal number system. These conventions are used in the code examples. For example, the designation 0x13F or 13Fh may be used.
B'bbbbbbbb'	Designates the number 'bbbbbbbb' in the binary number system. This convention is used in the text, figures and tables. For example, the designation B'10100000' may be used.
R-M-W	Read-Modify-Write. This occurs when a register or port is read, the value is modified, and that value is then written back to the register or port. This action can occur from a single instruction (such as bit set, <code>BSET</code>) or a sequence of instructions.
: (colon)	Used to specify a range or the concatenation of registers/bits/pins. One example is TMR3:TMR2, which is the concatenation of two 16-bit registers to form a 32-bit timer value. Concatenation order (left-right) usually specifies a positional relationship (MSb to LSb, higher to lower).
< >	Specifies bit(s) locations in a particular register. One example is SRxMPT (SPIxSTAT<5>), which specifies the abbreviation of bit and the register name, and associated bits or bit positions.
MSb, LSb	Indicates the Least/Most Significant bit in a field.
MSB, LSB	Indicates the Least/Most Significant Byte in a field of bits.
mshw, lshw	Most Significant half-word and least significant half-word. A half-word is 16 bits wide.
msw, lsw	Indicates the least/most significant word in a field of bits.
Courier New Font	Used for code examples, binary numbers and for instruction mnemonics that appear in the text.
Times New Roman Font (Italics)	Used for equations.
Note	A Note presents information that we want to re-emphasize, either to help you avoid a common pitfall or to make you aware of operating differences between some device family members. A Note can be in a box, or when used in a table or figure, it is located at the bottom of the table or figure.
Register cells	A bit reference that appears in a gray shaded cell of a register, signifies that the bit is either unimplemented (instead of a name an EM dash (—) is present) or is not relevant to the particular peripheral module.

1.5.2 Electrical Specifications

The individual family reference manual sections contain references to electrical specifications and their parameter numbers. Table 1-2 shows the parameter numbering convention for PIC32 devices. A parameter number represents a unique set of characteristics and conditions that is consistent between every data sheet, although the actual parameter value may vary from device to device.

To determine the parameter values for a specific device, users should refer to the “**Electrical Specifications**” section of the specific device data sheet.

Table 1-2: Electrical Specification Parameter Numbering Convention

Parameter Number Format	Comment
Dxxx	DC Specification
Axxx	DC Specification for Analog Peripherals
xxx	Timing (AC) Specification
PDxxx	Device Programming DC Specification
Pxxx	Device Programming Timing (AC) Specification

Legend: ‘xxx’ represents a parameter number.

1.6 RELATED DOCUMENTATION

Microchip, as well as other sources, offers additional documentation to aid you as you develop PIC32-based applications. The list below contains the most common documentation, but other documents may also be available. Please check the Microchip web site (www.microchip.com) for the latest published technical documentation.

1.6.1 Microchip Documentation

The following PIC32 documentation is available from Microchip. These documents provide application-specific information that gives actual examples of using, programming, and designing with PIC32 microcontrollers.

- *PIC32 Family Reference Manual Sections*

The individual family reference manual sections describe the PIC32 family architecture and operation of the peripheral modules, but do not cover the specifics of each device in the family.

- *PIC32MX Product Data Sheets*

These data sheets contain device-specific information, such as pinout and packaging details, electrical specifications and memory maps.

- *PIC32MX Programming Specification (DS61145)*

The programming specification contains detailed descriptions of, and electrical and timing specifications for, the programming process. Both In-Circuit Serial Programming™ (ICSP™) and Enhanced ICSP are described in detail.

1.6.2 Third-Party Documentation

Microchip does not review third-party documentation for technical accuracy; however, these references may be helpful to understand operation of the devices. Refer to the Microchip web site for available information on third-party documentation.

1.7 REVISION HISTORY

Revision A (September 2007)

This is the initial version of this document.

Revision B (October 2007)

Updated document to remove Confidential status.

Revision C (April 2008)

Revised status to Preliminary; Revised Section 1.1.

Revision D (September 2011)

This revision includes the following updates:

- Removed the Preliminary status in the footer
- Added a note box with information on related family reference manual sections
- Updated the bulleted list in [1.1 “Introduction”](#)
- Removed the feature list from [1.3.1 “MCU Core”](#)
- Updated the family reference manual section information in these sections:
 - [1.3.2 “System Memory”](#)
 - [1.3.3 “System Integration”](#)
 - [1.3.4 “Peripherals”](#)
- Updated the Document Conventions in [Table 1-1](#)
- In addition, updates to formatting and minor text edits were incorporated throughout the document

Note the following details of the code protection feature on Microchip devices:

- Microchip products meet the specification contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is one of the most secure families of its kind on the market today, when used in the intended manner and under normal conditions.
- There are dishonest and possibly illegal methods used to breach the code protection feature. All of these methods, to our knowledge, require using the Microchip products in a manner outside the operating specifications contained in Microchip's Data Sheets. Most likely, the person doing so is engaged in theft of intellectual property.
- Microchip is willing to work with the customer who is concerned about the integrity of their code.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of their code. Code protection does not mean that we are guaranteeing the product as "unbreakable."

Code protection is constantly evolving. We at Microchip are committed to continuously improving the code protection features of our products. Attempts to break Microchip's code protection feature may be a violation of the Digital Millennium Copyright Act. If such acts allow unauthorized access to your software or other copyrighted work, you may have a right to sue for relief under that Act.

Information contained in this publication regarding device applications and the like is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION, INCLUDING BUT NOT LIMITED TO ITS CONDITION, QUALITY, PERFORMANCE, MERCHANTABILITY OR FITNESS FOR PURPOSE. Microchip disclaims all liability arising from this information and its use. Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights.

Trademarks

The Microchip name and logo, the Microchip logo, dsPIC, KEELOQ, KEELOQ logo, MPLAB, PIC, PICmicro, PICSTART, PIC³² logo, rPIC and UNI/O are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.


FilterLab, Hampshire, HI-TECH C, Linear Active Thermistor, MXDEV, MXLAB, SEEVAL and The Embedded Control Solutions Company are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Analog-for-the-Digital Age, Application Maestro, chipKIT, chipKIT logo, CodeGuard, dsPICDEM, dsPICDEM.net, dsPICworks, dsSPEAK, ECAN, ECONOMONITOR, FanSense, HI-TIDE, In-Circuit Serial Programming, ICSP, Mindi, MiWi, MPASM, MPLAB Certified logo, MPLIB, MPLINK, mTouch, Omniscent Code Generation, PICC, PICC-18, PICDEM, PICDEM.net, PICkit, PICtail, REAL ICE, rfLAB, Select Mode, Total Endurance, TSHARC, UniWinDriver, WiperLock and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

All other trademarks mentioned herein are property of their respective companies.

© 2007-2011, Microchip Technology Incorporated, Printed in the U.S.A., All Rights Reserved.

 Printed on recycled paper.

ISBN: 978-1-61341-599-3

QUALITY MANAGEMENT SYSTEM
CERTIFIED BY DNV
== ISO/TS 16949:2009 ==

Microchip received ISO/TS-16949:2009 certification for its worldwide headquarters, design and wafer fabrication facilities in Chandler and Tempe, Arizona; Gresham, Oregon and design centers in California and India. The Company's quality system processes and procedures are for its PIC® MCUs and dsPIC® DSCs, KEELOQ® code hopping devices, Serial EEPROMs, microperipherals, nonvolatile memory and analog products. In addition, Microchip's quality system for the design and manufacture of development systems is ISO 9001:2000 certified.

Worldwide Sales and Service

AMERICAS

Corporate Office
2355 West Chandler Blvd.
Chandler, AZ 85224-6199
Tel: 480-792-7200
Fax: 480-792-7277
Technical Support:
<http://www.microchip.com/support>
Web Address:
www.microchip.com

Atlanta
Duluth, GA
Tel: 678-957-9614
Fax: 678-957-1455

Boston
Westborough, MA
Tel: 774-760-0087
Fax: 774-760-0088

Chicago
Itasca, IL
Tel: 630-285-0071
Fax: 630-285-0075

Cleveland
Independence, OH
Tel: 216-447-0464
Fax: 216-447-0643

Dallas
Addison, TX
Tel: 972-818-7423
Fax: 972-818-2924

Detroit
Farmington Hills, MI
Tel: 248-538-2250
Fax: 248-538-2260

Indianapolis
Noblesville, IN
Tel: 317-773-8323
Fax: 317-773-5453

Los Angeles
Mission Viejo, CA
Tel: 949-462-9523
Fax: 949-462-9608

Santa Clara
Santa Clara, CA
Tel: 408-961-6444
Fax: 408-961-6445

Toronto
Mississauga, Ontario,
Canada
Tel: 905-673-0699
Fax: 905-673-6509

ASIA/PACIFIC

Asia Pacific Office
Suites 3707-14, 37th Floor
Tower 6, The Gateway
Harbour City, Kowloon
Hong Kong
Tel: 852-2401-1200
Fax: 852-2401-3431

Australia - Sydney
Tel: 61-2-9868-6733
Fax: 61-2-9868-6755

China - Beijing
Tel: 86-10-8569-7000
Fax: 86-10-8528-2104

China - Chengdu
Tel: 86-28-8665-5511
Fax: 86-28-8665-7889

China - Chongqing
Tel: 86-23-8980-9588
Fax: 86-23-8980-9500

China - Hangzhou
Tel: 86-571-2819-3187
Fax: 86-571-2819-3189

China - Hong Kong SAR
Tel: 852-2401-1200
Fax: 852-2401-3431

China - Nanjing
Tel: 86-25-8473-2460
Fax: 86-25-8473-2470

China - Qingdao
Tel: 86-532-8502-7355
Fax: 86-532-8502-7205

China - Shanghai
Tel: 86-21-5407-5533
Fax: 86-21-5407-5066

China - Shenyang
Tel: 86-24-2334-2829
Fax: 86-24-2334-2393

China - Shenzhen
Tel: 86-755-8203-2660
Fax: 86-755-8203-1760

China - Wuhan
Tel: 86-27-5980-5300
Fax: 86-27-5980-5118

China - Xian
Tel: 86-29-8833-7252
Fax: 86-29-8833-7256

China - Xiamen
Tel: 86-592-2388138
Fax: 86-592-2388130

China - Zhuhai
Tel: 86-756-3210040
Fax: 86-756-3210049

ASIA/PACIFIC

India - Bangalore
Tel: 91-80-3090-4444
Fax: 91-80-3090-4123

India - New Delhi
Tel: 91-11-4160-8631
Fax: 91-11-4160-8632

India - Pune
Tel: 91-20-2566-1512
Fax: 91-20-2566-1513

Japan - Yokohama
Tel: 81-45-471- 6166
Fax: 81-45-471-6122

Korea - Daegu
Tel: 82-53-744-4301
Fax: 82-53-744-4302

Korea - Seoul
Tel: 82-2-554-7200
Fax: 82-2-558-5932 or
82-2-558-5934

Malaysia - Kuala Lumpur
Tel: 60-3-6201-9857
Fax: 60-3-6201-9859

Malaysia - Penang
Tel: 60-4-227-8870
Fax: 60-4-227-4068

Philippines - Manila
Tel: 63-2-634-9065
Fax: 63-2-634-9069

Singapore
Tel: 65-6334-8870
Fax: 65-6334-8850

Taiwan - Hsin Chu
Tel: 886-3-5778-366
Fax: 886-3-5770-955

Taiwan - Kaohsiung
Tel: 886-7-536-4818
Fax: 886-7-330-9305

Taiwan - Taipei
Tel: 886-2-2500-6610
Fax: 886-2-2508-0102

Thailand - Bangkok
Tel: 66-2-694-1351
Fax: 66-2-694-1350

EUROPE

Austria - Wels
Tel: 43-7242-2244-39
Fax: 43-7242-2244-393

Denmark - Copenhagen
Tel: 45-4450-2828
Fax: 45-4485-2829

France - Paris
Tel: 33-1-69-53-63-20
Fax: 33-1-69-30-90-79

Germany - Munich
Tel: 49-89-627-144-0
Fax: 49-89-627-144-44

Italy - Milan
Tel: 39-0331-742611
Fax: 39-0331-466781

Netherlands - Druenen
Tel: 31-416-690399
Fax: 31-416-690340

Spain - Madrid
Tel: 34-91-708-08-90
Fax: 34-91-708-08-91

UK - Wokingham
Tel: 44-118-921-5869
Fax: 44-118-921-5820