

# CSC 7700: Scientific Computing

## Module A: Basic Skills

### Lecture 7: Compiling, Debugging, Profiling

Dr Frank Löffler

November 2nd 2010





# Compiling



# Compiler

- ▶ computer program that transforms source code written in a programming language (the *source language*) into another computer language

Reason:

- ▶ CPU can only directly execute *machine code*.
- ▶ Developer wants to program in high-level language.

Hofstadter: “*Looking at a program written in machine language is vaguely comparable to looking at a DNA molecule atom by atom.*”

Don't confuse *machine code* with *Assembly language*

- ▶ Low-level programming language
- ▶ Symbolic representation of the binary machine code



# Terms

## Cross-compiler

- ▶ Generates *target code* which can only be run on different CPU/OS than compiling host

## Decompiler

- ▶ Translates from a low level language to a higher level one

## Language translator

- ▶ translates between high-level languages


## Bootstrapping

- ▶ Writing a compiler in the target language which it is intended to compile (chicken and egg problem)



# Compiler operations

- ▶ Preprocessing
- ▶ Lexical analysis
- ▶ Parsing
- ▶ Semantic analysis
- ▶ Code generation
- ▶ Code optimization



# Compiler structure

## 1. Frontend

- ▶ checks whether the program is correctly written in terms of the programming language syntax and semantics
- ▶ errors are reported, if any, in a useful way
- ▶ type checking is also performed by collecting type information
- ▶ generates intermediate representation for the middle-end

## 2. Middle-end

- ▶ optimizations for performance
- ▶ generates intermediate representation for the back-end

## 3. Back-end

- ▶ translation of intermediate representation into the target assembly code
- ▶ utilizes the hardware by figuring out how to e.g. keep parallel FUs busy



# Executable

File that causes a computer “to perform indicated tasks according to encoded instructions”

- ▶ Sometimes designated filename extensions (such as .exe)
- ▶ Sometimes noted alongside file metadata (such as “execute bit”)
- ▶ Usually file is checked before actual execution regardless
- ▶ Types:
  - ▶ Binary format, containing machine code (e.g. ELF)
  - ▶ Source code for use in scripting language (in a loose sense)
- ▶ Example formats
  - ▶ a.out - “assembler output”
  - ▶ COFF - “Common Object File Format”
  - ▶ ELF - “Executable and Linkable Format”
  - ▶ DOS COM - “Command file”
  - ▶ PE - “Portable Executable”





# Object files / Libraries

Object file: Organized collection of separate, named sequences of machine code

- ▶ contains instructions for the host machine to accomplish some task
- ▶ possibly accompanied by related data and metadata
- ▶ linker is typically used to generate an executable or library by combining parts of object files


Library: Collection of subroutines or classes

- ▶ Contains code and data that provide services to independent programs
- ▶ Allows the sharing and changing of code and data in a modular fashion



## Library real-world example

### Playing Ogg Vorbis



# Library types

- ▶ Static

- ▶ collection of ordinary object files
- ▶ conventional suffix: `.a`
- ▶ created using an archiver program, e.g. `ar`:  
`ar rcs my_library.a file1.o file2.o`
- ▶ linked into executable at compile time

- ▶ Shared / Dynamic

- ▶ not included in executable
- ▶ conventional suffix: `.so` or `.dll`
- ▶ Two types:
  - ▶ Loaded at program start
  - ▶ Loaded when needed while program execution



# Shared Library names

## Shared Library Names

- ▶ “linker name”
  - ▶ prefix `lib` + name of library + `.so`
  - ▶ used e.g. when requesting to link against this library
  - ▶ usually link to “soname”
  - ▶ example: `libreadline.so`
- ▶ “soname”
  - ▶ linker name + `.` + version number
  - ▶ changes with every library API change
  - ▶ usually link to “real name”
  - ▶ example: `libreadline.so.3`
- ▶ “real name”
  - ▶ filename of file containing actual library code
  - ▶ soname + `.` + minor number (+ `.` + release number)
  - ▶ example: `libreadline.so.3.0.0`



# Filesystem placement

## Filesystem Hierarchy Standard (FHS):

- ▶ Most libraries: `/usr/lib`
- ▶ Libraries required for startup: `/lib`
- ▶ Libraries that are not part of the system: `/usr/local/lib`

## Starting ELF executable:

- ▶ Program loader is loaded and run (`/lib/ld-linux.so.X`)
- ▶ Loader finds and loads all other required shared libraries
- ▶ Uses library location information cache (see `ldconfig`)



# Creating shared library

- ▶ Use “position independent code”: compiler flag `-fPIC` / `-fpic`
- ▶ Specify soname to linker: `-soname your_soname`, or through compiler: `-Wl,-soname,your_soname`

In one command:

```
gcc -shared -Wl,-soname,your_soname \  
    -o library_name file_list library_list
```

Complete Example:

```
gcc -fPIC -g -c -Wall a.c  
gcc -fPIC -g -c -Wall b.c  
gcc -shared -Wl,-soname,libmystuff.so.1 \  
    -o libmystuff.so.1.0.1 a.o b.o -lc
```



# Environment Variables

Colon-separated directory lists:

- ▶ `LD_RUN_PATH`
  - ▶ Additional search-path for libraries, encoded into executable while linking
  - ▶ Ignored if `-R/-rpath` linker option given
  - ▶ Check binary: `readelf -d FILE | grep RPATH`
- ▶ `LD_LIBRARY_PATH`
  - ▶ Additional search-path for libraries, used at run-time by dynamical linker
  - ▶ Good for testing, but try to avoid longer use



# Library path examples

- ▶ Set rpath on executable/library through compiler  
`-Wl,-rpath,/path/to/used/library`
- ▶ Add directory to search-path for linking files  
`LD_RUN_PATH=/path/to/used/library:$LD_RUN_PATH`
- ▶ Add directory to temporary search run-time path  
`LD_LIBRARY_PATH=/path/to/used/library:$LD_LIBRARY_PATH`
- ▶ List used libraries of object

```
$ ldd /bin/cat
linux-vdso.so.1 => (0x00007fff4fde3000)
libc.so.6 => /lib64/libc.so.6 (0x0000003afa600000)
/lib64/ld-linux-x86-64.so.2 (0x0000003afa200000)
```





# List symbols

`nm`

- ▶ Reports symbols in given library
- ▶ Details: name, value, type, definition location (filename and line number)
- ▶ Local types: lower case
- ▶ Global types: upper case
  - ▶ T: typical definition in code section
  - ▶ D: initialized data section
  - ▶ B: uninitialized data section
  - ▶ U: undefined symbol (used but not defined here)
  - ▶ W: weak symbol, can be overwritten

Example:

```
$ nm /lib/libm.so.6 | grep " sqrt"  
0000a870 W sqrt  
00011840 W sqrtf  
00019180 W sqrtl
```



# GCC Command Reference

<b>-c</b>	Compile, but don't link
<b>-o filename</b>	Specify output filename
<b>-v</b>	Be verbose
<b>-Wall</b>	Print warnings about (potential) problems
<b>-g</b>	Produce debugging information
<b>-pg</b>	Produce profiling information for gprof
<b>-O0</b>	Optimize nothing
<b>-O, -O1</b>	Optimize some
<b>-O2</b>	Optimize a lot
<b>-O3</b>	Optimize the most, potentially unreliable
<b>-std=standard</b>	Select language standard (e.g. c99)
<b>-Idirectory</b>	Searched directory for header files
<b>-Ldirectory</b>	Searches directory for libraries while linking
<b>-llibrary</b>	Links against library, put after needing object



# Debugging




# Bugs

Thomas Edison in 1878: "It has been just so in all of my inventions. The first step is an intuition, and comes with a burst, then difficulties arise—this thing gives out and [it is] then that 'Bugs' — as such little faults and difficulties are called—show themselves and months of intense watching, study and labor are requisite before commercial success or failure is certainly reached."

9/9

0800 Antenn started  
1000 stopped - antenn ✓ { 1.2700 9.030 847 025  
1300 (032) MP - MC 2.130476415 9.037 846 945 convch  
(033) PRO 2 2.130476415 4.615 925059(-2)  
convch 2.130676415  
Relays 6-2 in 033 failed speed speed test  
in relay 11.000 test.

1100 Started Cosine Tape (Sine check)  
1525 Started Multi-Adder Test.

1545  Relay #70 Panel F  
(mott) in relay.


First actual case of bug being found.  
1700 Antenn started.  
1700 closed down.

Relay 2145  
Relay 2376

1947:



# Bug prevention



oskay@flickr

- ▶ Programming style
- ▶ Programming techniques  
e.g. self-checking programs
- ▶ Development methodologies  
e.g. managing programmer activity
- ▶ Programming language support  
e.g. types, name spaces, modules
- ▶ Code analysis
- ▶ Instrumentation

# Debugging

Methodical process of finding and reducing the number of bugs

Debugger: software tools which enable the programmer to

- ▶ monitor the execution of a program
- ▶ stop it
- ▶ re-start it
- ▶ set breakpoints
- ▶ change values in memory



# Debugging Steps

1. Reproduce problem
  - ▶ Problem might be reported by someone else
  - ▶ Problem might only occur in “some situations”
  - ▶ Knowing what “some situations” means can be important
2. Simplify problem
  - ▶ might be parallel
  - ▶ might take very long to reproduce
3. Use debugger to examine program states
  - ▶ variable values
  - ▶ call stack
4. Find cause of problem
  - ▶ not necessarily where it shows
5. Fix it




# Debugging Techniques

- ▶ Print debugging (tracing)
  - ▶ watching print/trace statements, indicating flow of process
- ▶ Direct debugging by
  - ▶ Starting process inside debugger
  - ▶ Attaching debugger to running, local process
- ▶ Post-mortem debugging
  - ▶ debugging after program has crashed
  - ▶ e.g. analysis of memory dump (core dump)
- ▶ Remote debugging
  - ▶ Debug process on remote system via network interaction





# GDB - The GNU Project Debugger




Can

- ▶ Start programs, specifying anything that might affect its behavior
- ▶ Make programs stop on specified conditions
- ▶ Examine what has happened, when programs stop/crash
- ▶ Change things during program execution
- ▶ Debug many languages, e.g. Ada, C, C++, Objective-C, Pascal
- ▶ Debug locally or remotely
- ▶ Can run on most popular Unix and Microsoft Windows variants

# DDD - Display Data Debugger

- ▶ Graphical front-end for command-line debuggers (e.g. gdb)
- ▶ Can display data structure and contents, including dependencies
- ▶ Can plot numerical data



# GDB Example

```
1  #include <stdio.h>
2
3  int main()
4  {
5      /* Initialize variables */
6      const int x    = 10;
7      int factorial = 1;
8      /* Loop through all x */
9      for (int i=0; i<=x; i++)
10     {
11         factorial *= i;
12     }
13     printf("%d! is %d\n", x, factorial);
14     return 0;
15 }
```



# GDB Example - Run program

- ▶ Compile: `gcc -g -std=c99 -o A7 A7.c`
- ▶ Run: `10! is 0` → bug
- ▶ Debug:

```
$ gdb A7
(gdb) b 11
Breakpoint 1 at 0x400501: file A7.c, line 11.
(gdb) r
Starting program: /home/login/path/A7
Breakpoint 1, main () at A7.c:11
11      factorial *= i;
(gdb) print factorial
$2 = 1
(gdb) print i
$1 = 0
condition 1 i==5
(gdb) c
Breakpoint 1, main () at A7.c:11
11      factorial *= i;
(gdb) print i
$1 = 5
(gdb) print factorial
$3 = 0
```



# GDB Example - Attach to process

- ▶ Find xpdf process number: `ps afxuwww | grep xpdf`
- ▶ Attach gdb:

```
$ gdb -p 5256
```

```
...
```

```
Attaching to process 5256
```

```
Reading symbols from /usr/bin/xpdf.bin...(no debugging symbols found)...done.
```

```
Reading symbols from /usr/lib/libt1.so.5...(no debugging symbols found)...done.
```

```
...
```

```
0x00007f64dcf69b9f in poll () from /lib/libc.so.6
```

```
(gdb) bt
```

```
#0 0x00007f64dcf69b9f in poll () from /lib/libc.so.6
```

```
#1 0x00007f64de9269fa in _XtWaitForSomething () from /usr/lib/libXt.so.6
```

```
#2 0x00007f64de927b03 in XtAppNextEvent () from /usr/lib/libXt.so.6
```

```
#3 0x00007f64de91ac9b in XtAppMainLoop () from /usr/lib/libXt.so.6
```

```
#4 0x000000000004aa6b6 in ?? ()
```

```
#5 0x00007f64dcec11a6 in __libc_start_main () from /lib/libc.so.6
```

```
#6 0x00000000000406329 in ?? ()
```



# GDB Example - Dead process

- ▶ Run normally: Segmentation fault (core dumped)
- ▶ Run gdb on “core dump”:

```
$ gdb testit core
```

```
Core was generated by 'testit'.
```

```
Program terminated with signal 11, Segmentation fault.
```

```
Reading symbols from /usr/lib/libstdc++-libc6.1-1.so.2...done.
```

```
Reading symbols from /lib/libm.so.6...done.
```

```
Reading symbols from /lib/libc.so.6...done.
```

```
Reading symbols from /lib/ld-linux.so.2...done.
```

```
#0  0x804851a in main () at testit.c:10
```

```
10          temp[3]='F';
```

Look at declaration of temp: `char *temp = "Paras";`



# GDB Command Reference

<b>gdb</b> program [core]	debug program [using coredump]
<b>r</b> [arglist]	start program [with arglist]
<b>p</b> expr	print value of expr
<b>set var=expr</b>	set variable to value of expr
<b>c</b>	continue
<b>n</b>	next line, step over function calls
<b>s</b>	next line, step into function calls
<b>b</b> [file:]function	set breakpoint at function [in file]
<b>b</b> [file:]line	set breakpoint at line [in file]
<b>b ... if</b> expr	break conditionally on nonzero expr
<b>watch</b> expr	set watchpoint for expr
<b>info break</b>	show defined breakpoints
<b>info watch</b>	show defined watchpoints
<b>clear ...</b>	clear breakpoint
<b>bt</b>	backtrace: show program stack
<b>up</b> n	select frame n frames up
<b>down</b> n	select frame n frames down
<b>info args</b>	arguments of selected frame
<b>info locals</b>	local variables of selected frame
<b>q</b>	quit



# Profiling





# Profiling

Investigation of a program's behavior using information gathered as the program executes, usually with the goals

- ▶ to increase its overall speed
- ▶ to decrease its memory requirement

Profiler measures typically the frequency and duration of function calls and can output:

- ▶ A statistical summary of the events observed (a profile)
- ▶ A stream of recorded events (a trace)
- ▶ An ongoing interaction with the hypervisor

Can in simple cases done by hand by inserting

- ▶ print statements and directly observing output at runtime
- ▶ user-built timers around interesting program parts



# Profiler types

## Statistical profilers

- ▶ Operate by sampling: probes the target program's program counter at regular intervals
- ▶ Typically less numerically accurate and specific
- ▶ Allow for near full speed
- ▶ Can often provide a more accurate picture
  - ▶ not as intrusive to the target program
  - ▶ don't have as many side effects

## Instrumenting profilers

- ▶ Instrument the target program with additional instructions
- ▶ Can cause changes in the performance of the program
- ▶ Can be on just one machine instruction on some targets
- ▶ Impact of instrumentation can often be eliminated from the results



# An example: gprof

gprof: statistical and instrumenting profiler

- ▶ Compile program to generate profile data: `-g -pg`
- ▶ Execute program to generate profile data: `gmon.out`
- ▶ Run gprof:

```
gprof options [executable [profile-data-files ...]]
```

Some gprof options:

- a suppresses the printing of statically declared (private) functions
- e function name don't print information about the function function name
- f function name limit the call graph to the function function name and its children



# An example: gprof

## Flat profile:

Each sample counts as 0.01 seconds.

% time	cumulative seconds	self seconds	calls	self ms/call	total ms/call	name
33.34	0.02	0.02	7208	0.00	0.00	open
16.67	0.03	0.01	244	0.04	0.12	offtime
16.67	0.04	0.01	8	1.25	1.25	memccpy
16.67	0.05	0.01	7	1.43	1.43	write
16.67	0.06	0.01				mcount
0.00	0.06	0.00	236	0.00	0.00	tzset
0.00	0.06	0.00	192	0.00	0.00	tolower
0.00	0.06	0.00	47	0.00	0.00	strlen
0.00	0.06	0.00	45	0.00	0.00	strchr
0.00	0.06	0.00	1	0.00	50.00	main
0.00	0.06	0.00	1	0.00	0.00	memcpy
0.00	0.06	0.00	1	0.00	10.11	print
0.00	0.06	0.00	1	0.00	0.00	profil
0.00	0.06	0.00	1	0.00	50.00	report



# An example: gprof

## Call graph:

index	called	name
	72384/72384	sym_id_parse [54]
[3]	72384	match [3]
-----		
	4/9052	cg_tally [32]
	3016/9052	hist_print [49]
	6032/9052	propagate_flags [52]
[4]	9052	sym_lookup [4]
-----		
	5766/5766	core_create_function_syms [41]
[5]	5766	core_sym_class [5]
-----		
	24/1537	parse_spec [19]
	1513/1537	core_create_function_syms [41]
[6]	1537	sym_init [6]
-----		
	1511/1511	core_create_function_syms [41]
[7]	1511	get_src_info [7]
-----		
	2/1510	arc_add [31]
	1508/1510	cg_assemble [38]
[8]	1510	arc_lookup [8]
-----		
	1509/1509	cg_dfn [15]
[9]	1509	is_numbered [9]
-----		
	1508/1508	propagate_flags [52]
[10]	1508	inherit_flags [10]
-----		
	1508/1508	cg_dfn [15]
[11]	1508	is_busy [11]



## Module A: The End