

☰ Documentation

[Apple Maps Server API](#) / Search for a place using an identifier

Web Service Endpoint

Search for a place using an identifier

Obtain a Place object for a given Place ID.

Apple Maps Server API 1.2+

URL

```
GET https://maps-api.apple.com/v1/place/:id
```

Path Parameters

id **(Required)** A single Place ID.
string

Query Parameters

lang The language code for the response.
Lang Default: en-US

Response Codes

200	OK
Place	A Place result. Content-Type: application/json
400	Bad Request
ErrorResponse	An ErrorResponse object that contains an error message and an array of strings that contain additional details about the error. Content-Type: application/json

401 ErrorResponse	Unauthorized An ErrorResponse object that contains an error message that indicates the Maps access token is missing or invalid, and an array of strings that contains additional details about the error. Content-Type: application/json
500 ErrorResponse	Internal Server Error An ErrorResponse object that contains a server error message and an array of strings that describe additional details about the error. Content-Type: application/json

See Also

Searching

`type AddressCategory`

Search categories related to political geographical boundaries.

`type SearchACResultType`

An enumerated string that indicates the result type for the search request.

`type SearchResultType`

An enumerated string that indicates the result type for the search autocomplete request.

`object AlternateIdsResponse`

A list of alternate Place IDs and associated errors.

`object AlternateIdsResponse.AlternateIds`

Contains a list of alternate Place IDs for a given Place ID.

`object PlacesResponse`

A list of Place IDs and errors.

`object PlacesResponse.PlaceLookupError`

An error associated with a lookup call.

`Search for places that match specific criteria`

Find places by name or by specific search criteria.

`Search for places that meet specific criteria to autocomplete a place search`

Find results that you can use to autocomplete searches.

Search for places using multiple identifiers

Obtain a set of Place objects for a given set of Place IDs.

Obtain a list of alternate place identifiers

Get a list of alternate Place IDs given one or more Place IDs.