

[XCUIAutomation](#) / [XCUIScreenShot](#)

Class

XCUIScreenShot

A captured image of a screen, app, or UI element state.

iOS | iPadOS | Mac Catalyst | macOS | tvOS | visionOS | watchOS | Xcode 16.3+

```
@MainActor  
class XCUIScreenShot
```

Overview

Screenshots capture the current UI state of classes that conform to the [XCUIScreenShot Providing](#) protocol, such as [XCUIScreen](#) and [XCUIElement](#). Each screenshot contains an image representation of the captured UI at the point the screenshot was taken.

The following code demonstrates taking screenshots of a screen and a UI element:

```
func testTakeScreenshots() {  
  
    // Take a screenshot of the current device's main screen.  
    let mainScreenScreenshot = XCUIScreen.main.screenshot()  
  
    // Take a screenshot of an app's first window.  
    let app = XCUIApplication()  
    app.launch()  
    let windowScreenshot = app.windows.firstMatch.screenshot()  
  
}
```

If you use [XCTest](#) for your UI automation tests, you can attach a screenshot of your app's UI to a test or activity to store it for later analysis. Create an attachment for a screenshot by calling the

`XCTAttachment` initializer `init(screenshot:)` or `init(screenshot:quality:)`. Add the attachment to a test or activity by calling the `XCTActivity` method `add(_ :)`. For more information, see [Adding Attachments to Tests, Activities, and Issues](#).

Topics

Screenshot representations

`var image: UIImage`

A representation of the screenshot as a platform-native image object.

`var pngRepresentation: Data`

A representation of the screenshot as PNG image data.

Relationships

Inherits From

`NSObject`

Conforms To

`CVarArg`

`CustomDebugStringConvertible`

`CustomStringConvertible`

`Equatable`

`Hashable`

`NSObjectProtocol`

`Sendable`

See Also

Screenshots

```
class XCUIScreen
```

A physical screen attached to a device.

```
protocol XCUIScreenScreenshotProviding
```

A type that can provide a screenshot of its current UI state.