

[Background Tasks](#) / BGTaskRequest

Class

BGTaskRequest

An abstract class for representing task requests.

iOS 13.0+ | iPadOS 13.0+ | Mac Catalyst 13.1+ | tvOS 13.0+ | visionOS 1.0+

```
class BGTaskRequest
```

Topics

Configuring a Task Request

```
var earliestBeginDate: Date?
```

The earliest date and time at which to run the task.

```
var identifier: String
```

The identifier of the task associated with the request.

Relationships

Inherits From

NSObject

Inherited By

BGAppRefreshTaskRequest, BGContinuedProcessingTaskRequest, BGProcessingTaskRequest

Conforms To

CVarArg
CustomDebugStringConvertible
CustomStringConvertible
Equatable
Hashable
NSCopying
NSObjectProtocol

See Also

Task requests

`class` BGProcessingTaskRequest

A request to launch your app in the background to execute a processing task that can take minutes to complete.

`class` BGAppRefreshTaskRequest

A request to launch your app in the background to execute a short refresh task.

`class` BGHealthResearchTaskRequest

A request to launch your app in the background to execute processing for a health research study in which a user participates.

`class` BGContinuedProcessingTaskRequest

A request for a workload that the system continues processing even if a person backgrounds the app.