

[Foundation](#) / NSTemporaryDirectory()

Function

NSTemporaryDirectory()

Returns the path of the temporary directory for the current user.

iOS 2.0+ | iPadOS 2.0+ | Mac Catalyst 13.0+ | macOS 10.0+ | tvOS 9.0+ | visionOS 1.0+ | watchOS 2.0+

```
func NSTemporaryDirectory() -> String
```

Return Value

A string containing the path of the temporary directory for the current user.

Discussion

See the [FileManager](#) method [url\(for:in:appropriateFor:create:\)](#) for the preferred means of finding the correct temporary directory.

For more information about temporary files, see [File System Programming Guide](#).

See Also

Related Documentation

```
func NSSearchPathForDirectoriesInDomains(FileManager.SearchPathDirectory, FileManager.SearchPathDomainMask, Bool) -> [String]
```

Creates a list of directory search paths.

Accessing user directories

```
var homeDirectoryForCurrentUser: URL
```

The home directory for the current user.

```
func NSHomeDirectory() -> String
```

Returns the path to either the user's or application's home directory, depending on the platform.

```
func NSUserName() -> String
```

Returns the logon name of the current user.

```
func NSFullUserName() -> String
```

Returns a string containing the full name of the current user.

```
func homeDirectory(forUser: String) -> URL?
```

Returns the home directory for the specified user.

```
func NSHomeDirectoryForUser(String?) -> String?
```

Returns the path to a given user's home directory.

```
var temporaryDirectory: URL
```

The temporary directory for the current user.