

[Intents](#) / `INSendPaymentIntentResponseCode`

## Enumeration

# INSendPaymentIntentResponseCode

Constants indicating the state of the response.

iOS 10.0+ | iPadOS 10.0+ | Mac Catalyst 13.1+ | visionOS 1.0+ | watchOS 3.2+

```
enum INSendPaymentIntentResponseCode
```

## Topics

### Constants

`case unspecified`

The response didn't specify a response code.

`case ready`

You are ready to handle the intent.

`case inProgress`

You are in the process of handling the intent.

`case success`

You successfully handled the intent.

`case failure`

You were unable to send the funds.

`case failureRequiringAppLaunch`

The user must launch your app to send the funds.

`case failureCredentialsUnverified`

You were unable to deliver the request.

`case failurePaymentsAmountBelowMinimum`

You were unable to deliver the request.

`case failurePaymentsAmountAboveMaximum`

You were unable to deliver the request.

`case failurePaymentsCurrencyUnsupported`

You were unable to deliver the request.

`case failureInsufficientFunds`

You were unable to deliver the request.

`case failureNoBankAccount`

You were unable to deliver the request.

`case failureNotEligible`

The request failed because a user was not eligible to perform the transaction.

`case failureTermsAndConditionsAcceptanceRequired`

The request failed because the user must accept the app's terms and conditions.

## Initializers

`init?(rawValue: Int)`

---

# Relationships

## Conforms To

BitwiseCopyable

Equatable

Hashable

RawRepresentable

Sendable

SendableMetatype

---

## See Also

### Getting the Response Code

```
var code: INSendPaymentIntentResponseCode
```

The code indicating whether you successfully handled the intent.