

[Wi-Fi Aware](#) / [WAPairedDevice](#) / WAPairedDevice.DevicesSequence

## Structure

# WAPairedDevice.DevicesSequence

A sequence that vends updates to a paired device list, as the list changes.

iOS 26.0+ | iPadOS 26.0+

```
struct DevicesSequence
```

## Overview

The `DevicesSequence` produces an asynchronous sequence of [WAPairedDevice.Devices](#) items, providing the latest snapshot of the paired devices known to your app.

## Topics

### Getting an initial snapshot

```
func current() async throws -> WAPairedDevice.DevicesSequence.Element?
```

Fetches a one-time snapshot of all paired devices that are currently known and accessible to your app.

### Getting async updates

```
class AsyncIterator
```

An iterator for the sequence of devices.

```
func makeAsyncIterator() -> WAPairedDevice.DevicesSequence.Async  
Iterator
```

Makes an asynchronous iterator that provides successive device snapshots when the list of paired devices known to the app changes.

```
typealias Element
```

A dictionary holding a snapshot of currently paired devices accessible to your app.

---

## Relationships

### Conforms To

AsyncSequence

---

## See Also

### Paired devices

```
struct WAPairedDevice
```

A known Wi-Fi Aware device that your app can connect to.

```
typealias Devices
```

A dictionary holding a snapshot of currently paired devices accessible and known to your app.

```
struct PairingInfo
```

A collection of unauthenticated information the system receives from a device before it's paired for the first time.