

[Foundation](#) / [NSUserNotificationAction](#) **Deprecated**

Class

NSUserNotificationAction **Deprecated**

An action that the user can take in response to receiving a notification.

macOS 10.10–11.0 **Deprecated**

```
class NSUserNotificationAction
```

Deprecated

Use the [User Notifications](#) framework instead.

Overview

User notifications can specify one or more actions to show to the user by using the [additional](#) [ActivationAction](#) or [additionalActions](#) properties. [NSUserNotificationAction](#) objects contain the localized title shown to the user and an identifier used to differentiate between presented actions.

Topics

Creating User Notification Actions

~~convenience~~ ~~`init(identifier: String?, title: String?)`~~

Creates a user notification action with a specified identifier and title.

Getting the Identifier and Title

~~var identifier: String?~~

The identifier for the user notification action.

~~var title: String?~~

The localized title shown to the user.

Relationships

Inherits From

NSObject

Conforms To

CVarArg

CustomDebugStringConvertible

CustomStringConvertible

Equatable

Hashable

NSCopying

NSObjectProtocol

See Also

User Notifications

~~class NSUserNotification~~

A notification that can be scheduled for display in the notification center.

Deprecated

~~class NSUserNotificationCenter~~

An object that delivers notifications from apps to the user.

Deprecated

`protocol NSNotificationCenterDelegate`

An interface that enables customizing the behavior of the default notification center.