

[Foundation](#) / [...](#) / [FileManager.SearchPathDirectory](#) / FileManager.SearchPathDirectory.itemReplacementDirectory

Case

FileManager.SearchPathDirectory.itemReplacementDirectory

The constant used to create a temporary directory.

iOS 4.0+ | iPadOS 4.0+ | Mac Catalyst 13.1+ | macOS 10.6+ | tvOS 9.0+ | visionOS 1.0+ | watchOS 2.0+

```
case itemReplacementDirectory
```

Discussion

Pass this constant to the [FileManager](#) method [url\(for:in:appropriateFor:create:\)](#) in order to create a temporary directory.

See Also

Directory Locations

```
case applicationDirectory
```

Supported applications (/Applications).

```
case demoApplicationDirectory
```

Unsupported applications and demonstration versions.

```
case developerApplicationDirectory
```

Developer applications (/Developer/Applications).

case adminApplicationDirectory

System and network administration applications.

case libraryDirectory

Various user-visible documentation, support, and configuration files (/Library).

case developerDirectory

Developer resources (/Developer).

case userDirectory

User home directories (/Users).

case documentationDirectory

Documentation.

case documentDirectory

Document directory.

case coreServiceDirectory

Core services (System/Library/CoreServices).

case autosavedInformationDirectory

The user's autosaved documents (Library/Autosave Information).

case desktopDirectory

The user's desktop directory.

case cachesDirectory

Discardable cache files (Library/Caches).

case applicationSupportDirectory

Application support files (Library/Application Support).

case downloadsDirectory

The user's downloads directory.