

[SwiftData](#) / Additional query macros

API Collection

Additional query macros

Supplementary macros that enable you to narrow query results and tell SwiftData how to sort and order those results.

Topics

Basic queries

```
macro Query(animation: Animation)
```

Fetches all instances of the attached model type, using the specified animation to animate any subsequent changes.

```
macro Query(transaction: Transaction)
```

Fetches all instances of the attached model type, using the specified transaction to animate any subsequent changes.

Predicate-based queries

```
macro Query<Element>(filter: Predicate<Element>?, sort: [SortDescriptor<Element>], animation: Animation)
```

Fetches a sorted subset of the attached model type that satisfy the specified predicate.

```
macro Query<Value, Element>(filter: Predicate<Element>?, sort: KeyPath<Element, Value>, order: SortOrder, animation: Animation)
```

Fetches a subset of the attached model type, in a specific order, by sorting on a nonoptional attribute.

```
macro Query<Value, Element>(filter: Predicate<Element>?, sort: KeyPath<Element, Value?>, order: SortOrder, animation: Animation)
```

Fetches a subset of the attached model type, in a specific order, by sorting on an optional attribute.

```
macro Query<Element>(filter: Predicate<Element>?, sort: [SortDescriptor<Element>], transaction: Transaction?)
```

Fetches and sorts the subset of the attached model type that satisfy the specified predicate.

```
macro Query<Value, Element>(filter: Predicate<Element>?, sort: KeyPath<Element, Value>, order: SortOrder, transaction: Transaction?)
```

Fetches a subset of the attached model type, in a specific order, by sorting on a nonoptional attribute.

```
macro Query<Value, Element>(filter: Predicate<Element>?, sort: KeyPath<Element, Value?>, order: SortOrder, transaction: Transaction?)
```

Fetches a subset of the attached model type, in a specific order, by sorting on an optional attribute.

Descriptor-based queries

```
macro Query<Element>(FetchDescriptor<Element>, animation: Animation)
```

Fetches only the subset of the attached model type that satisfy the provided fetch descriptor's criteria.

```
macro Query<Element>(FetchDescriptor<Element>, transaction: Transaction?)
```

Fetches only the subset of the attached model type that satisfy the provided fetch descriptor's criteria.

See Also

Model fetch

`{}` Filtering and sorting persistent data

Manage data store presentation using predicates and dynamic queries.

```
macro Query()
```

Fetches all instances of the attached model type.

```
struct Query
```

A type that fetches models using the specified criteria, and manages those models so they remain in sync with the underlying data.

`struct FetchDescriptor`

A type that describes the criteria, sort order, and any additional configuration to use when performing a fetch.