

[Intents](#) / INStartWorkoutIntentResponseCode

Enumeration

INStartWorkoutIntentResponseCode

Constants that indicate the response state.

iOS 10.0+ | iPadOS 10.0+ | Mac Catalyst 13.1+ | visionOS 1.0+ | watchOS 3.2+

```
enum INStartWorkoutIntentResponseCode
```

Topics

Response State

`case unspecified`

A response code that indicates an unknown state.

`case ready`

A response code that indicates app readiness.

~~`case continueInApp`~~

A response code that indicates your app extension is ready to transfer control to the app to start the workout.

Deprecated

`case success`

A response code that indicates your app succeeded.

`case handleInApp`

A response code that indicates you want to handle the intent in your app instead.

`case failure`

A response code that indicates you were unable to start the specified workout.

`case failureRequiringAppLaunch`

A response code that indicates the user must launch your app to start the workout.

`case failureOngoingWorkout`

A response code that indicates a workout is already in progress, so another can't start.

`case failureNoMatchingWorkout`

A response code that indicates you didn't find the specified workout.

Initializers

`init?(rawValue: Int)`

Relationships

Conforms To

BitwiseCopyable
Equatable
Hashable
RawRepresentable
Sendable
SendableMetatype

See Also

Getting the Response Code

`var code: INStartWorkoutIntentResponseCode`

The code that indicates whether you successfully handled the intent.