

[Apple Pay Merchant Tok...](#) / Invalidate a Merchant Token

Web Service Endpoint

# Invalidate a Merchant Token

Invalidate a merchant token associated with your merchant identifier, making it invalid for future transaction authorizations.

App Store Connect API 1.0.10+

---

## URL

**POST** `https://apple-pay-gateway.apple.com/paymentservices/v1/merchantId/{merchantId}`,

## Path Parameters

**merchantId** **(Required)** Your merchant identifier.  
string

## Header Parameters

**Accept**  
string

**Content-Type** **(Required)**  
string

**x-request-id** **(Required)**  
string

## HTTP Body

[MerchantTokenUnlink Request](#)

The request body you use to specify the merchant token that Apple Pay should invalidate.

# Response Codes

## 204 No Content

Success. The service doesn't return any additional information.

## 400 Bad Request

### ErrorResponse

Invalid request. The merchant token identifier isn't valid for the merchant identifier.

Content-Type: application/json

## 500 Internal Server Error

### ErrorResponse

Internal server error.

Content-Type: application/json

# Discussion

When you call this endpoint, Apple Pay server unlinks — invalidates — the merchant token, and the token is no longer valid for future transaction authorizations. Call this endpoint in the following cases:

- Someone cancels a recurring transaction on your website or in your app that uses this merchant token
- Someone changes the payment method for a recurring transactions, for example, they stop using Apple Pay for the transaction

# See Also

## Merchant token invalidation

object MerchantTokenUnlinkRequest

The request body you use to invalidate a merchant token.