

[App Store Server API](#) / [Get Refund History V1](#) **Deprecated**

Web Service Endpoint

Get Refund History V1 **Deprecated**

Get a list of up to 50 of a customer's refunded in-app purchases for your app.

App Store Server API 1.1–1.6 **Deprecated**

Deprecated

Use [Get Refund History](#) instead.

URL

```
GET https://api.storekit.itunes.apple.com/inApps/v1/refund/lookup/{originalTransactionId}
```

Sandbox URL

```
GET https://api.storekit-sandbox.itunes.apple.com/inApps/v1/refund/lookup/{originalTransactionId}
```

Path Parameters

originalTransactionId	(Required) The original transaction identifier for a transaction that belongs to the customer.
<code>originalTransactionId</code>	

Response Codes

200 **OK**

`RefundLookupResponse` Request succeeded.

Content-Type: application/json

400

[InvalidOriginalTransactionIdError](#)

Bad Request

The request is invalid. Check the specific error message for further information.

Content-Type: application/json

401

Unauthorized

The JSON Web Token (JWT) in the authorization header is invalid. For more information, see [Generating JSON Web Tokens for API requests](#).

404

[OriginalTransactionIdNotFound](#)

Not Found

The request is invalid. Check the specific error message for further information.

Content-Type: application/json

429

[RateLimitExceededError](#)

Content-Type: application/json

500

[\(GeneralInternalError | GeneralInternalRetryableError\)](#)

Internal Server Error

The request failed. This may be due to a temporary outage. Check the specific error message for further information.

Content-Type: application/json

Mentioned in

 [App Store Server API changelog](#)

 [Identifying rate limits](#)

Discussion

Call this endpoint to get a customer's refund history for your app. The response ([RefundLookupResponse](#)) includes up to 50 of the customer's most-recently refunded transactions, based on the [revocationDate](#).

Note

To get the complete refund history, use [Get Refund History](#).

To call this endpoint, provide any original transaction identifier (originalID) for any of the customer's in-app purchases. The response only includes App Store-approved refunds for any product type: consumable, non-consumable, auto-renewable subscriptions, and non-renewing subscriptions. For more information about product types, see In-app purchase.

The information in the response is the same as the information in one or more REFUND notifications (notificationType) from App Store Server Notifications. Use this API to retrieve any refund notifications you may have missed, such as during a server outage.

A successful response may have an empty `signedTransactions` array if the customer hasn't received any App Store-approved refunds. To identify the date and reason code for a refund, see `revocationDate` and `revocationReason` in the JWSTransactionDecodedPayload.

The App Store Server API returns information based on the customer's in-app purchase history regardless of whether the customer installs, removes, or reinstalls the app on their devices.

See Also

Deprecated

~~Get Transaction History V1~~

Get a customer's in-app purchase transaction history for your app, except finished consumable in-app purchases.

Deprecated

~~object RefundLookupResponse~~

A response that contains an array of signed JSON Web Signature (JWS) transactions.

Deprecated