

□ Documentation

[App Store Server API](#) / Get Transaction Info

Web Service Endpoint

Get Transaction Info

Get information about a single transaction for your app.

App Store Server API 1.8+

URL

```
GET https://api.storekit.itunes.apple.com/inApps/v1/transactions/{transactionId}
```

Sandbox URL

```
GET https://api.storekit-sandbox.itunes.apple.com/inApps/v1/transactions/{transactionId}
```

Path Parameters

transactionId	(Required) The identifier of a transaction that belongs to the customer, and which may be an original transaction identifier (originalTransactionId).
----------------------	--

Response Codes

200 OK

TransactionInfo Response
Request succeeded.
Content-Type: application/json

400 **Bad Request**

**(InvalidTransaction
 IdError | App
 TransactionIdNot
 SupportedError)**
Invalid request.
Content-Type: application/json

401	Unauthorized
	The JSON Web Token (JWT) in the authorization header is invalid. For more information, see Generating JSON Web Tokens for API requests .
404	Not Found
TransactionIdNotFoundError	The transaction identifier wasn't found. Content-Type: application/json
429	The request exceeded the rate limit.
RateLimitExceededError	Content-Type: application/json
500	Internal Server Error
(GeneralInternalError GeneralInternalRetryableError)	Server error. Try again later. Content-Type: application/json

Mentioned in

- 📄 App Store Server API changelog
- 📄 Identifying rate limits

Discussion

Use this endpoint to get transaction information for any transaction identifier, including original transaction identifiers. This endpoint supports all in-app purchase types, including consumable, non-consumable, non-renewing subscriptions, and auto-renewable subscriptions. It also supports transactions that your app marked as finished using `finish()` or `finishTransaction(:)` in StoreKit.

See Also

Transaction information

object `TransactionInfoResponse`

A response that contains signed transaction information for a single transaction.