

[Accounts](#) / `ACErrorCode`

Structure

ACErrorCode

Codes for errors that may occur.

iOS 5.0+ | iPadOS 5.0+ | Mac Catalyst 13.0+ | macOS 10.8+

```
struct ACErrorCode
```

Topics

Errors

```
var ACErrorUnknown: ACErrorCode
```

Error code that indicates an unknown error occurred.

```
var ACErrorAccountMissingRequiredProperty: ACErrorCode
```

Error code that indicates an account wasn't saved because a required property is missing.

```
var ACErrorAccountAuthenticationFailed: ACErrorCode
```

Error code that indicates an account wasn't saved because authentication of its credential failed.

```
var ACErrorAccountTypeInvalid: ACErrorCode
```

Error code that indicates an account wasn't saved because its account type is invalid.

```
var ACErrorAccountAlreadyExists: ACErrorCode
```

Error code that indicates an account wasn't added because it already exists.

```
var ACErrorAccountNotFound: ACErrorCode
```

Error code that indicates an account wasn't deleted because it couldn't be found.

`var ACPERMISSION_DENIED: ACPERMISSION_DENIED`

Error code that indicates the operation failed because the application doesn't have permission to perform the operation.

`var ACPERMISSION_DENIED: ACPERMISSION_DENIED`

Error code that indicates the client's access info dictionary has incorrect or missing values.

`var ACPERMISSION_DENIED: ACPERMISSION_DENIED`

Error code that indicates the client doesn't have access to the requested data.

`var ACPERMISSION_DENIED: ACPERMISSION_DENIED`

Error code that indicates due to the current protection policy, the credentials couldn't be fetched.

`var ACPERMISSION_DENIED: ACPERMISSION_DENIED`

Error code that indicates no credentials were found.

`var ACPERMISSION_DENIED: ACPERMISSION_DENIED`

Error code that indicates the credentials couldn't be fetched from Keychain.

`var ACPERMISSION_DENIED: ACPERMISSION_DENIED`

Error code that indicates the credentials couldn't be stored in Keychain.

`var ACPERMISSION_DENIED: ACPERMISSION_DENIED`

Error code that indicates the credentials couldn't be removed from Keychain.

`var ACPERMISSION_DENIED: ACPERMISSION_DENIED`

Error code that indicates an account save failed because the account being updated has been removed.

`var ACPERMISSION_DENIED: ACPERMISSION_DENIED`

Error code that indicates the client making the request doesn't have a valid bundle ID.

`var ACPERMISSION_DENIED: ACPERMISSION_DENIED`

Error code that indicates a plugin prevented the expected action from occurring.

`var ACPERMISSION_DENIED: ACPERMISSION_DENIED`

Error code that indicates an error occurred while trying to save to a Core Data store.

`var ACPERMISSION_DENIED: ACPERMISSION_DENIED`

Error code that indicates an account's information couldn't be serialized.

`var ACErrorInvalidCommand: ACErrorCode`

Error code that indicates an invalid command was attempted.

`var ACErrorMissingTransportMessageID: ACErrorCode`

Error code that indicates an expected message identifier wasn't found while performing a command.

`var ACErrorCredentialItemNotFound: ACErrorCode`

Error code that indicates a credential item wasn't saved because it couldn't be found.

`var ACErrorCredentialItemNotExpired: ACErrorCode`

Error code that indicates a credential item wasn't removed because it hasn't yet expired.

Initializers

`init(UInt32)`

Initializes a new error code structure.

`init(rawValue: UInt32)`

Initializes a new error code structure.

Instance Properties

`var rawValue: UInt32`

The raw integer value of the error code.

Relationships

Conforms To

BitwiseCopyable

Equatable

Hashable

RawRepresentable

Sendable

See Also

Errors

`let ACErrorDomain: String`

The error domain for the Accounts framework.