

[EventKit](#) / [EKEventStore](#) / `remove(_:span:commit:)`

Instance Method

remove(_:span:commit:)

Removes an event or recurring events from the event store by either committing or batching the changes.

iOS 5.0+ | iPadOS 5.0+ | Mac Catalyst 13.1+ | macOS 10.8+ | visionOS 1.0+

```
func remove(
    _ event: EKEvent,
    span: EKSpan,
    commit: Bool
) throws
```

Parameters

event

The event to remove.

span

The span that indicates whether to remove a single event or all future instances of the event in the case of a recurring event.

commit

true to remove the event immediately; otherwise, the change is batched until the `commit()` method is invoked.

Mentioned in

 [Creating events and reminders](#)

Discussion

This method raises an exception if it's passed an event from another event store.

Handling Errors in Swift

In Swift, this method returns `Void` and is marked with the `throws` keyword to indicate that it throws an error in cases of failure. Call this method in a `try` expression and handle any errors in the catch clauses of a `do` statement, as described in [Error Handling in The Swift Programming Language](#) and [About Imported Cocoa Error Parameters](#).

See Also

Related Documentation

```
func commit() throws
```

Commits all unsaved changes to the event store.

Accessing calendar events

```
func event(withIdentifier: String) -> EKEvent?
```

Locates the first occurrence of an event with a given identifier.

```
func calendarItem(withIdentifier: String) -> EKCalendarItem?
```

Locates a reminder or the first occurrence of an event with the specified identifier.

```
func calendarItems(withExternalIdentifier: String) -> [EKCalendarItem]
```

Locates all reminders or the first occurrences of all events with the specified external identifier.

```
func remove(EKEvent, span: EKSpan) throws
```

Removes an event from the event store.

```
func remove(EKReminder, commit: Bool) throws
```

Removes a reminder from the event store by either committing or batching the changes.

```
func save(EKEvent, span: EKSpan) throws
```

Saves changes to an event permanently.

```
func save(EKEvent, span: EKSpan, commit: Bool) throws
```

Saves an event or recurring events to the event store by either committing or batching the changes.

```
func save(EKReminder, commit: Bool) throws
```

Saves changes to a reminder by either committing or batching the changes.