

□ Documentation

[Apple Pay Merchant Token Management API](#) / Update Merchant Metadata

Web Service Endpoint

Update Merchant Metadata

Update the merchant token's notification URL.

Apple Pay Merchant Token Management API 1.0.12+

URL

POST `https://apple-pay-gateway.apple.com/paymentservices/v1/merchantId/{merchantId}`

Path Parameters

merchantId string	(Required) The merchant identifier issued by Apple. Maximum length: 64
-----------------------------	--

Header Parameters

Accept string	The response format the client expects, for example, application/json for JSON.
Content-Type string	(Required) The format of the data sent in the request body, for example, application/json for JSON payloads.
x-request-id string	(Required) The header used to uniquely identify the request.

HTTP Body

UpdateMerchantMetadataRequest	The request body you use to specify the updated merchant metadata. Content-Type: application/json
---	--

Response Codes

200	OK
	Successful response.
400	Bad Request
ErrorResponse	Bad request. Content-Type: application/json
403	Forbidden
ErrorResponse	Authorization failed. Content-Type: application/json
404	Not Found
ErrorResponse	Resource not found. Content-Type: application/json
500	Internal Server Error
ErrorResponse	Internal server error. Content-Type: application/json

Discussion

The merchant server calls this API to update the value of a merchant token's token NotificationURL. This URL receives life-cycle and metadata update notifications from the Apple Pay servers about the Apple Pay merchant token.

See Also

Merchant token notification handling

-  Receiving and handling merchant token notifications
Implement an endpoint to receive and handle merchant token life-cycle updates from Apple Pay.

Send Merchant Token Event

Receive and handle merchant token life-cycle updates from Apple Pay.