

[Account Data Transfer](#) / Get recurring request status

## Web Service Endpoint

# Get recurring request status

Get the status of an instance of a recurring download request.

Account Data Transfer 1.0+

---

## URL

**GET** `https://accountdatatransfer.apple.com/api/transfer/accountdata/{parentRequestId}`

## Path Parameters

<b>parentRequestId</b> string	<b>(Required)</b> A UUID that identifies the series of recurring download requests.
<b>requestId</b> string	<b>(Required)</b> A UUID that identifies the individual request.

## Response Codes

<b>200</b> <a href="#">RequestStatus</a>	<b>OK</b> Content-Type: application/json
<b>400</b>	<b>Bad Request</b>
<b>401</b>	<b>Unauthorized</b>
<b>403</b>	<b>Forbidden</b>
<b>500</b>	<b>Internal Server Error</b>

# Overview

Request

Response

```
% curl -X GET \  
-H "Authorization: Bearer [ACCESS_TOKEN]" \  
-H "X-Apple-Transaction-Id: E3857B28-7FC4-41C8-AC54-08E121E26F59" \  
-H "Accept: application/json" \  
https://accountdatatransfer.apple.com/api/transfer/accountdata/EABD06C0-9210-47FF-
```

## See Also

### Status

Get one-time request status

Find the status of a one-time download request.

object RequestStatus

An object that represents the status of a download request.