

[App Store Server API](#) / Get App Transaction Info

Web Service Endpoint

Get App Transaction Info

Get a customer's app transaction information for your app.

App Store Server API 1.17+

URL

GET <https://api.storekit.itunes.apple.com/inApps/v1/transactions/appTransactions/{transactionId}>

Sandbox URL

GET <https://api.storekit-sandbox.itunes.apple.com/inApps/v1/transactions/appTransactions/{transactionId}>

Path Parameters

transactionId transactionId	(Required) Any originalTransactionId , transactionId or appTransactionId that belongs to the customer for your app.
---	--

Response Codes

200 AppTransactionInfoResponse	OK Request succeeded. Content-Type: application/json
400 InvalidTransactionIdError	Bad Request Invalid request. Content-Type: application/json
401	Unauthorized

The JSON Web Token (JWT) in the authorization header is invalid. For more information, see [Generating JSON Web Tokens for API requests](#).

404
([TransactionIdNotFound](#) | [AppTransactionDoesNotExist](#))

Not Found

Check the specific error message for further information.

Content-Type: application/json

429
[RateLimitExceeded](#)
[Error](#)

The request exceeded the rate limit. For more information, see [Identifying rate limits](#).

Content-Type: application/json

500
([GeneralInternalError](#) | [GeneralInternalRetryableError](#))

Internal Server Error

Server error. Try again later.

Content-Type: application/json

Mentioned in

 [App Store Server API changelog](#)

 [Identifying rate limits](#)

Discussion

Use this endpoint to get the app transaction information for a customer of your app. You can provide any transaction ID that belongs to the customer to get their app transaction information.

App transaction information represents the customer's purchase of the app, cryptographically signed by the App Store. The App Store generates a single, globally unique [appTransactionId](#) for each Apple Account that downloads your app and for each family group member for apps that support Family Sharing. The `appTransactionId` value remains the same for the same Apple Account and app if the customer redownloads the app on any device, receives a refund, repurchases the app, or changes the storefront. For apps that support Family Sharing, the `appTransactionId` is unique for each family group member.

App transaction information includes details about the app the customer purchased, such as its `bundleID`, original version, original purchase date, and more. You can also get app transaction information in your app from StoreKit, using [AppTransaction](#).

See Also

App Transaction information

`object` AppTransactionInfoResponse

A response that contains signed app transaction information for a customer.