

[Address Book](#) / `ABMultiValue`

Class

ABMultiValue

An immutable representation of a property that might have multiple values.

macOS

```
class ABMultiValue
```

Overview

Each value in a multivalue list must be of the same type, and must have an associated predefined or user-defined label, and unique identifier. The labels, however, need not be unique. For example, you can have multiple Home phone numbers. Each multivalue object may have a primary identifier—used as a default value when a label is not provided. For example, a person record may have multiple addresses with the labels Home and Work, where Work is designated as the primary value. Instances of this class are immutable, see [ABMutableMultiValue](#) for methods that manipulate the content of a multivalue list.

The `ABMultiValue` class is “toll-free bridged” with its procedural C opaque-type counterpart. This means that the [ABMultiValue](#) type is interchangeable in function or method calls with instances of the `ABMultiValue` class.

Topics

Accessing the primary identifier

```
func primaryIdentifier() -> String!
```

Returns the identifier for the primary value.

Accessing identifiers

```
func identifier(at: Int) -> String!
```

Returns the identifier for the given index.

```
func index(forIdentifier: String!) -> Int
```

Returns the index for the given identifier.

Accessing entries

```
func label(at: Int) -> String!
```

Returns the label for the given index.

```
func value(at: Int) -> Any!
```

Returns the value for the given index.

```
func value(forIdentifier: String!) -> Any!
```

Returns the value for the given identifier.

```
func label(forIdentifier: String!) -> Any!
```

Returns the label for the given identifier.

Querying the list

```
func count() -> Int
```

Returns the number of entries in a multivalue list.

```
func propertyType() -> ABPropertyType
```

Returns the type for the values in a multivalue list.

Relationships

Inherits From

NSObject

Inherited By

ABMutableMultiValue

Conforms To

CVarArg

CustomDebugStringConvertible

CustomStringConvertible

Equatable

Hashable

NSCopying

NSFastEnumeration

NSMutableCopying

NSObjectProtocol

See Also

Data Types

`class` `ABPerson`

An object that encapsulates all information about a person in the Address Book database.

`class` `ABGroup`

An object that represents a group of records in the Address Book database.

`class` `ABMutableMultiValue`

A mutable representation of a property that might have multiple values.

`protocol` `ABImageClient`

Methods for responding to a request to load images associated with a contact.

`class` `ABRecord`

An abstract class that defines the common properties for all Address Book records.