

[App Store Connect API](#) / Request reports

Web Service Endpoint

Request reports

Request analytics reports for your apps.

App Store Connect API 3.4+

URL

POST `https://api.appstoreconnect.apple.com/v1/analyticsReportRequests`

HTTP Body

[AnalyticsReport](#)
[RequestCreateRequest](#)

Content-Type: application/json

Response Codes

201

[AnalyticsReport](#)
[RequestResponse](#)

Created

Content-Type: application/json

400

[ErrorResponse](#)

Bad Request

Content-Type: application/json

401

[ErrorResponse](#)

Unauthorized

Content-Type: application/json

403

[ErrorResponse](#)

Forbidden

Content-Type: application/json

409

Conflict

[ErrorResponse](#)

Content-Type: application/json

422

Content-Type: application/json

[ErrorResponse](#)

429

[ErrorResponse](#)

Content-Type: application/json

Mentioned in

 [Downloading Analytics Reports](#)

Discussion

When making a request with this endpoint, the `accessType ONGOING` is most common and provides current data. This report request generates reports daily for each granularity: daily, weekly, and monthly. Use `ONE_TIME_SNAPSHOT` to get historical data.

Example Request and Response

Request Response

```
POST https://api.appstoreconnect.apple.com/v1/analyticsReportRequests
{
  "data": {
    "type": "analyticsReportRequests",
    "attributes": {
      "accessType": "ONGOING"
    },
    "relationships": {
      "app": {
        "data": {
          "type": "apps",
          "id": "1476097583"
        }
      }
    }
  }
}
```

See Also

Making, Reading, and Deleting Requests

Read report requests

Read analytics report requests for a specific app.

Read report request information

Get details for and the state of a specific analytics report request.

Read reports for a specific request

Get a list of reports generated from a specific analytics report request.

Read reports Ids for a specific request

Get a list of reports Ids from a specific analytics report request.

Delete a report request

Remove a specific analytics report request.