

[Video Subscriber Account](#) / [VSUserAccountManager](#) / deleteAutoSignInToken()

## Instance Method


# deleteAutoSignInToken()

Deletes the value of the current Automatic Sign-In token.

iOS 26.0+ | iPadOS 26.0+ | macOS 26.0+ | tvOS 26.0+ | visionOS 26.0+

```
func deleteAutoSignInToken() async throws
```

## Mentioned in

 Signing people in to their media accounts automatically

## Discussion

This method sets the contents of value to `nil` for the current autoSignInToken.

You might delete an Automatic Sign-In token, for example, if:

- Your app provides its own UI that lets the person opt out of Automatic Sign-In.
- The person changes their password and wants to sign out from all of their devices.
- Your app implements conditions to invalidate a token, such as if a person flags a specific log in as unauthorized.

## See Also

### Signing people in automatically

`struct AutoSignInToken`

A value that represents a person's account and their consent to Automatic Sign-In.

`struct AutoSignInTokenUpdateContext`

An object that contains information about a person's choice in the Automatic Sign-In prompt.

`enum AutoSignInAuthorization`

The possible states the framework sets for Automatic Sign-In.

`var autoSignInToken: VSUserAccountManager.AutoSignInToken`

The current Automatic Sign-In token.

`func requestAutoSignInAuthorization() async throws -> VSUserAccountManager.AutoSignInTokenUpdateContext`

Presents a modal sheet that offers a person to opt in to Automatic Sign-In.

`func updateAutoSignInToken(String, updateContext: VSUserAccountManager.AutoSignInTokenUpdateContext) async throws`

Sets the current Automatic Sign-In token.