

[AccessorySetupKit](#) / [ASDiscoveredAccessory](#)

## Class

# ASDiscoveredAccessory

A discovered accessory, for use in creating a customized picker display item.

iOS 26.1+ | iPadOS 26.1+

```
class ASDiscoveredAccessory
```

## Overview

When your app's picker uses the [filterDiscoveryResults](#) option, you receive [ASAccessoryEventType.accessoryDiscovered](#) events that contain this type. Use the discovered accessory's Bluetooth properties to create a new [ASDiscoveredDisplayItem](#), incorporating traits like a custom accessory name or a newly downloaded product image. You can then add this item to the picker to allow the person using the app to set up the accessory.

## Topics

### Working with accessory properties

```
var bluetoothAdvertisementData: [AnyHashable : Any]?
```

The Bluetooth advertisement data from the discovered accessory.

```
var bluetoothRSSI: Int?
```

The Bluetooth RSSI (Received Signal Strength Indicator) value from the discovered accessory.

---

# Relationships

## Inherits From

ASAccessory

## Conforms To

- CVarArg
- CustomDebugStringConvertible
- CustomStringConvertible
- Equatable
- Hashable
- NSObjectProtocol
- Sendable
- SendableMetatype

---

## See Also

### Accessory description

```
class ASAccessory
    An accessory discovered by the accessory session.

enum AccessoryState
    An enumeration of possible authorization states of an accessory.
```