

[Assignables](#) / AnonymousUserIdentity

Structure

AnonymousUserIdentity

A user identity for unknown editors.

iOS 17.4+ | iPadOS 17.4+ | Mac Catalyst 17.4+ | visionOS

```
struct AnonymousUserIdentity
```

Topics

Creating an anonymous identity

```
init()
```

Initializes an instance of `AnonymousUserIdentity`.

Inspecting an identity

```
var stringRepresentation: String
```

String representation of this user identity for display or debugging purposes.

```
var typeID: String
```

A unique type identifier for this user identity.

```
static var typeID: String
```

A unique type identifier for this user identity.

Relationships

Conforms To

Decodable
Encodable
Equatable
Hashable
Sendable
SendableMetatype
UserIdentity

See Also

Identity

`protocol` `UserIdentity`

Types conforming to this protocol can act as user identities for editors of a document.

`struct` `AnyUserIdentity`

A user identity that performs type erasure by wrapping another user identity.

`struct` `StringUserIdentity`

A user identity defined by a string.

`class` `UserIdentityTypeRegistry`

A registry for user identity types. Assignable documents and document elements store user identity data as `Data` objects. In order for that data to be deserialized, the type to deserialize it as needs to be known to `UserIdentityTypeRegistry`. Without registration of the user identity, custom types won't be deserializable.

`enum` `UserIdentityFactory`

A type that contains helpers for creating user identity objects.