

[Apple Music API](#) / Add resource to favorites

## Web Service Endpoint

# Add resource to favorites

Add the user's resource to favorites.

Apple Music 1.0+

---

## URL

**POST** `https://api.music.apple.com/v1/me/favorites`

## Query Parameters

<b>ids</b> [string]	<b>(Required)</b> The ids of the specific type.
<b>1</b> string	The localization to use, specified by a language tag. The possible values are in the <code>supportedLanguageTags</code> array belonging to the <code>Storefront</code> object that <code>storefront</code> specifies. Otherwise, the default is <code>defaultLanguageTag</code> in <code>Storefront</code> .

## Response Codes

<b>202</b> <a href="#">EmptyBodyResponse</a>	<b>Accepted</b> Request accepted. Content-Type: application/json
<b>401</b> <a href="#">UnauthorizedResponse</a>	<b>Unauthorized</b> A response indicating an incorrect Authorization header. Content-Type: application/json
<b>403</b> <a href="#">ForbiddenResponse</a>	<b>Forbidden</b> A response indicating invalid or insufficient authentication.

Content-Type: application/json

**500**  
**ErrorsResponse**

### **Internal Server Error**

A response indicating an error occurred on the server.

Content-Type: application/json

## Discussion

This endpoint allows the user to favorite a resource. For example, if a customer favorites a song, the song is added to their `favorite_songs` playlist. If they like an album or playlist, they can filter on `favorited_album` in their library view.

If successful, the HTTP status code is 202 (Accepted) and there's no response body. For requested IDs that the system can't add to a user's library, Apple Music Library ignores those IDs. If unsuccessful, the HTTP status code indicates the error and the details are in the `errors` array.

### Note

Bulk additions of heterogeneous types are permitted.