

[Accelerate](#) / [vDSP](#) / `threshold(_:to:with:)`

## Type Method

# threshold(\_:to:with:)

Returns the elements of the supplied double-precision vector after applying a specified thresholding rule.

iOS 13.0+ | iPadOS 13.0+ | Mac Catalyst | macOS 10.15+ | tvOS 13.0+ | visionOS | watchOS 6.0+

```
static func threshold<U>(  
    _ vector: U,  
    to lowerBound: Double,  
    with rule: vDSP.ThresholdRule<Double>  
) -> [Double] where U : AccelerateBuffer, U.Element == Double
```

## See Also

## Threshold Operations

```
static func threshold<U>(U, to: Float, with: vDSP.ThresholdRule<Float>)  
-> [Float]
```

Returns the elements of the supplied single-precision vector after applying a specified thresholding rule.

```
static func threshold<U, V>(U, to: Double, with: vDSP.ThresholdRule<  
Double>, result: inout V)
```

Calculates the elements of the supplied double-precision vector after applying a specified thresholding rule.

```
static func threshold<U, V>(U, to: Float, with: vDSP.ThresholdRule<  
Float>, result: inout V)
```

Calculates the elements of the supplied single-precision vector after applying a specified thresholding rule.

enum ThresholdRule

Constants that specify vector threshold rules.